

SELECT with various clause – BETWEEN, IN, Aggregate function

```
MySQL 8.0 Command Line Cli × + ∨

mysql> CREATE DATABASE SelectDemo;
Query OK, 1 row affected (0.01 sec)

mysql>
mysql> USE SelectDemo;
Database changed
mysql>
mysql> CREATE TABLE Student (
  -> ID INT,
  -> Name VARCHAR(30),
  -> Age INT,
  -> Marks INT
  -> );
Query OK, 0 rows affected (0.04 sec)

mysql>
mysql> INSERT INTO Student VALUES
  -> (1, 'Arun', 20, 80),
  -> (2, 'Bala', 21, 65),
  -> (3, 'Charan', 19, 90),
  -> (4, 'Divya', 22, 75),
  -> (5, 'Kiran', 20, 85);
Query OK, 5 rows affected (0.01 sec)
Records: 5 Duplicates: 0 Warnings: 0

mysql>
mysql> SELECT * FROM Student;
+----+-----+-----+-----+
| ID | Name  | Age  | Marks |
+----+-----+-----+-----+
| 1  | Arun  | 20   | 80    |
| 2  | Bala  | 21   | 65    |
| 3  | Charan| 19   | 90    |
| 4  | Divya | 22   | 75    |
| 5  | Kiran | 20   | 85    |
+----+-----+-----+-----+
5 rows in set (0.00 sec)

mysql>
mysql> SELECT * FROM Student
  -> WHERE Marks BETWEEN 70 AND 90;
+----+-----+-----+-----+
| ID | Name  | Age  | Marks |
+----+-----+-----+-----+
| 1  | Arun  | 20   | 80    |
| 3  | Charan| 19   | 90    |
| 4  | Divya | 22   | 75    |
| 5  | Kiran | 20   | 85    |
+----+-----+-----+-----+
4 rows in set (0.00 sec)

mysql>
mysql> SELECT * FROM Student
  -> WHERE ID IN (1, 3, 5);
+----+-----+-----+-----+
| ID | Name  | Age  | Marks |
+----+-----+-----+-----+
| 1  | Arun  | 20   | 80    |
| 3  | Charan| 19   | 90    |
| 5  | Kiran | 20   | 85    |
+----+-----+-----+-----+
3 rows in set (0.00 sec)

mysql>
mysql> SELECT COUNT(*) AS Total_Students
  -> FROM Student;
+-----+
| Total_Students |
+-----+
| 5              |
+-----+
1 row in set (0.01 sec)
```



```
mysql> SELECT * FROM Student  
-> WHERE ID IN (1, 3, 5);
```

ID	Name	Age	Marks
1	Arun	20	80
3	Charan	19	90
5	Kiran	20	85

3 rows in set (0.00 sec)

```
mysql>  
mysql> SELECT COUNT(*) AS Total_Students  
-> FROM Student;
```

Total_Students
5

1 row in set (0.01 sec)

```
mysql>  
mysql> SELECT MAX(Marks) AS Highest_Marks  
-> FROM Student;
```

Highest_Marks
90

1 row in set (0.00 sec)

```
mysql>  
mysql> SELECT MIN(Marks) AS Lowest_Marks  
-> FROM Student;
```

Lowest_Marks
65

1 row in set (0.00 sec)

```
mysql>  
mysql> SELECT AVG(Marks) AS Average_Marks  
-> FROM Student;
```

Average_Marks
79.0000

1 row in set (0.00 sec)

```
mysql>  
mysql> SELECT SUM(Marks) AS Total_Marks  
-> FROM Student;
```

Total_Marks
395

1 row in set (0.00 sec)

```
mysql> |
```