
Question 2: Prepare a CI/CD workflow report describing the pipeline architecture, stages, automation results, and observations with supporting screenshots.

Executed on Ubuntu 24.04 LTS (WSL2) by Meenakshi Rakesh. Repository: https://github.com/meenakshi16rp/Devops-lab-1-

1. Pipeline architecture



- Source control: GitHub repository Devops-lab-1- (main branch) owned by meenakshi16rp; the developer pushes commits with a feature-branch workflow.
- Automation trigger: Jenkins polls the repository every 5 minutes (H/5 * * * *). When new commits are found the pipeline starts on its own - no manual build step.
- CI/CD engine: Jenkins 2.580.2 LTS with a declarative pipeline (Jenkinsfile) checked out from the same repository - the pipeline itself is version controlled.
- Target: the built application is deployed to a local deployment directory and served on port 5000; the pipeline verifies the health endpoint before declaring success.

2. Pipeline stages


Stage	What it does	Tool / command	Result
Checkout SCM	Jenkins fetches the Jenkinsfile from main	Git + github-creds	1 s, OK
Checkout	Pulls source code of the latest commit	checkout scm	1 s, OK
Build	Creates a Python virtual environment and installs dependencies	python3 -m venv + pip install -r app/requirements.txt	8 s, OK
Test	Runs the unit test suite	pytest app/tests -v (3 tests)	0.75 s, OK
Deploy	Copies the app to the deploy directory, (re)starts it, verifies health	./deploy/deploy.sh + curl :5000/health	2 s, OK
Post Actions	Success/failure notification echo; workspace cleanup	post + cleanWs()	0.38 s, OK


3. Automation results


Build	Trigger	Commit	Result	Duration
#1	Manual (first run)	eedda81	FAILURE (Deploy stage)	30.6 s
#2	Manual (after fix)	c9df47c	SUCCESS	18.7 s
#3	Automatic - Started by an SCM change	eaa01d3	SUCCESS	18.3 s


- All three unit tests (index, health, info) pass in every successful build.
- The deployed application answers /health with {"status":"UP"} and /info reports author Meenakshi and the Jenkins declarative CI/CD pipeline.

4. Evidence









5. Observations

- Pipelines-as-code made the whole workflow reproducible: recreating the job only requires pointing Jenkins at the repository.
- The first run failed exactly where an undebugged script typically fails (deployment environment); the console log pinpointed the missing Flask module within seconds - a good demonstration of why each stage should fail fast.

- Poll SCM is a simple, reliable trigger for environments where GitHub cannot reach the Jenkins host for webhooks (the WSL2 lab is not publicly reachable).
- Cleanup (cleanWs) in the post section keeps the workspace small across builds.