Source: https://cam.feedzai.com/ds-studio-ds-api/25.0/reference/exploration/utils/

# utils Â¶

## friendly_type Â¶

```
friendly_type(datatype) -> str
```

Checks if the given pyspark datatype matches any of the supported types.

Parameters:

| Name | Type | Description | Default |
|---|---|---|---|
| **`datatype`** Â¶ | | pyspark dataType. | *required* |

Returns:

| Type | Description |
|---|---|
| `str` | friendly type ('numerical', 'timestamp', 'string', 'unsupported'). |

## get_pyspark_column_type Â¶

```
get_pyspark_column_type(df, column_name)
```

Returns the type of a column with a given name in a Pyspark dataframe

Parameters:

| Name | Type | Description | Default |
|---|---|---|---|
| **`df`** Â¶ | | PySpark dataframe | *required* |
| **`column_name`** Â¶ | | String containing the name of the column to get the type | *required* |

Returns:

| Type | Description |
|---|---|
| `unknown` | a string with the data type of the column with column_name. If the column does not exist in the dataframe, does not return anything. |

## is_finite_col Â¶

```
is_finite_col(c: Column) -> Column
```

Column expression: not null, not NaN, not infinite.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `c` Â¶ | `Column` | The numerical column to evaluate. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `Column` | A BooleanType Column expression that evaluates to True only for finite, non-null numerical values. |

## is_finite_number Â¶

```
is_finite_number(num)
```

Checks if num is a finite number.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `num` Â¶ | | any object. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if num is a finite number. |

## is_number Â¶

```
is_number(num)
```

Checks if num is a number.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `num` Â¶ | | any object. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if num is a number (int, float). |

## is_pandas_categorical Â¶

```
is_pandas_categorical(datatype)
```

Checks if the given pandas datatype matches our supported categorical types.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `datatype` Â¶ | | pandas data type. This is a numpy.dtype and can be found with df[].dtype. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if matches supported categorical types, False otherwise. |

## is_pandas_numerical Â¶

```
is_pandas_numerical(datatype)
```

Checks if the given pandas datatype matches our supported numerical types.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `datatype` Â¶ | | pandas data type. This is a numpy.dtype and can be found with df[].dtype. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if matches supported numerical types, False otherwise. |

## is_pandas_timestamp Â¶

```
is_pandas_timestamp(datatype)
```

Checks if the given pandas datatype matches our supported timestamp types.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `datatype` Â¶ | | pandas data type. This is a numpy.dtype and can be found with df[].dtype. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if matches supported timestamp types, False otherwise. |

## is_pyspark_numerical Â¶

```
is_pyspark_numerical(datatype)
```

Checks if the given pyspark datatype matches our supported numerical types.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `datatype` Â¶ | | pyspark dataType. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if matches supported numerical types, False otherwise. |

## is_pyspark_string Â¶

```
is_pyspark_string(datatype)
```

Checks if the given pyspark datatype matches our supported string types.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `datatype` Â¶ | | pyspark dataType. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if matches supported string types, False otherwise. |

## is_pyspark_supported_type Â¶

```
is_pyspark_supported_type(datatype)
```

Checks if the given pyspark datatype matches any of the supported types.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `datatype` Â¶ | | pyspark dataType. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if matches supported types, False otherwise. |

## is_pyspark_timestamp Â¶

```
is_pyspark_timestamp(datatype)
```

Checks if the given pyspark datatype matches our supported timestamp types.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `datatype` Â¶ | | pyspark dataType. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if matches supported timestamp types, False otherwise. |

## is_string Â¶

```
is_string(x)
```

Checks if x is a string.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `x` Â¶ | | any object. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if x is a string. |

## is_string_pair Â¶

```
is_string_pair(x)
```

Checks if x is a pair of strings.

Parameters:

| Name | Type | Description | Default |
| --- | --- | --- | --- |
| `x` Â¶ | | any object. | *required* |

Returns:

| Type | Description |
| --- | --- |
| `unknown` | True if x is a tuple (string, string). |

## print_with_timestamp Â¶

```
print_with_timestamp(text)
```