

On this page

Map

Properties¹

title	String	Yes	118n key to the map title.
cssClass	String	Yes	Map CSS classes, separated by space.
headerClassName	String	Yes	Map header class names, separated by spaces.
markers	Array<Object>	Yes	List of markers that should appear on the map. Each item must be an object with these properties .
height	String	Yes	Map minimum height. It can be any valid CSS height value. Default value: "350px" E.g. "100px", "20%", "calc(100%-20px)",
defaultCenter	Object	Yes	Default map center. This object must have the following properties: • lat (number) - Latitude of the map center position. • lon (number) - Longitude of the map center position. Note: This property is only used when there are not markers.
defaultZoom	Number	Yes	Default zoom. If the configured defaultZoom is smaller (furthest from Earth) than the actual zoom calculated from the visible markers, the defaultZoom is assumed.
name	String	Yes ¹	A unique identifier representing the widget.
resource	String	Yes	Resource name that points to the endpoint that populates the widget. Supports template data type to format the URL.
filter	String	Yes	Filter for the external resource. Supports template data type to format the string.
orderBy	String	Yes	OrderBy for the external resource. Supports template data type to format the string.
limit	Number	Yes	Limits the number of results for the external resource.

¹ Mandatory if **resource** is present.

markers¹

keyLat	String	Yes	Data object key to look for the latitude value.
keyLon	String	Yes	Data object key to look for the longitude value.
cssClass	String	Yes	Marker CSS classes, separated by spaces.
iconPath	String	Yes	Path to a custom icon. It can be either an URL or a relative path to a local file.