

On this page

Linked Alerts

Properties

title	String	No	l18n key to the widget title.
cssClass	String	Yes	Widget custom class names, separated by space.
checkboxLabel	String	Yes	l18n key to the checkbox label.
name	String	No	A unique identifier representing the widget. It is a mandatory prop if resource is present.
resource	String	No	Resource name that points to the endpoint that populates the widget. Supports template data type to format the URL.
filter	String	Yes	Filter for the external resource. Supports template data type to format the string.
orderBy	String	Yes	OrderBy for the external resource. Supports template data type to format the string.
limit	Number	Yes	Limits the number of results for the external resource.
tableConfiguration	Object	No	Table configuration which supports these properties .

tableConfiguration

Same as the [Table](#) widget, except for the *title*, *key*, *cssClass* and *selectConfiguration* properties that are not necessary.

Additionally, you can configure bulk and inline actions using the following properties:

inlineActions	Array<Object>	Yes	List of inline actions that will be mapped into small button icons and be placed in each table row. Each action will only take effect on a specific item. Each inline action must be an object with these properties .
bulkActions	Array<Object>	Yes	Configures the bulk actions. Please check the Alert Button List section to see the available properties.

channels

The channels property lets you define in what events this widget will be displayed, for the event displayed the component will fetch the specific channel configuration. For each channel you have to define a specific table configuration.