

On this page

Action Button List

Properties

tooltipsPlacement	String	Yes	Tooltips placement. It can be one of: ['left','right','top','bottom', 'topLeft', 'topRight', 'bottomLeft', 'bottomRight']. Default: "top"
numberVisibleActions	Number	Yes	Number of visible actions. If the number of visible actions is less than the total number of actions, the remaining ones will be inside a drop down list. Default: 1
actions	Object[]	Yes	List of actions that will be mapped to buttons, where each button can perform a certain action over a set of alerts. Each action must be an object with these properties.
dropDown	Object	Yes	Configures the drop down button. Check its available properties.
channels	Object	Yes	If available, the actions being configured here will only be available to the channels specified as key of this property. If this property isn't present, the actions will be visible to all events from all channels. For each key (that must match a channelId), the value should be an object. The object should be left empty if you want to keep the other properties already configured. If there is a need to override one of the other properties for that channel, you can add those properties to the object with the desired value. Example 1 - Actions that are only available for channels aml and open_banking <pre>{ "numberVisibleActions": 0, "dropDown": { "button": { "iconCssClass": "icon-more", "showIcon": true }, "kind": "primary", "position": "bottom right" }, "actions": [...], }</pre>

```
"channels": {  
  
    "aml": {},  
  
    "open_banking": {}  
  
}  
  
}
```

Example 2 - Actions that are only available for channels aml and open_banking, but where only a small subset of actions is available to the channel aml.

```
{  
  
    "numberVisibleActions": 0,  
  
    "dropDown": {  
  
        "button": {  
  
            "iconCssClass": "icon-more",  
  
            "showIcon": true  
  
        },  
  
        "kind": "primary",  
  
        "position": "bottom right"  
  
    },  
  
    "actions": [...],  
  
    "channels": {  
  
        "aml": {  
  
            "actions": [ ... ] // for this channel,  
this will be the final set of actions instead of the ones defined  
in the global scope  
  
        },  
  
        "open_banking":  
  
    }  
  
}
```

If you are configuring a Case Manager without multiple channels, this property isn't required.

This property is only applied to the actions configured in the event details page, in the top bar.

Actions

title	String	No	Button label
type	String	No	The action type. Currently, we only support the following type of actions: • state - Action to change the alert state • move-to-queue - Action to move a set of alerts to a queue • assign-to-user - Action to assign a user to a set of alerts • assign-to-me - Action to assign an event to the logged user (only available in details page) • change-reasons - Action to change the alerts reasons without changing its state • extension - Custom action to be executed (requires an action property) • note-case - Action to add a note to a case. This should only be added in the Case Details page. • link-event-case - Action to link events to cases. This can be added to a table of Events, or to the Event Details page actions. • unlink-event-case - Action to unlink events from a case. This can only be added in the Link Events table of the Case Details Page. • upload-docs - Action to upload documents and link them to a case. This should only be added in the Case Details page. • decision-score-card - Action to open the decision score card wizard. • case-states - Action to change the state of a case. It required an extra config property. This should only be added in the Case Details page. • change-access-group - Action to change the access group of the event. • link-to - action to navigate to a custom link ◦ require permission : cm:action:link-to ◦ resource property is required to use this action • reveal-all - Action that allows the users to unlock all fields for a given Event. This action is only meant to be used in Event Tables and as an inline action.
action	String	No	The name of the custom action to be executed. Note: This property is only required when defining an action of type "extension"
entityType	String	No	A string to be sent to the extension action representing the entity where it was triggered. Note: This property is only required when defining an action of type "extension"
statusId	String	No	The alert status unique identifier assigned to this action. Note: This property is only required when defining an action of type "state"
cssClass	String	Yes	Custom CSS classes, separated by space.
iconCssClass	String	Yes	Icon CSS class to give the action button an icon.
tooltip	String	Yes	l18n key to the message to appear in the tooltip for this action.
kind	String	Yes	Button kind [Ã defaultÃ , primary, danger, warning, success, info]
config	Object	Yes	Additional configuration, depending on the action type. Please check the section "config for Action buttons" below.
skipDialog	Boolean	Yes	Whether the dialog should be skipped when performing the action.

			<i>Note: This property is only available for the action of type <code>state</code> and <code>decision-score-card</code>. By default, it is set to <code>false</code>.</i>
permissions	Array<String>	Yes	Holds a set of permissions the user must have in order to see and act over the action being configured here. The permissions added in this property are a complement to the permission <code>"cm:action::create:*"</code>. This means that you don't need to add that permission to this set, because it will be evaluated anyway. Example For the following inline action configuration: <pre>{ type: "state", statusId: "fraud", permissions: ["cm:channels:aml:create:*"] },</pre> The user must have the following permissions in order to see that action: <code>"cm:action:state:create:*"</code>, <code>"cm:channels:aml:create:*"</code>
confirmationDialog (since 10.0.0)	Object	Yes	Holds the configuration for prompting a confirmation dialog before action execution. (This configuration is only available for custom actions, i.e. <code>action</code> property is defined) The object can have the following properties: • titleLabel (String) - i18n key that represents the dialog title. • messageLabel (String) - i18n key that represents the dialog message. • submitButtonLabel (String) - i18n key that represents the submit button text. • cancelButtonLabel (String) - i18n key that represents the cancel button text. All these properties are <i>optional</i> and will fallback to the following i18n keys, if they were not configured: • titleLabel - <code>dialog.confirmation.title</code> • messageLabel - <code>dialog.confirmation.message</code> • submitButtonLabel - <code>button.submit</code> • cancelButtonLabel - <code>button.cancel</code>
newTab (since 10.0.0)	Boolean	Yes. Defaults to <code>false</code>	On <code>link-to</code> action type is possible to open a link to a new tab or in the current tab • true - will open the link in new tab • false (Default) - will open in the current tab
resource (since 10.0.0)	String	No. (link-to action is required)	To open a new link in <code>link-to</code> action-type define a template link in this property . edit case example (link-to) For the following inline link-to action configuration:

			<pre>{ "type": "link-to", "iconCssClass": "icon-note", "kind": "primary", "title": "edit-case", "resource": "/case/{{id}}/edit?timestamp={{createdAt}} &channelId={{channelId}}", "newTab": false }</pre>
--	--	--	---

Configuration for Action Buttons [↗](#)

Action type: "case-states" [↗](#)

states	Array<18n keys>	No	Holds the possible states associated with the button. The states should be 18n keys. It should also be states that were configured in the Core Configuration. If you add a state that wasn't configured there, CM will ignore it.
alwaysOpenModal	Boolean	Yes. Defaults to <i>false</i>	When there is only 1 possible state, this property indicates if the modal should still open or not. This allows the user to insert a note. If this property is set to false, when the user clicks on the button the state will be immediately changed, without opening the modal. This property is not needed when there are multiple states configured, because in that case the modal will always open, because the user is required to choose one state.

dropdown [↗](#)

position	String	Yes	Defines the Dropdown content position when opened. It accepts both vertical (top, bottom) and horizontal (left, right) alignments and they must be separated by a space. E.g: "top left", "top", "left", ...
cssClass	String	Yes	Custom class names, separated by spaces
kind	String	Yes	Dropdown kind [default , primary, danger, warning, success, info]
button	Object	No	Defines the dropdown trigger button appearance. Check the properties within button .
showArrowIcon	Boolean	Yes	Whether to show an arrow icon on the right side of the dropdown trigger button.

button [↗](#)

title	String	(Optional) Trigger button title.
cssClass	String	(Optional) Custom CSS classes, separated by spaces.
iconCssClass	String	(Optional) Icon CSS class to give the trigger button an icon.
showIcon	Boolean	(Optional) Whether the trigger button shows an icon or not.
pullIconRight	Boolean	(Optional) Whether the trigger button icon appears on the right or not.
isDisabled	Boolean	(Optional) Whether the trigger button is disabled or not
kind	String	(Optional) Dropdown kind [default , primary, danger, warning, success, info]