

On this page

List Box

box	Object Array<Object>	No	Can be one single box configuration (Object) or a multiple box configuration (Array<Object>). When using a single configuration, the schema is the same as Box widget. When using multiple configurations, you should provide an extra field in each box schema, named matchingFields (please check the below description for more info about this property).
key	String	No	Path in the event object to get the value to populate this widget.
title	String	Yes	I18n message key to the list box title.
cssClass	String	Yes	Custom CSS classes, separated by space.
name	String	Yes ¹	A unique identifier representing the widget.
resource	String	Yes	Resource name that points to the endpoint that populates the widget. Supports template data type to format the URL.
filter	String	Yes	Filter for the external resource. Supports template data type to format the string.
orderBy	String	Yes	OrderBy for the external resource. Supports template data type to format the string.
limit	Number	Yes	Limits the number of results for the external resource.

¹ Mandatory if **resource** is present.

matchingFields

Type	Optional	Description
Array<Object>	Yes	This property should be added to the Box schema when providing multiple configurations to the List Box widget. The goal of providing multiple configurations is to give the possibility to conditionally configure boxes based on the data being presented. Each object in this property should have the properties key and value, where key is the path in the data object to fetch a value and the value is the value that should be in that path. In order to a box configuration to be applied, all the items in this property should match. If several box configurations are provided, the first that matches all the fields is the one that will be used. If this property is no present, then it will always evaluate to false when trying to match the fields.