

On this page

Box

Properties¹

fields	Array<Object>	No	List of fields to be displayed in the Box. Each item is an object that can have these properties .
title	String	Yes	118n key to the message to show in the box title.
cssClasses	String	Yes	Box custom CSS classes, separated by space.
fieldsPerRow	String	Yes	Number of fields displayed per row. Default: 1.
headerClassName	String	Yes	Box header custom classes, separated by space.
rowClassName	String	Yes	Custom classes, separated by space, for each Box row.
groupClassName	String	Yes	Custom classes, separated by space, for each Box field.
name	String	Yes ¹	A unique identifier representing the widget.
resource	String	Yes	Resource name that points to the endpoint that populates the widget. Supports template data type to format the URL.
filter	String	Yes	Filter for the external resource. Supports template data type to format the string.
orderBy	String	Yes	OrderBy for the external resource. Supports template data type to format the string.
limit	Number	Yes	Limits the number of results for the external resource.
noBorder	Boolean	Yes. Default: false	If set to true, the widget won't have any border.
headerPill	Object	No	• kind (string) - Specifies the color of the Pill. Can be one of the following: <code>default</code>, <code>primary</code>, <code>success</code>, <code>warning</code>, <code>danger</code> • icon (string number) - The classname of the icon to be used: Please refer to Font Awesome to see the available icons. Please note that Case Manager only imports the light version icons. • type (string number) - Field data type. Please check the Data Types section for more info about the available data types. • matchingFields (string number) - Holds the list of fields that should match for the widget to appear. For more details about this property, read the matchingFields section.

¹ Mandatory if **resource** is present.

fields^â

Property	Type	Optional	Description
title	String	Yes	I18n key of the message that represents the field title.
titleTooltip	String	No	I18n key of the message that represents the field title tooltip.
type	String	No	Field data type. Please check the Data Types section for more info about the available data types.
key	String	No	Path to fetch the value in the data object. When configuring a field of type template or custom, it is not required to provide a path to a data object property, but instead you can provide any string you like.
cssClass	String	Yes	Custom CSS classes, separated by space, to add to the element that wraps the field.
dynamicCssClassKey	String	Yes	Contains a key to the data object. If present, it will add a CSS class with the cell key and the value of the key passed in this property. The CSS class will have the following template: <code>fdz-css-{key}-{data[dynamicCssClassKey]}</code> .
fieldTooltip	Object	Yes	Configures a tooltip in the field value. The object can have the following properties: • key (String) - Path to fetch the value in the data object, to show in the tooltip. • type (String) - Tooltip value type. Please check the Data Types section for more info about the available data types.
linkIcons	Array<Object>	Yes	List of link icons to be added to the field. Each item must be an object with these linkicon properties .
inlineActions	Array<Object>	Yes	List of field inline actions. Each object on the list can have the following properties: • key (String) - Path to fetch the value in the data object. • type (String) - Action type. Currently, the only action type supported is "copy-to-clipboard". • title (String) - Value used to build the action tooltip.
valueCssClass	String	Yes	Custom CSS classes, separated by space, to be added to the field value.
titleCssClass	String	Yes	Custom CSS classes, separated by space, to be added to the field title.
fieldLinkUrl	String	Yes	URL to where the box field should point to. You can pass a simple string or you can use a string with the same format as the one used in the template data type.
openInNewTab	Boolean	Yes	Whether the URL, associated with the field, should open in a new tab or not.
externalLink	Boolean	Yes	Whether the URL is internal or external.
permissions	string Array<string>	Yes	Specifies the necessary user permissions to view this field. When passing a list of permissions, the user must have all the permissions in order to view the field.

linkIcons (Extensions)^â

Property	Type	Description
iconCssClass	String	Icon CSS class to give the link an icon.
action	String	The name of the external action to be executed.
tooltipKey	String	I18n key to the message to show in the tooltip.
entityType	String	A string to be sent to the extension action representing the entity where it was triggered.

Property	Type	Description
<code>data</code>	<code>Object</code>	Represents a Context and it is not mandatory.
<code>matchingFields</code> (since 4.2.3)	<code>Array<Object></code>	Holds the list of fields that should match for the widget to appear. For more details about this property, read the matchingFields section.
<code>confirmationDialog</code> (since 10.0.0)	<code>Object</code>	Holds the configuration for prompting a confirmation dialog before action execution. The object can have the following properties: • titleLabel (String) - i18n key that represents the dialog title. • messageLabel (String) - i18n key that represents the dialog message. • submitButtonLabel (String) - i18n key that represents the submit button text. • cancelButtonLabel (String) - i18n key that represents the cancel button text. All these properties are optional and will fallback to the following i18n keys, if they were not configured: • titleLabel - <i>dialog.confirmation.title</i> • messageLabel - <i>dialog.confirmation.message</i> • submitButtonLabel - <i>button.submit</i> • cancelButtonLabel - <i>button.cancel</i>