

On this page

Paginated Widget

This Widget structure is identical to Box Widget. The main difference is that it receives a resource from where it will fetch the data to show.

Properties

fields	Array<Object>	No	List of fields to be displayed in the Box. Each item is an object that can have these properties .
resource	string	No	Resource of the paginated widget, it can be something like <code>/resource/{{id}}?timestamp={{createdAt}}</code>
title	String	Yes	l18n key to the message to show in the box title.
cssClass	String	Yes	Box custom CSS classes, separated by space.
fieldsPerRow	String	Yes	Number of fields displayed per row. Default: 1.
headerClassName	String	Yes	Box header custom classes, separated by space.
rowClassName	String	Yes	Custom classes, separated by space, for each Box row.
groupClassName	String	Yes	Custom classes, separated by space, for each Box field.
name	String	Yes ¹	A unique identifier representing the widget.
resource	String	Yes	Resource name that points to the endpoint that populates the widget. Supports template data type to format the URL.
filter	String	Yes	Filter for the external resource. Supports template data type to format the string.
orderBy	String	Yes	OrderBy for the external resource. Supports template data type to format the string.
limit	Number	Yes	Limits the number of results for the external resource.
noBorder	Boolean	Yes. Default: false	If set to true, the widget won't have any border.

¹ Mandatory if **resource** is present.

fields

title	String	Yes	l18n key to the message that represents the field title.
type	String	No	Field data type. Please check the Data Types section for more info about the available data types.
key	String	No	Path to fetch the value in the data object. When configuring a field of type template or custom, it is not required to provide a path to a data object property, but instead you can provide any string you like.
cssClass	String	Yes	Custom CSS classes, separated by space, to add to the element that wraps the field.
dynamicCssClassKey	String	Yes	

			Contains a key to the data object. If present, it will add a CSS class with the cell key and the value of the key passed in this property. The CSS class will have the following template: <code>fdz-css-{key}-{data[dynamicCssClassKey]}</code> .
fieldTooltip	Object	Yes	Configures a tooltip in the field value. The object can have the following properties: • key (String) - Path to fetch the value in the data object, to show in the tooltip. • type (String) - Tooltip value type. Please check the Data Types section for more info about the available data types.
linkIcons	Array<Object>	Yes	List of link icons to be added to the field. Each item must be an object with these linkicon properties .
valueCssClass	String	Yes	Custom CSS classes, separated by space, to be added to the field value.
titleCssClass	String	Yes	Custom CSS classes, separated by space, to be added to the field title.
fieldLinkUrl	String	Yes	URL to where the box field should point to. You can pass a simple string or you can use a string with the same format as the one used in the template data type.
openInNewTab	Boolean	Yes	Whether the URL, associated with the field, should open in a new tab or not.
externalLink	Boolean	Yes	Whether the URL is internal or external.
permissions	string Array<string>	Yes	Specifies the necessary user permissions to view this field. When passing a list of permissions, the user must have all the permissions in order to view the field.

linkIcons

iconCssClass	String	Icon CSS class to give the link an icon.
url	String	Link to where the icon points to. Note: This URL supports a string template, where the values inside {} are replaced by the correspondent values. E.g. " https://www.facebook.com/search/top?q=&#123;&#123;enrichers.customer.email&#125;&#125; ;"
tooltipKey	String	l18n key to the message to show in the tooltip.
openInNewTab	Boolean	Whether the URL, associated with the icon, should open in a new tab or not.
externalLink	Boolean	Whether the URL is internal or external.
matchingFields (since 4.2.3)	Array<Object>	Holds the list of fields that should match in order to the widget to appear. For more detail about this property, see matchingFields .

linkIcons (Extensions)

iconCssClass	String	Icon CSS class to give the link an icon.
action	String	The name of the external action to be executed.
tooltipKey	String	l18n key to the message to show in the tooltip.
entityType	String	A string to be sent to the extension action representing the entity where it was triggered.
data	Object	Represents a Context and it is not mandatory.

matchingFields (since 4.2.3)	Array<Object>	Holds the list of fields that should match in order to the widget to appear. For more detail about this property, see matchingFields .
---------------------------------	---------------	--