

On this page

PB Delegate

As of version 2.8.0 we have introduced a set of changes to make the PB Delegate use case ready for use, to allow a customer to delegate another customer to make payments on their behalf.

This page focuses on explaining the changes made to both Pulse and Case Manager to support this feature.

Pulse API Changes

In this section you can find a description of the API changes to support this feature.

All of the fields described in this section were also added to the `Payments` and `Payments + Outcomes` schemas to allow events to be enriched when received by Pulse and also to enable them to be used in the fraud strategy.

Channel fields

As described in the [2.8.0 Release Notes](#) we have added a set of new fields to Pulse Transfers and Digital Activity APIs.

Please find below a list of the new added fields:

Field Name	Datatype	Endpoints
delegate_id	String	Transfers & Digital Activity
delegate_initiated	Boolean	Transfers & Digital Activity
approver_id	String	Transfers & Digital Activity
transaction_id	String	Transfers & Digital Activity
account_holder_customer_id	String	Transfers & Digital Activity

Reference Data fields

The Reference Data API was also changed with the addition of the following fields:

Field Name	Datatype	Description
delegate_of	List of Objects	List of delegate ids (their customer id in HSBC) and the date when the delegate was assigned
delegates	List of Objects	List of customers whom the customer serves as a delegate

Each entry of `delegate_of` and `delegates` has the following fields:

Field Name	Datatype
customer_id	String
date_added	Long

In the below snippet you can find an example of customer data that acts as a delegate for two different customers:

```
{
  "delegate of": [
    {
      "customer_id": "customer_id_1",
      "date_added": 1603207359060
    },
    {
      "customer_id": "customer_id_2",
      "date_added": 1603207359060
    }
  ]
}
```

```

{
  "customer_id": "customer_id_2",
  "date_added": 1603207359061
}
]
}

```

Copy

A customer can have multiple delegates and a single delegate can also represent multiple customers. The following example illustrates a scenario where a customer has more than one delegate acting on their behalf:

```

{
  "delegates": [
    {
      "customer_id": "customer_id_3",
      "date_added": 1603207359060
    },
    {
      "customer_id": "customer_id_4",
      "date_added": 1603207359061
    }
  ]
}

```

Copy

Case Manager

Similarly to Pulse, we also made changes to Case Manager in order to support this feature. In this section you can find a description of the changes.

Event Details Page

In the Event Details Page we have created a new field mapping (`By Delegate`) linked to the delegate id that acted on behalf of a customer, added to the following widgets:

- Transfers `Transaction` widget
- Digital Activity `Event Summary` widget

In the same page, the `Transaction History` widget now features a new Delegate CIN column and filter.



note

In order for an event to appear when filtering by `Delegate CIN`, the `customer_id` must match the `delegate_id` field of an event

Customer Details Page

In the Customer Details Page we have added the `Transaction History Delegate` widget, similar to `Transaction History`, where events in which a customer acted as a delegate will be shown.

This new widget will only show the `Transfers` and `Digital Activity` channels and have specific filters for `Delegate CIN`.



note

In order for an event to appear when filtering by `Delegate CIN`, the `customer_id` must match the `delegate_id` field of an event

In addition we have also added two new widgets to show the current delegations the customer has in place and also to which customers it is delegated to.

Each of the entries links to the given customer page.

Enable new features in the Case Manager UI

The new widgets can be enabled/disabled via a new Ansible variable `show_delegate_transaction_history_widget`, set to `true` by default.

This can be used, for instance, to hide the widgets if a specific region or market does not require the PB Delegate use case.

Please refer to [Case Manager Configuration Reference](#) for more information.