

On this page

Configuration Recommendations



For a complete reference check the [official Configuration Guide](#).

Ansible



Available ansible variables for running the ansible playbook.

Variable	Default Value
ansible_user	feedzai
ansible_local_user	{{ ansible_user }}
cm_install_path	"/opt/feedzai"
cm_home_path	"{{ cm_install_path }}/product-cm-{{ cm_version }}"
cm_java_options	"-Xms4g -Xmx4g"
database_casemanager_hostname	"postgres"
database_casemanager_port	"5432"
database_casemanager_database_name	"feedzai"

Variable	Default Value
database_casemanager_ro_hostname	"{{ database_casemanager_hostname }}"
database_casemanager_ro_port	"{{ database_casemanager_port }}"
database_casemanager_ro_database_name	"{{ database_casemanager_database_name }}"
database_casemanager_jdbc_opts	[currentSchema={{ database_casemanager_schema }}, loginTimeout=10, connectTimeout=2,
database_casemanager_jdbc	"jdbc:postgresql://{{ database_casemanager_hostname }}:{{ database_casemanager_port }}/{
database_casemanager_jdbc_ro_opts	[currentSchema={{ database_casemanager_schema }}, loginTimeout=10, connectTimeout=2,
database_casemanager_ro_jdbc	"jdbc:postgresql://{{ database_casemanager_ro_hostname }}:{{ database_casemanager_ro_p
database_casemanager_username	casemanager
database_casemanager_password	secret
database_casemanager_schema	casemanager
database_casemanager_ro_username	{{ database_casemanager_username }}

Variable	Default Value
database_casemanager_ro_password	{{ database_casemanager_password }}
database_casemanager_ro_schema	{{ database_casemanager_schema }}
cm_url	"http://localhost:8090"
reference_data_servers	reference-data
reference_data_url	"http://{{reference_data_servers}}:{{reference_data_port}}"
reference_data_casemanager_jwt_token	"eyJraWQiOiJkZWZhdWx0liwidHlwIjoiSldUliwiYWxnIjoiSFMyNTYifQ.eyJzdWliOiJoc2JjIiwibm9ybm8isg4"
cm_jetty_http_port	8080
pulse_casemanager_username	casemanager
pulse_casemanager_password	Secret1!
rabbitmq_casemanager_brokers	{{ rabbitmq_brokers }}
rabbitmq_casemanager_username	cm
rabbitmq_casemanager_password	secret
rabbitmq_casemanager_vhost	cm
jks_store_password	N/A
cm_truststore_path	"{{ cm_home_path }}/conf/trustedca.jks"

Variable	Default Value
pulse_internal_url	"http://pulse:8080"
pulse_url	{{ pulse_internal_url }}
cm_secret_value	N/A
cm_properties_to_encrypt	[]
afis_scheme	https
afis_scheme_send_sms	{{ afis_scheme }}
afis_payment_fulfillment_cm_extension_enabled	true
afis_mobile_outbound_cm_extension_enabled	true
afis_cm_extension_enabled_send_sms	true

Variable	Default Value
send_2_way_sms_extension_enabled	true
send_1_way_sms_extension_enabled	true
send_reminder_sms_extension_enabled	true
inbound_payment_notification_extension_enabled	true
card_status_update_extension_enabled	true
afis_host	
afis_host_send_sms	{{ afis_host }}
afis_port	443
afis_port_send_sms	{{ afis_port }}

Variable	Default Value
afis_api_endpoint	feedzai-event-notification
afis_api_endpoint_send_sms	{{ afis_api_endpoint }}
afis_timeout_in_seconds_send_sms	{{ afis_timeout_in_seconds }}
afis_waitstrategy_in_seconds_send_sms	{{ afis_waitstrategy_in_seconds }}
afis_stopstrategy_attempts_send_sms	{{ afis_stopstrategy_attempts }}
afis_proxy_enabled_send_sms	{{ afis_proxy_enabled }}
afis_proxy_host_send_sms	{{ afis_proxy_host }}
afis_proxy_port_send_sms	{{ afis_proxy_port }}

Variable	Default Value
dsp_endpoint	
dsp_username	{{ lookup('gcp_secret_manager', secret='dsp_username', version=secret_manager_secret_ver
dsp_password	{{ lookup('gcp_secret_manager', secret='dsp_password', version=secret_manager_secret_ver
dsp_endpoint_send_sms	{{ dsp_endpoint }}
dsp_username_send_sms	{{ dsp_username }}

Variable	Default Value
casemanager_api_url	{{ cm_url }}
casemanager_api_username	{{ pulse_casemanager_username }}
casemanager_api_password	{{ pulse_casemanager_password }}
cm_liquibase_environment	
getnext_time_frame	604800
casemanager_setup_thread_dumps_cron	false
casemanager_thread_dumps_cron_job	[]
cm_liquibase_rollback	false

Variable	Default Value
apps_enabled	apps_enabled: Â Â - uk_outbound_payments
cm_multi_tenancy_enabled	false
payment_fulfillment_exclude_events_without_status_reason	true
show_delegate_transaction_history_widget	true
cm_loggers	{}
cm_probes_log_level	"OFF"

Variable	Default Value
cm_probes_output_file_name	"cm-probes.log"
use_rsync	true
show_hsbnet_search_fields	false
fulfillment_channels_state_machines	{ "transfers": [{"name": "status"}], "inbound-payments": [{"name": "status"}], "cards": [{"name": "status"}], "outbound-payments": [{"name": "status"}], "transfers": [{"name": "status"}], "inbound-payments": [{"name": "status"}], "cards": [{"name": "status"}], "outbound-payments": [{"name": "status"}] }

Variable	Default Value
cm_transaction_block_date_offset_days	5
rabbitmq_casemanager_use_quorum_queues	false

Cron type

Variable	type	Mandatory	Default Value	Description
name	STRING	X		Name of the cron job
hour	STRING		*	The cron expression for <code>hour</code>
minute	STRING		*	The cron expression for <code>minute</code>
day	STRING		*	The cron expression for <code>day</code>
weekday	STRING		*	The cron expression for <code>weekday</code>
month	STRING		*	The cron expression for <code>month</code>

PDB channel specific database

Variable	Default Value	Description
pdb_active_channels		Identifies the usage of the dedicated databases. The first channel of the list identifies the main database. Available values: Â Â - cards Â Â - digital-activity Â Â - inbound-payments Â Â - transfers Â Â - non-mon

Each of the following variables needs a suffix `_<channel>` that identifies the channel and the configuration of the dedicated database.

Variable	Default Value
database_casemanager_engine_<channel>	"{{ database_casemanager_engine }}"
database_casemanager_jdbc_<channel>	"{{ database_casemanager_jdbc }}"
database_casemanager_username_<channel>	"{{ database_casemanager_username }}"
database_casemanager_password_<channel>	"{{ database_casemanager_password }}"
database_casemanager_schema_<channel>	"{{ database_casemanager_schema }}"
database_casemanager_schemapolicy_<channel>	"{{ database_casemanager_schemapolicy }}"
database_casemanager_pool_size_<channel>	"{{ database_casemanager_pool_size }}"
database_casemanager_pool_lazy_<channel>	"{{ database_casemanager_pool_lazy }}"
database_casemanager_reconnect_on_lost_<channel>	"{{ database_casemanager_reconnect_on_lost }}"
database_casemanager_max_number_retries_<channel>	"{{ database_casemanager_max_number_retries }}"
database_casemanager_retry_interval_<channel>	"{{ database_casemanager_retry_interval }}"
database_casemanager_query_select_timeout_<channel>	"{{ database_casemanager_query_select_timeout }}"
database_casemanager_ro_jdbc_<channel>	"{{ database_casemanager_ro_jdbc }}"
database_casemanager_ro_pool_size_<channel>	"{{ database_casemanager_ro_pool_size }}"
database_casemanager_ro_username_<channel>	"{{ database_casemanager_ro_username }}"
database_casemanager_ro_password_<channel>	"{{ database_casemanager_ro_password }}"
database_casemanager_ro_schema_<channel>	"{{ database_casemanager_ro_schema }}"
database_casemanager_ro_reconnect_on_lost_<channel>	"{{ database_casemanager_ro_reconnect_on_lost }}"
database_casemanager_ro_max_number_retries_<channel>	"{{ database_casemanager_ro_max_number_retries }}"
database_casemanager_ro_retry_interval_<channel>	"{{ database_casemanager_ro_retry_interval }}"
database_casemanager_ro_query_select_timeout_<channel>	"{{ database_casemanager_ro_query_select_timeout }}"
database_casemanager_ro_pool_lazy_<channel>	"{{ database_casemanager_ro_pool_lazy }}"
database_casemanager_ro_schemapolicy_<channel>	"{{ database_casemanager_ro_schemapolicy }}"

Performance configuration

With the inclusion of new use cases it is expected that Case Manager sizing to be updated. Aside from bare metal sizing updates, Case Manager also provides performance configurations that allow fine tuning of the various nodes.



Changing any of these configurations can have a performance impact in Case Manager. They should only be changed in agreement with the project team.

Please find below a description of each of the available configurations.

Variable	Default Value	Description
cm_performance_event_worker_threads	8	The number of workers that should be used to asynchronously store events into event storage.
cm_performance_queue_prefetch_size	200	The number of messages Case Manager fetches from RabbitMQ.
cm_performance_batch_storage_size	300	The size of the batch, i.e. the number of entries the batch can hold after which a flush will occur.
cm_performance_batch_storage_timeout	1000	

Variable	Default Value	Description
		The batch timeout, i.e. the time after which a batch flush will occur, regardless of the amount of entries present in it.
cm_performance_batch_flush_workers	4	The number of workers that should be used to asynchronously execute batch flush callback operations.
cm_performance_batch_flush_queue_size	5000	The size of the buffer that holds events to be added to the batch.
cm_performance_event_storage_queue_size	200	The size of the buffer that holds events to be added to the batch.
cm_performance_event_storage_batch_size	500	The size of the batch, i.e. the number of entries the batch can hold after which a flush will occur.
cm_performance_event_storage_batch_timeout	1000	The batch timeout, i.e. the time after which a batch flush will occur, regardless of the amount of entries present in it.
cm_performance_event_storage_batch_threads	1	The batch threads, i.e. the number of threads getting entries of the queue and writing to the batch.
cm_performance_related_max_last_flush_secs	10	Maximum period (in seconds) that notifier should wait before sending the RTS notification.
cm_performance_ignore_event_updates	false	Whether event updates should be ignored, and thus, the event ingestion process optimized.
cm_performance_disable_auditing_without_users	false	Whether the audit for actions without users should be skipped in the database.
cm_performance_max_queued_explanations	5000	The Number of queued explanations for persistence by the explanations batch.
cm_performance_max_related_transactions	500	The maximum number of related transactions to an event to fetch.
cm_performance_explanations_batch_size	300	The size of the batch, i.e. the number of entries the batch can hold after which a flush will occur.
cm_performance_automation_worker_threads	4	The batch threads, i.e. the number of threads getting entries of the queue and writing to the batch.
cm_performance_automation_batches_queue_size	200	The size of the buffer that holds events to be added to the batch.
cm_performance_automation_batches_batch_size	500	The size of the batch, i.e. the number of entries the batch can hold after which a flush will occur.
cm_performance_automation_batches_batch_timeout	1000	The batch timeout, i.e. the time after which a batch flush will occur, regardless of the amount of entries present in it.
cm_performance_automation_batches_batch_threads	1	The batch threads, i.e. the number of threads getting entries of the queue and writing to the batch.
cm_performance_automation_rule_cache	0	Automation cache value until automation rules are refreshed in memory.
cm_performance_max_queued_automations	5000	Maximum number of queued automations for execution by the automation worker threads
cm_performance_audit_batches_queue_size	200	The size of the buffer that holds events to be added to the batch.
cm_performance_audit_batches_batch_size	300	The size of the batch, i.e. the number of entries the batch can hold after which a flush will occur.

Variable	Default Value	Description
cm_performance_audit_batches_batch_timeout	1000	The batch timeout, i.e. the time after which a batch flush will occur, regardless of the amount of entries present in it.
cm_performance_audit_batches_batch_threads	1	The batch threads, i.e. the number of threads getting entries of the queue and writing to the batch.
cm_performance_enable_db_heuristic_for_event_queue_search	false	Whether an explicit <code>queueId neq null</code> should be added to improve queue searches.