

On this page

Installing Data Extraction Pipelines with Ansible

Data Extraction Pipelines

The Feedzai Ansible Toolkit refers to a series of Ansible Playbooks created by Feedzai to automate the data extraction pipelines installation and manage configurations across multiple environments.

Requirements

- All servers hostnames must resolve their own IP's.
- The servers should be able to resolve each others hostnames, please update the /etc/hosts file if necessary, or use a DNS service.
- Use ping to ensure to confirm that each server is able to ping other servers.
- A Linux-based Node (preferably dedicated to this task), with a deployment user configured. The node must have Python3 for running Ansible.
- A deployment user on each server with superuser (sudo) permissions (some deployment steps include installing system services, and changing ownership of folders).

Data Extraction Pipelines Installation

To install a the data extraction pipelines component, execute the following command:

```
python3 ansible-playbook \
  --connection=local \
  -i project-default \
  -i project-hsbc \
  -i gcp \
  logstash.yml \
  --tags external-notification-exporter.install
```

Copy

To configure data extraction pipelines component for a given `<env>` (e.g.: `dev` , `qa` , `prod` ...):

```
python3 ansible-playbook \
  --connection=local \
  -i project-default \
  -i project-hsbc \
  -i project-<env> \
  logstash.yml \
  --tags external-notification-exporter.configure
```

Copy