

On this page

Data Extraction Pipelines Configurations

Ansible

Variable	type	Mandatory	Default Value	Description
rabbitmq_casemanager_brokers	STRING	X		RabbitMQ host from where the pipelines will read the Case Manager notifications (same as configured in Case Manager)
rabbitmq_casemanager_username	STRING	X		RabbitMQ user from where the pipelines will read the Case Manager notifications (same as configured in Case Manager)
rabbitmq_casemanager_password	STRING	X		RabbitMQ password from where the pipelines will read the Case Manager notifications (same as configured in Case Manager)
rabbitmq_casemanager_vhost_blue	STRING	X		RabbitMQ Blue vhost from where the pipelines will read the Case Manager notifications (same as configured in Case Manager)
rabbitmq_casemanager_vhost_green	STRING	X		RabbitMQ Green vhost from where the pipelines will read the Case Manager notifications (same as configured in Case Manager)
rabbitmq_casemanager_queue_type_blue	STRING		CLASSIC	RabbitMQ Blue Queue Type (can be one of CLASSIC / QUORUM)
rabbitmq_casemanager_queue_type_green	STRING		CLASSIC	RabbitMQ Green Queue Type (can be one of CLASSIC / QUORUM)
pulse_elb	STRING	X		Pulse host name (to be used in Rules Metadata pipeline) - in the format http(s)://<host>:<port>
pulse_app_id	STRING		599912dbf381eb06	Pulse Payments application identifier (to be used in Rules Metadata pipeline)

Variable	type	Mandatory	Default Value	Description
pulse_workflow_id	STRING		daef64964ee3b9b9	Pulse Payments workflow identifier (to be used in Rules Metadata pipeline)
pulse_insights_logstash_username	STRING	X		Pulse user name (to be used in Rules Metadata pipeline)
pulse_insights_logstash_password	STRING	X		Pulse password (to be used in Rules Metadata pipeline)
gcs_tmp_directory	STRING		/tmp/logstash/	Directory where temporary files are stored
case-manager-cases-case.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
case-manager-cases-event.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
case-manager-cases-queue.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
case-manager-cases-status.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
case-manager-cases-user.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
case-manager-events-event.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
case-manager-events-notes.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
case-manager-events-queue.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
case-manager-events-status.workers	NUMBER		1	Setting determines how many threads to run for

Variable	type	Mandatory	Default Value	Description
				filter and output processing for the specified pipeline
case-manager-events-user.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
rules-metadata.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
pulse-workflow-audit.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
pulse-workflow-audit-recovery.workers	NUMBER		1	Setting determines how many threads to run for filter and output processing for the specified pipeline
logstash_heap_size	STRING		{{ (ansible_memtotal_mb * 0.5)}}	int
gcs_bucket_name	STRING	X		Bucket to where the pipelines will export the data
gcs_bucket_name_cases_case	STRING		{{ gcs_bucket_name }}	Bucket to where the New Case pipeline will export the data
gcs_bucket_name_cases_event	STRING		{{ gcs_bucket_name }}	Bucket to where the Case events linked/unlinked pipeline will export the data
gcs_bucket_name_cases_queue	STRING		{{ gcs_bucket_name }}	Bucket to where the Case queue changed pipeline will export the data
gcs_bucket_name_cases_status	STRING		{{ gcs_bucket_name }}	Bucket to where the Case state change pipeline will export the data
gcs_bucket_name_cases_user	STRING		{{ gcs_bucket_name }}	Bucket to where the Case assignee changed pipeline will export the data
gcs_bucket_name_events_event	STRING		{{ gcs_bucket_name }}	Bucket to where the Event arrival pipeline will export the data
gcs_bucket_name_events_notes	STRING		{{ gcs_bucket_name }}	Bucket to where the Add note pipeline will export the data
gcs_bucket_name_events_queue	STRING		{{ gcs_bucket_name }}	

Variable	type	Mandatory	Default Value	Description
				Bucket to where the Event queue changed pipeline will export the data
gcs_bucket_name_events_status	STRING		{{ gcs_bucket_name }}	Bucket to where the Event state changed pipeline will export the data
gcs_bucket_name_events_user	STRING		{{ gcs_bucket_name }}	Bucket to where the Event assignee changed pipeline will export the data
gcs_bucket_name_rules_metadata	STRING		{{ gcs_bucket_name }}	Bucket to where the rules metadata pipeline will export the data
gcs_bucket_name_pulse_workflow_audit	STRING		{{ gcs_bucket_name }}	Bucket to where the pulse workflow audit pipeline will export the data
gcs_bucket_name_pulse_workflow_audit_recovery	STRING		{{ gcs_bucket_name }}	Bucket to where the pulse workflow audit pipeline will export the data
max_file_size_kbytes	NUMBER		1024 (from defaults)	Sets max file size in kbytes. 0 disable max file check
uploader_interval_secs	NUMBER		60	Uploader interval when uploading new files to GCS. Adjust time based on your time pattern (for example, for hourly files, this interval can be around one hour)
logstash_pipelines_tmp_path	STRING		/tmp/staging/logstash/pipelines	Source directory of the pipeline template files
dead_letter_queue_enable	BOOLEAN		False	Enable Logstash Dead Letter Queueing System
allow_superuser_execution	BOOLEAN		True	Allows superuser execution