

On this page

Logstash Pulse Workflow Audit Pipeline Recovery Tool

Playbook to run the *pulse-workflow-audit* Logstash pipeline in recovery mode.

This playbook can be executed for a specific interval when there is any problem with the pipeline and the data is not exported as it should.

By running this playbook, the *pulse-workflow-audit* pipeline will execute once for the defined interval and export the results to the configured GCP bucket.

This pipeline also supports a cron entry that restarts the *pulse-workflow-audit* pipeline on a schedule, and exposes variables to control whether to install base dependencies needed to have the cron daemon `crond` installed for the scheduling, as well as a variable to control the location of the temporary trimmed pipeline config that it needs as part of its restart operation.

Configuration

All the following variables are **mandatory**.

Variable	Type	Default Value	Description
logstash_pipeline_recovery_mode	boolean	true	Defines if we are running the pipeline in recovery mode. Needs to be true
logstash_pipeline_recovery_name	string	pulse-workflow-audit	Name of the pipeline that we are running in recovery mode
logstash_audit_pipeline_since	number		The start date of the interval to run the pipeline in Unix time format
logstash_audit_pipeline_until	number		The end date of the interval to run the pipeline in Unix time format
pulse.host	string		Pulse host name - in the format <code>http(s)://<host>:<port></code>
pulse.user	string		Pulse user name
pulse.password	string		Pulse password
gcs_bucket_name	string		Bucket to where the pipeline will export the data
gcs_tmp_directory	string	/tmp/logstash/	Directory where temporary files are stored
max_file_size_kbytes	number	1024	Sets max file size in kbytes. 0 disable max file check
uploader_interval_secs	number	60	Uploader interval when uploading new files to GCS.
restart_pipeline_base_dependencies	list	[]	Dependencies to ensure the cron daemon is started for pipeline restarts
start_crond_service	boolean	false	Controls whether to install dependencies (restart_pipeline_base_dependencies)
temp_trimmed_pipeline_config_name	string	/tmp/trimmed_pipeline.conf	The location of the temporary trimmed pipeline needed by the pipeline restarter

Running the Playbook

```
python3.6 ansible-playbook \
-i project-default \
```

```
-i project-hsbc \
-i gcp \
-i project-<env> \
execute-logstash-audit-pipeline.yml
```

Copy