

On this page

Configuration Recommendations

Ansible



Available ansible variables for running the ansible playbook.

Variable	Default Value	Description
reference_data_app_port	8080	Reference data connection port
reference_data_admin_port	8081	Reference data administration connection port
reference_data_cassandra.tableName	feedzai_reference_data	Cassandra table name
reference_data_cassandra.keyspaceName	hsbc	Cassandra keyspace name
reference_data_cassandra.username	cassandra	Cassandra username
reference_data_cassandra.password	cassandra	Cassandra password
reference_data_cassandra.cluster	rds cluster	Cassandra cluster name
reference_data_cassandra.contactPoints	["localhost:9042"]	Cassandra contact points
reference_data_cassandra.consistencyLevel	"LOCAL_ONE"	Cassandra consistency level
reference_data_cassandra.replicationStrategy	"class:'NetworkTopologyStrategy', 'dc1': 1"	Cassandra replication strategy
reference_data_jwt_secret	"Ojd40327td208347t02k3487t23k40t87320t"	JWT secret, needs to be set
reference_data_use_https	false	When <code>true</code> RDS will use https for connection
keyStorePath	"{{ reference_data_home_path }}/conf/keystore.jks"	Keystore path, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
keyStorePassword	N/A	Keystore password, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
keyStoreType	"JKS"	Key store type, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
keyManagerPassword	N/A	Key manager password, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
validateCerts	true	

Variable	Default Value	Description
		Set to validate certificates, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
<code>validatePeers</code>	<code>true</code>	Set to validate peers, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
<code>supportedProtocols</code>	<code>[TLSv1.2]</code>	Set supported protocols, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
<code>supportedCipherSuites</code>	<code>[TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256]</code>	Set supported ciphers, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
<code>allowRenegotiation</code>	<code>true</code>	Set to allow renegotiation, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
<code>reference_data_secret_value</code>	N/A	Value used to encrypt sensitive properties
<code>reference_data_properties_to_encrypt</code>	<code>[]</code>	List of properties to encrypt. Encrypted properties can be used by adding the suffix <code>_encrypted</code> to the original property name, i.e <code><PROPERTY_NAME>_encrypted</code> . Doesn't support dictionary variables
<code>reference_data_grace_period_ms</code>	<code>30000</code>	The number of milliseconds the service will stay available after a shutdown request is received
<code>reference_data_log_level</code>	<code>INFO</code>	Default log level for all components in RDS. Please note that changing this value may impact the amount of produced logs.
<code>reference_data_loggers</code>	<code>{}</code>	Controls extra loggers in RDS, allowing to override the default value per logger. Keys in this dictionary are the loggers and the values the log level for that logger.



info

There are no configuration recommendations for this service besides the ones already described in the guide.