

On this page

Requirements

Service Requirements

This service requires the following software to run.

Java Environment

OpenJDK SE Development Kit version 1.8, with the following vendors (with their latest hotfix versions):

- Azul Zulu [rpm](#) [zip](#) [tar.gz](#)
- Azul Platform Prime (formerly Zing)
- Amazon Corretto
- Oracle



Product tests are done with the **Azul Zulu JVM**.

The following versions are not supported, and are known to have problems:

- 1.8.0u242
- 1.8.0u121
- 1.8.0u60
- 1.8.0u45 and earlier

Non-listed releases are either not supported or haven't been put to extensive testing.

Setup Requirements

Database

The Reference Data Service is a service responsible for storing reference data that belongs to individual entities (e.g. Card, Customer, etc). The type of storage that better suits this use-case are *key-value* stores.

The following systems are supported:

- Apache Cassandra 2.1 or higher - version 3.11.3 is the recommended version, and [DSE](#) is also supported

Cassandra

When using Cassandra, RDS will also automatically create the entities tables, considering the following:

1. A Cassandra cluster is available, and working properly. To connect to Cassandra, you must define the contact points in `cassandra.contactPoints` (for example, `cassandra-1,cassandra-2`).
2. A user has been created for RDS with the following permissions:
 - Create a Keyspace
 - Create tables
 - Modify (Insert, Delete, Update, Truncate)
 - Select

The credentials of the user must be configured in `cassandra.user|password` .