

On this page

API Authentication

In this page you can find an outline of the authentication process, necessary parameters, and the required flow to interact with the Pulse APIs, for example, in the context of authenticating a service account before using the Pulse and Case Manager servlets that allow [log levels changes at runtime](#) or [export and import Pulse applications](#).

Authentication Process

Pulse and Case Manager APIs require authentication for accessing and performing actions. Specifically, Basic Authentication is used for authenticating service accounts through their credentials (username and password). These credentials need to be encoded in Base64 before being sent in the API requests. The authentication flow is as follows:

- Take note of a Pulse service account's username and password
- Encode the username and password using a Base64 encoder of your choosing
- Send a request to the authentication endpoint with the credentials in the request body
- If the request succeeds, Pulse will return a session cookie that can be used in subsequent API calls, e.g. a request to the logging API

You can find below the authentication diagram:

After receiving a successful response the cookie can be used to make authenticated requests to the Pulse API to, for example, change logging levels via the [Logging API](#).

API definition

In this section you can find the authentication API endpoint definition.

Endpoint URL

POST /pulseviews/api/sessions (authenticates a service account)

Parameters

None

Responses

Code	Content-type	Response
200	application/json	JSON object with user information
401	text/html; charset=iso-8859-1	Error 401 Unauthorized

Example cURL

```
curl -X POST http://<PULSE_URL>/pulseviews/api/sessions \
-H "Content-Type: application/json" \
-H "X-Requested-With: XMLHttpRequest" \
-d '{"username": "<base64_username>", "password": "<base64_password>"}' -c -
```

Copy

Example response

```
{ "blockedState": "NONE", "createdAt": 1732196807880, ... }  
#HttpOnly localhost FALSE / FALSE 0 SS0cookie cee99ab5-xxxx-xxxx-xxxx-xxx  
xxxxxxxxxx
```

Copy