

On this page

# Case Manager Database Table Structure

Find in this page a detailed guide on the important tables used for Case Manager.

## AM\_EVENT\_STORAGE

- This table contains the referential records to all historical transactions, where the event request is stored in EVENT\_DATA in raw json format. This includes all events for a given lifecycle\_id, not just a single record per lifecycle\_id.

| Column Name      | Column Type | Description                                                                                                       |
|------------------|-------------|-------------------------------------------------------------------------------------------------------------------|
| EVENT_ID         | PRIMARY KEY | The event's unique identifier. Randomly generated UUID, generated for each event.                                 |
| EVENT_VERSION_ID | PRIMARY KEY | It is usually equal to EVENT_ID. New Id gets generated in case the event is an update to the initial transaction. |
| EVENT_DATA       | JSON        | The field stores event data                                                                                       |

## AM\_EVENT\_DIGITAL\_ACTIVITY

- The records in this table correspond to the Digital Activity events (e.g. Credentials Update, Device Update, New Payee, Alias, Profile Update, etc).
- The AM\_EVENT\_DIGITAL\_ACTIVITY table only holds one record for all events with the same lifecycle\_id. Subsequent events for the same lifecycle\_id will update the record as opposed to creating a new record.
- Use this extract to find all the unique Digital Activity transactions uploaded using Digital Activity API

| Column Name      | Column Type | Description                                                                                                                               |
|------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| EVENT_ID         | PRIMARY KEY | Internal field. The event's unique identifier. Randomly generated UUID, equal to the corresponding FDZ_UUID in the Pulse's event storage. |
| EVENT_ALERT      | BOOLEAN     | Boolean for whether it is an alert or not.                                                                                                |
| EVENT_TENANT     | STRING      | Internal field which stores the tenant key.                                                                                               |
| QUEUE_ID         | STRING      | The ID of the current queue.                                                                                                              |
| USER_ID          | STRING      | The ID of the current assignee.                                                                                                           |
| ACCESS_GROUP_ID  | STRING      | The ID of the access group.                                                                                                               |
| channelId        | STRING      | Channel identifier.                                                                                                                       |
| event_type       | STRING      | An internal field that indicates the endpoint from which the event entered.                                                               |
| fraud_score      | STRING      | Calculated fraud score.                                                                                                                   |
| outcome_decision | STRING      | Event decision outcome.                                                                                                                   |
| amount           | INTEGER     | Transaction amount performed by the sender, in the currency specified by the <code>currency</code> field.                                 |
| channel_type     | STRING      | Specifies the transaction payment channel.                                                                                                |
| currency_code    | STRING      | The local currency of the business.                                                                                                       |
| customer_dob     | STRING      | Customer date of birth (YYYYMMDD).                                                                                                        |
| customer_email   | STRING      | Customer's email.                                                                                                                         |

| Column Name           | Column Type | Description                                |
|-----------------------|-------------|--------------------------------------------|
| customer_id           | STRING      | Customer ID generated by the issuing bank. |
| customer_name         | STRING      | Customer's name.                           |
| customer_phone_number | STRING      | Customer phone number.                     |

## AM\_EVENT\_TRANSFERS

- The records in this table correspond to the Transfer events (e.g. Initiation, Settlement, Info, Feedback, etc).
- The AM\_EVENT\_TRANSFERS database table only holds one record for all events with the same lifecycle\_id. Subsequent events for the same lifecycle\_id will update the record as opposed to creating a new record.
- Use this extract to find all the unique transfers uploaded using Transfers API

| Column Name            | Column Type | Description                                                                                                                               |
|------------------------|-------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| EVENT_ID               | PRIMARY KEY | Internal field. The event's unique identifier. Randomly generated UUID, equal to the corresponding FDZ_UUID in the Pulse's event storage. |
| EVENT_ALERT            | BOOLEAN     | Boolean for whether it is an alert or not.                                                                                                |
| EVENT_TENANT           | STRING      | Internal field which stores the tenant key.                                                                                               |
| QUEUE_ID               | STRING      | The ID of the current queue.                                                                                                              |
| USER_ID                | STRING      | The ID of the current assignee.                                                                                                           |
| ACCESS_GROUP_ID        | STRING      | The ID of the access group.                                                                                                               |
| channelId              | STRING      | Channel identifier.                                                                                                                       |
| event_type             | STRING      | An internal field that indicates the endpoint from which the event entered.                                                               |
| fraud_score            | STRING      | Calculated fraud score.                                                                                                                   |
| outcome_decision       | STRING      | Event decision outcome.                                                                                                                   |
| merchant_city          | STRING      | Card acceptor city.                                                                                                                       |
| dispute_end_date       | STRING      | Timestamp corresponding to the moment when the dispute was closed.                                                                        |
| dispute_feedback_notes | STRING      | Contextual information associated with the dispute communication.                                                                         |
| dispute_refunded       | STRING      | Whether the funds were refunded to the cardholder.                                                                                        |
| oob_feedback_notes     | STRING      | Contextual information associated with the out-of-band communication.                                                                     |
| feedback_type          | STRING      | Identifies the different types of feedback.                                                                                               |
| dispute_notes          | STRING      | Contextual information left by the analyst at the time of the dispute opening.                                                            |
| dispute_reason         | STRING      | Why the dispute was opened.                                                                                                               |
| dispute_start_date     | STRING      | Timestamp that corresponds to the time when the dispute was opened.                                                                       |
| dispute_submitted_by   | STRING      | Who submitted the dispute.                                                                                                                |

## AM\_EVENT\_STATUS

- Holds the history on status changes for events - previous state, new state, when the state change happened and who did it.

| Column Name     | Column Type | Description                                                           |
|-----------------|-------------|-----------------------------------------------------------------------|
| EVENT_STATUS_ID | PRIMARY KEY | Internal field, randomly generated identifier for each status change. |
| OLD_STATUS_ID   | STRING      | The ID of the old status.                                             |
| NEW_STATUS_ID   | STRING      | The ID of the new status.                                             |

| Column Name | Column Type | Description                                       |
|-------------|-------------|---------------------------------------------------|
| TIMESTAMP   | INTEGER     | Unix timestamp at which the event note was added. |
| USER_ID     | STRING      | ID of the user that added the note.               |

## AM\_EVENT\_EXPLANATION

- This table contains the explanations of why the event triggered an alert, that is the Rules that triggered the alert. This contains the rules explanation for events in AM\_EVENT table.

| Column Name                    | Column Type | Description                                                                                                               |
|--------------------------------|-------------|---------------------------------------------------------------------------------------------------------------------------|
| EVENT_ID                       | STRING      | The event's unique identifier. Randomly generated UUID, equal to the corresponding FDZ_UUID in the Pulse's event storage. |
| EVENT_TIMESTAMP                | INTEGER     | Corresponds to the FDZ_timestamp field in the Pulse's event storage for this particular EVENT_ID.                         |
| EVENT_VERSION_ID               | STRING      | It is equal to EVENT_ID.                                                                                                  |
| EVENT_VERSION_TIMESTAMP        | INTEGER     | It is equal to EVENT_TIMESTAMP.                                                                                           |
| EVENT_EXPLANATION_GENERATOR_ID | STRING      | Contains the internal rule ID. The primary key of this table is composed of the event ID and the rule ID.                 |
| EVENT_EXPLANATION_GEN_NAME     | STRING      | Contains the rule name.                                                                                                   |
| EVENT_EXPLANATION_TYPE         | STRING      | The type of trigger that caused the alert.                                                                                |
| EVENT_EXPLANATION_DESCRIPTION  | STRING      | The explanation provided by the risk engine for triggering the rule.                                                      |

## AM\_EVENT\_NOTE

- Notes added by analysts that may include personal information. The key is the EVENT\_NOTE\_ID column.

| Column Name   | Column Type | Description                                                                 |
|---------------|-------------|-----------------------------------------------------------------------------|
| EVENT_NOTE_ID | PRIMARY KEY | Randomly generated identifier for each note manually added by the analysts. |
| NOTE_MESSAGE  | STRING      | Note added by the analyst.                                                  |
| USER_ID       | STRING      | ID of the analyst that added the note.                                      |

## AM\_EVENT\_STATUS\_REASON

- This will provide the reason why the status of an event was changed as selected in the UI.
- The table is related to the AM\_STATUS\_REASON table via the column STATUS\_REASON\_ID as the foreign key. The possible values for STATUS\_REASON\_ID is a small set of mostly static values that correspond to a few options in a drop-down menu that a Case Manager user can choose from in the UI.

| Column Name      | Column Type | Description                                                                                                |
|------------------|-------------|------------------------------------------------------------------------------------------------------------|
| EVENT_STATUS_ID  | PRIMARY KEY | ID of the status associated with this reason change. Maps to the EVENT_STATUS_ID field in AM_EVENT_STATUS. |
| STATUS_REASON_ID | FOREIGN KEY | Foreign key to AM_STATUS_REASON table.                                                                     |
| TIMESTAMP        | PRIMARY KEY | Unix timestamp at which the event note was added.                                                          |

## AM\_SLA

- The table stores the SLA definition or metadata that is created to automatically perform actions on events.

| Column Name     | Column Type | Description             |
|-----------------|-------------|-------------------------|
| SLA_ID          | PRIMARY KEY | ID of the SLA.          |
| SLA_NAME        | PRIMARY KEY | Name of the SLA.        |
| SLA_DESCRIPTION | STRING      | Description of the SLA. |
| SLA_GOAL        | STRING      | Goal of the SLA.        |
| SLA_CONDITIONS  | STRING      | Conditions of the SLA.  |
| SLA_ACTIONS     | STRING      | SLA actions.            |

### AM\_EVENT\_SLA

- The table links specific events to SLA's.

| Column Name  | Column Type | Description                  |
|--------------|-------------|------------------------------|
| EVENT_ID     | PRIMARY KEY | Unique event id.             |
| EVENT_SLA_ID | PRIMARY KEY | Event sla unique id.         |
| SLA_ID       | FOREIGN KEY | Foreign key to AM_SLA table. |

### AM\_AUTOMATION

- The table stores the Automation rules created to automatically perform actions events and cases based on conditions.

| Column Name            | Column Type | Description                        |
|------------------------|-------------|------------------------------------|
| AUTOMATION_ID          | PRIMARY KEY | ID of the service level agreement. |
| AUTOMATION_POSITION    | UNIQUE KEY  | Numeric position.                  |
| AUTOMATION_NAME        | STRING      | Name of Automation.                |
| AUTOMATION_DESCRIPTION | STRING      | Automation description.            |
| AUTOMATION_CONDITIONS  | STRING      | Automation conditions.             |
| AUTOMATION_ACTIONS     | STRING      | Automation actions.                |

### AM\_CASE\_\*



note

AM\_CASE\_\* - They are not used by HSBC