

Permissions Guide

Â

Functionality Tool	Action	Permission	Description
Case Manager and Pulse Common Permissions	Login	cm:login pulseviews:login	Lets the user log into pulse and case m
Case Manager Events	View	cm:resource:event:read:*	Lets the user read an event.
	Update	cm:resource:event:update:*	Lets the user update events.
	Assign/Unassign Event	cm:resource:event-user:create:* - Backend cm:action:event-user:create:* - Frontend	Lets the user assign users to event.
		cm:resource:assign:*	Gives the user rights to assign an eve already assigned to another user to its Permission only relevant for Assign an
		cm:action:event-case:delete:*	Lets the user unlink events from cases
	Notes	cm:resource:event-note:create:* - Backend cm:action:event-note:create:* - Frontend	Lets the user create notes in events.
		(1) cm:action:event-note:read:*	(1) Lets the user see Event Notes wid events details page.
		(2) cm:resource:event-note:read:*	(2) Lets the user see notes in events.
	Move to Queue	cm:resource:event-queue:create:* - Backend cm:action:event-queue:create:* - Frontend	Lets the user move events to queues.
	Move to Close	cm:action:manual-close-alert	Lets the user manually move events to status
	Resource Manager	cm:resource:manager:*	Gives the user rights to have all action permissions even if is not assigned the Permission only relevant for Assign an
	Export/download search results	cm:resource:event-export:read:*	Lets the user export the results.
		cm:action:event-export:create:*	Lets the user see the export button.

		Status	cm:action:event-status:create:*	Lets the user set event statuses
			cm:resource:status:read:*	Lets the user read event status options
		Files	(1) cm:resource:event-file:create:*	(1) Lets the user create N-to-N relations between events and files.
			(2) cm:resource:file:create:*	(2) Lets the user create files.
			cm:resource:file:read:*	Lets the user read files.
			cm:resource:file:update:*	Lets the user update an existing file.
			cm:resource:file:delete:*	Lets the user delete an existing file
			(1) cm:resource:file:event-file:create:*	Lets the user upload an existing file in Details page (Attached Files widget).
			(2) cm:resource:file:event-file:update:*	Lets the user update an existing file in Details page(widget: Attached Files).
			cm:resource:file:event-file:read:*	Lets the user list all the files associated with an event.
	Locale		cm:resource:locale:create:*	Lets the user create locales.
			cm:resource:locale:read:*	Lets the user read locales.
			cm:resource:locale:update:*	Lets the user update locales.
			cm:resource:locale:delete:*	Lets the user delete locales.
	Users		cm:resource:user:read:*	Lets the user read available users.
Case Manager Lists	View		cm:resource:list:search:*	Lets the user search for entities in lists
			cm:section:settings-lists:read:*	Lets the user see List Management options in the menu Settings section.
			cm:action:view-entity-audit:read:*	Lets the user view the "view-entity-audit" action.
	Update		cm:resource:list:update:*	Lets the user update lists content and order
	Create		cm:action:add-entity:create:*	Lets the user add a EntityValue to a List
			cm:action:event-list:create:*	Lets the user add events to lists.
	Delete		cm:action:remove-entity:delete:*	Lets the user remove an EntityValue from a List.
	Posneg		cm:action:event-posneg:create:*	Lets the user add events to posneg lists
			cm:resource:event-posneg:create:*	Lets the user create posneg lists for events
			cm:resource:event-posneg:read:*	Lets the user read posneg lists for events

Case Manager SLAs	View SLAs	cm:resource:sla:read:* - Backend cm:section:settings-slas:read:* - Frontend	Lets the user read SLAs.
	Create SLAs	cm:resource:sla:create:* - Backend cm:section:settings-slas:create:* - Frontend	Lets the user create SLAs.
	Edit SLAs	cm:resource:sla:update:* - Backend cm:section:settings-slas:update:* - Frontend	Lets the user update SLAs.
	Delete SLAs	cm:resource:sla:delete:* - Backend cm:section:settings-slas:delete:* - Frontend	Lets the user delete SLAs.
	View Cases	cm:resource:case:read:* - Backend cm:section:case:read:* - Frontend	Lets the user read cases.

Case Manager
Cases

	cm:section:case-details:read:*	Lets the user see the Case Details page.
	cm:section:case-details:*	Lets the user access all case-details pages and functionalities.
Search Cases	cm:section:case-search:*	Lets the user search for cases
Create Cases	cm:resource:case:create:* - Backend cm:section:case:create:* - Frontend	Lets the user create cases.
Update case	cm:resource:case:update:* - Backend cm:section:case:update:* - Frontend	Lets the user update cases.
Delete case	cm:resource:case:delete:*	Lets the user delete cases.
Assign Case	cm:resource:case-user:create:*	Lets the user assign users to cases.
Link events/alerts to cases	cm:action:event-case:create:*	Lets the user link events to case.
	cm:resource:event-case:create:*	Lets the user add events to cases.
	cm:resource:event-case:delete:*	Lets the user delete events in cases.
	cm:resource:event-case:read:*	Lets the user read events in cases.
	cm:resource:event-case:update:*	Lets the user update events in cases.
Move case to queue	cm:resource:case-queue:create:*	Lets the user create queues for cases
Set case status	cm:action:case-state:create:*	Lets the user open or close case state in cases.
Upload/Download Files	(1) cm:resource:case-file:create:* (2) cm:resource:file:case-file:read:*	(1) Lets the user upload file in Case Details page. (2) Lets the user download file in Case Details page.
Files	cm:resource:case-details:create:*	Lets user list all the files associated with current case.
	cm:resource:file:case-file:update:*	Lets the user update file in Case Details page.
Channels	cm:action:case*-global:read:*	Lets the user see channels in cases.
	cm:action:case-global:create:*	Lets the user select channels in cases. Note that, for Omnichannel Multichannel cases, the channel field should be hidden and for Omnichannel Single channel (Default) cases, the channel field should be visible.
Export	(1) cm:action:case-export:create:* (2) cm:resource:case-export:read:*	(1) Lets the user see the export button in cases search page. (2) Lets the user export the results from cases search page, or any other table. Only uses those cases fields.
	(1) cm:action:case-note:create:* - Frontend	

		Notes	cm:resource:case-note:create:* - Backend (2) cm:action:case-note:read:* - Frontend cm:resource:case-note:read - Backend (3) cm:resource:case-note:update (4) cm:resource:case-note:delete	(1) Lets the user add a note to a case on the Case Details page. (2) Lets the user see case notes on Notes widget. (3) Lets the user update notes in cases. (4) Lets the user delete notes in cases.
		States	cm:resource:case-state:create:*	Lets the user create states for cases.
		Casetype	cm:resource:casetype:<CASE_TYPE_NAME>:read (e.g cm:resource:casetype:fraud:read)	Gives read-level permission over the case type given by <CASE_TYPE_NAME>, where the case type name is given by the configured case type name without the type. Prefix (example: for a configured case type of type.aml, the permission is cm:resource:casetype:aml:read)
			cm:resource:casetype:<CASE_TYPE_NAME>:write (e.g cm:resource:casetype:fraud:write)	Gives both read and write-level permission over the case type given by <CASE_TYPE_NAME>, where the case type name is given by the configured case type name without the type. Prefix (example: for a configured case type of type.fraud, the permission is cm:resource:casetype:fraud:write).
Case Manager	Reasons	View Reasons	cm:resource:status-reason:read:* - Backend cm:section:settings-reason:read:* - Frontend	Enables the user to list the available reasons.
		Create Reasons	cm:section:settings-reason:create:*	Enables the user to create new reasons.
		Delete Reasons	cm:action:reason:delete:*	Enables the user to remove reasons.
Case Manager	Automation Rules	View Automation Rule	(1) cm:resource:automation:read:* (2) cm:resource:configuration-automation:read:* (3) cm:section:settings-automation:read:*	(1) Lets the user read automation rules. (2) Lets the user read the automation rule configuration. (3) Lets the user see the Automation Rules page
		Create Automation Rule	cm:section:settings-automation:create:* - Frontend cm:resource:automation:create:* - Backend	Lets the user create automation rules on the Automation Rules page
		Edit Automation Rule	cm:resource:automation:update:* - Backend cm:section:settings-automation:update:* - Frontend	Lets the user update automation rules on the Automation Rules page
		Delete Automation Rule	cm:resource:automation:delete:* - Backend cm:section:settings-automation:delete:* - Frontend	Lets the user delete automation rules on the Automation Rules page
			(1) cm:resource:queue:read:* (2) cm:resource:queue-user:read:*	(1) Lets the user read queues. (2) Lets the user read its own queues.

Case Manager Queue	View Queue	(3) cm:resource:queue-user:* (4) cm:section:settings-queue:read:*	(3) Lets the user perform CRUD operations over the current queues assigned to a user. (4) Lets the user see the queues page in the Settings section.
	Create Queue	cm:resource:queue:create:* - Backend cm:section:settings-queue:create:* - Frontend	Lets the users create queues in the Settings section.
	Edit Queue	cm:resource:queue:update:* - Backend cm:section:settings-queue:update:* - Frontend	Lets the user update queues in the Settings section.
	Delete Queue	cm:resource:queue:delete:* - Backend cm:section:settings-queue:delete:* - Frontend	Lets the user delete queues in the Settings section.
	Assign Queues	cm:resource:queue-user:assign:*	Lets the user assign queues to users.
	Import and Export Queues	cm:resource:settings:import-export:* - Backend cm:action:settings:import-export:* - Frontend	Lets the user import and export queues.
	Get Next	cm:resource:user-queue:*	Lets the user see the working queues, in the context of the review next feature.
Case Manager Self Service Rules	View SSR	cm:section:settings-rules:read:*	Lets the user see rules in the Self-Service Rules page.
	Create SSR	cm:section:settings-rules:create:*	Lets the user create rules in the Self-Service Rules page.
	Edit SSR	cm:section:settings-rules:update:*	Lets the user update rules in the Self-Service Rules page.
	Delete SSR	cm:section:settings-rules:delete:*	Lets the user delete rules in the Self-Service Rules page.
	Publish SSR	cm:section:settings-rules:publish:*	Lets the user publish rules in the Self-Service Rules page.
	Test SSR	(1) cm:resource:settings-rules-custom-test:create:* (2) cm:resource:settings-rules-test:create:* cm:section:settings-rules-test:create:*	(1) Lets the user test rules with custom properties, either the user is a landlord or contains the permission. (2) Lets the user test rules, either the user is a landlord or contains the permission.
		cm:section:settings-rules-test:create:*	Lets the user test rules, either the user is a landlord or contains the permission.
	Rules Audit	cm:resource:self-service-rules:audit:*	Lets the user access rules audit entries.
Case Manager Reports	View reports	cm:resource:report:read:* - Backend cm:section:report:read:* - Frontend	Lets the user read reports.

	Create reports	cm:resource:report:create:* - Backend cm:section:report:create:* - Frontend	Lets the user create reports.
	Update reports	cm:resource:report:update:*	Lets the user update reports.
	Delete reports	cm:resource:report:delete:* - Backend cm:action:delete-generated-report:delete:* - Frontend	Lets the user delete reports.
	Download reports	cm:resource:file:report:read:*	Lets the user download reports.
Case Manager Report Templates	View	cm:resource:report-template:read:* - Backend cm:section:settings-report-template:read:* - Frontend	Lets the user read report templates.
	Create	cm:resource:report-template:create:* - Backend cm:section:settings-report-template:create:* - Frontend	Lets the user create report templates.
	Update	cm:resource:report-template:update:* - Backend cm:section:settings-report-template:update:* - Frontend	Lets the user update report templates.
	Delete	cm:resource:report-template:delete:* - Backend cm:section:settings-report-template:delete:* - Frontend	Lets the user delete report templates.
	Download	cm:resource:file:report-template:read:*	Lets the user download report templates.
Case Manager Entity Notes	View	cm:action:entity-note:read:* - Frontend cm:resource:entity-note:read:* - Backend	Allows the user to see Notes widget (e.g. customer notes widget) on an entity details page (e.g., Customer details page).
	Create	cm:action:entity-note:create:* - Frontend cm:resource:entity-note:create:* - Backend	Allows the user to assign notes to data entities.
Case Manager Entity Data	View	(1) cm:section:customer-details:read:* - Frontend (2) cm:entity-data:<entity_type>:read:* - Backend (entity_type available right now are accounts, cards and customers)	(1) Lets the user see the customer page (2) Lets the user read data about an entity of a given type (e.g. customers, cards, etc.) in places such as the customer page
Case Manager Entity Files	View	cm:resource:file:entity-file:read:*	Lets the user read files associated with entities (e.g. customers, cards, etc.) in places such as the customer page.
Case Manager Cases Sources	View	cm:resource:case-source:read:* - Backend cm:section:settings-case-source:read:* - Frontend	Lets the user have access to the case sources page and list case sources
	Create	cm:resource:case-source:create:* - Backend cm:section:settings-case-source:create:* - Frontend	Lets the user create new case sources
	Update		

		cm:resource:case-source:update:* - Backend cm:section:settings-case-source:update:* - Frontend	Lets the user edit (enable/disable) existing case sources.
Case Manager Custom Extensions	onEventStatusUpdate	cm:action:extension:onEventStatusUpdate	Lets the user execute the custom extension given by onEventStatusUpdate
Case Manager Channel Based Permissions	Read and Write	cm:channel:<channel_id>:read-write	Lets the users see and edit <channel_id> events and artifacts (cards, digital action transfers, inbound-payments, non-monetary artifacts)
	Read Only	cm:channel:<channel_id:resource:group:readel_id>:read-only	Users can see <channel_id>'s events and artifacts, but cannot edit them (except notes and file-uploading)
	None	cm:channel:<channel_id:resource:group:readel_id>:none	Users do not have access to <channel_id>
Case Manager Access Groups	Search	cm:resource:group:read:*	Lets the user search groups.
Case Manager Multi-tenancy	Landlord	cm:resource:landlord:*	Lets the user have landlord permissions
	Tenant	cm:resource:tenant:read:*	Lets the user read the tenant list.
Case Manager Multiple State Machines	Change Status	cm:state-machine:event-status:write:<STATEMACHINE>	Lets the user change the status for a given state machine (whose id is <STATEMACHINE>)
	Read	cm:state-machine:event:read:<state-machine-id>	Enables the user to read the state machine information.
	List Reasons	cm:state-machine:status-reason:read:<state-machine-id>	Enables the user to list the status reasons for a state machine with a given id.
	Create Reasons	cm:state-machine:status-reason:write:<state-machine-id>	Enables the user to create a status reason for a state machine with a given id.
Case Manager Tokenizer	Reveal	(1) cm:action:reveal-<field_path> (2) cm:resource:reveal-all (3) cm:resource:reveal-<FIELD> (4) cm:resource:reveal:* (5) cm:resource:search-by:<FIELD>	(1) Lets the user see the reveal icon to reveal a field. (2) Lets the user automatically reveal all encrypted fields when entering an event details page. (3) Lets the user reveal a field value using a tokenizer. (The <field_path> has to be replaced with the field path in the object) (4) Give user all permissions regarding the reveal action (5) Lets the user perform a search operation by a specified field in plain text using a tokenizer. This permission combined with user permission cm:resource:search-by:<FIELD> allows users to search for all tokenized elements.
Case Manager Details Page	Widgets	(1) cm:action:self-service-config:advanced-mode (2) cm:resource:self-service-config	(1) Lets the user have access to the Advanced edit mode in the UI. (2) Lets the user list active preferences

Case Manager Login and Logout	Login and Logout	(1) security:ownership:read (2) security:permissions:read	(1) Lets the user see the ownership de Pulse user groups (toggle "advanced" (2) Lets the user read the permissions
Case Manager Manage Message	Manage Message	(1) cm:section:settings-message:read:* (2) cm:resource:message:read:* (3) cm:action:settings-message:create:* (4) cm:resource:message:create:* (5) cm:action:settings-message:update:* (6) cm:resource:message:update:* (7) cm:action:settings-message:delete:* (8) cm:resource:message:delete:*	(1) Lets the user see the Messages pa the Settings section. (2) Lets the user read messages. (3) Lets the user create new message Settings section. (4) Lets the user create new message (5) Lets the user update messages in Settings section. (6) Lets the user update messages. (7) Lets the user delete messages in t Settings section. (8) Lets the user delete messages.
Case Manager General Permissions	Dashboards	cm:section:dashboard-analyst-performance:* cm:section:dashboard-business-overview:* cm:section:dashboard-psd2:* cm:section:rules-monitoring-rules-filter:* cm:resource:dashboards-user-sync:update:* cm:section:rules-monitoring-transactions-filter:*	Allows the users to see the dashboard (Requires enabling Insights)
	Get Next	cm:section:review-next:read:*	Lets the user see the review next func
	UI Configuration	cm:resource:configuration:read:* cm:resource:configuration:create:* cm:resource:configuration:update:* cm:resource:configuration:delete:* cm:action:gui-config:edit cm:resource:gui-config:edit cm:resource:gui-config:reset-to-default cm:resource:gui-config:list-active:*	Lets the user read and modify the UI configuration.
	Language Configuration	cm:resource:language:read:* cm:resource:language:create:* cm:resource:language:delete:* cm:resource:language:update:*	Lets the user read and modify the ava languages.
	Time Configuration	cm:resource:timezone:read:* cm:resource:timezone:create:*	Lets the user read and modify timezon

	cm:resource:timezone:delete:* cm:resource:timezone:update:*	
Translated Messages	cm:resource:message:read:*	Lets the user read the translated mess
Event Status	cm:resource:event-status:create:*	Lets the user create status for events.
Edit Resource	cm:action:edit-resource:update:*	Lets the user edit the resource.
Custom Link	cm:action:link-to	Lets the user navigate to a custom link
Pulse App	(1) cm:resource:pulse-app:read:* (2) cm:resource:pulse-rules:read:*	(1) Gets the Pulse application status a (2) Gets the Pulse application rules
Session	cm:resource:session:read:* cm:resource:session:create:* cm:resource:session:update:* cm:resource:session:delete:*	Lets the user read and modify session information in Case Manager.
Event Visibility	cm:resource:event-visibility cm:resource:event-visibility:create:*	Gives the user full event visibility.
Customer Page	cm:section:customer:read:*	Lets the user have access to Customer details
Event Details	cm:section:event-details:*	Lets the user have access to all Event operations
	cm:section:event-details:read:* cm:section:event:*	Lets the user have access to read Eve Details
	cm:resource:event-users:read:*	Retrieves a list of users that can be us assignment according to the tenant pr
	cm:resource:event-queues:read:*	Retrieves a list of queues that are ass with an event's tenant.
	cm:section:event:read:*	Lets the user have access to read Eve Details
	cm:section:event:create:*	Lets the user have access to create E Details
	cm:section:event:delete:*	Lets the user have access to delete E Details
	cm:section:event:update:*	Lets the user have access to update E Details
Fraud Alerts	cm:section:fraud-alerts:*	Lets the user have access to all Fraud operations
	cm:section:fraud-alerts:read:*	Lets the user have access to read Fra
Rules Block	cm:resource:configuration-rules-block:read:*	Lets the user read the configuration of blocks.
Search	cm:action:search-by-schema.card_pan	Lets the user search by Card Pan
Assign	cm:resource:assign-no-steal:*	

			Allows users to assign unassigned events to themselves and to others.
	Export Entity	cm:resource:entity-export:read:* cm:action:entity-export:create:*	Lets the user export the results from an entity's search page.
	Edit Mode	cm:action:self-service-config:normal-mode	Lets the user have access to the Normal mode in the UI.
Pulse App Management	Create	application:apps:create	Permission to create new applications.
	Delete	application:apps:delete	Permission to delete applications.
	Manage	application:apps:manage	Permission to start/stop/publish/export applications.
	Manage	application:apps:all-nodes-publish	Permission to publish applications in a non-rolling fashion (all nodes at the same time).
	View	application:apps:read	Permission to read applications.
	Update	application:apps:update	Permission to update applications.
	Import	application:apps:partialImport	Permission to partially import applications.
	Export	application:apps:partialExport	Permission to partially export applications.
	All CRUD Permissions	application:*	Permission to perform all CRUD actions on application models.
Read Applications	application:*.read	Permission to read applications.	No
Pulse Sandbox Evaluations	View	application:sandbox_evaluations:read	Permission to read sandbox evaluations.
	Create	application:sandbox_evaluations:create	Permission to create sandbox evaluations.
	Update	application:sandbox_evaluations:update	Permission to update sandbox evaluations.
	Delete	application:sandbox_evaluations:delete	Permission to delete sandbox evaluations.
Pulse Custom Services	View	application:dependencies:read	Permission to read custom service.
	Create	application:dependencies:create	Permission to create new custom service.
	Update	application:dependencies:update	Permission to update custom service.
	Delete	application:dependencies:delete	Permission to delete custom service.
Pulse Application History	View	application:history:global:read application:history:resource:read	Permission to read history log application wide. Permission to read history log of a single resource.
Pulse Job Executions	Create	application:jobexecutions:create	Permission to create new job execution.
	View	application:jobexecutions:read	Permission to read job execution.
	Update	application:jobexecutions:update	Permission to update job execution.
	Delete	application:jobexecutions:delete	Permission to delete job execution.
	Start	application:jobexecutions:start	Permission to start job executions
	Abort	application:jobexecutions:abort	Permission to abort job executions
	View	application:job_profiles:read	Permission to read job profiles.

	Pulse Job Profiles	Create	application:job_profiles:create	Permission to create job profiles.
		Update	application:job_profiles:update	Permission to update job profiles.
		Delete	application:job_profiles:delete	Permission to delete job profiles.
	Pulse Managed Lists	View	application:managedlists:read	Permission to read managed lists.
		Create	application:managedlists:create	Permission to create managed lists.
		Update	application:managedlists:update	Permission to update managed lists.
		Delete	application:managedlists:delete	Permission to delete managed lists.
	Pulse Managed List Items	View	application:managedlistitems:read	Permission to read managed list items.
		Create	application:managedlistitems:create	Permission to create managed list items.
		Update	application:managedlistitems:update	Permission to update managed list items.
		Delete	application:managedlistitems:delete	Permission to delete managed list items.
		Decrypt	application:managedlistitems:decrypt	Permission to download encrypted values of managed list items in plain text format. Plain text download needs to be enabled in the pulse.global.lists.allowListDownloadInPlainText property.
		View Revision	application:managedlistitems:revision:read	Permission to read managed list revisions.
		Update Revision	application:managedlistitems:revision:update	Permission to update managed list revisions.
		Create Revision	application:managedlistitems:revision:create	Permission to create managed list revisions.
	Pulse Outcome Combinators	View	application:outcome_combinators:read	Permission to read outcome combinators.
		Create	application:outcome_combinators:create	Permission to create a new outcome combinator.
		Update	application:outcome_combinators:update	Permission to update outcome combinators.
		Delete	application:outcome_combinators:delete	Permission to delete a outcome combinator.
	Pulse Workflows	View	application:rte_workflows:read	Permission to read workflow.
		Create	application:rte_workflows:create	Permission to create new workflow.
		Update	application:rte_workflows:update	Permission to update workflow.
		Delete	application:rte_workflows:delete	Permission to delete workflow.
	Pulse User Management	View	security:users:read	Permission to read user.
		Create	security:users:create	Permission to create new user.
		Update	security:users:update	Permission to update user.
		Delete	security:users:delete	Permission to delete user.
	Pulse Admin Rights	Admin	admin:view	Permission to access the administrative screens.
		Read Logs	admin:logs:read	Permission that grants access to the logs.
		Manage Cluster	admin:cluster:manage	Permission that grants management access to the cluster.
		Read Cluster	admin:cluster:read	Permission that grants read access to the cluster.
		Delete Configuration	admin:configuration:delete	Permission to delete configurations on the administration screens.

		Read Configuration	admin:configuration:read	Permission to read configurations on the administration screens.
		Update Configuration	admin:configuration:update	Permission to update configurations on the administration screens.
		Deploy Services	admin:deploy	Permission to deploy services through the REST API.
		Reload Security	admin:security:reload	Permission to reload security through the REST API.
		Control Services	admin:service:control	Permission to start and stop services through the Administration API.
	Pulse Tabs	Management Tabs	pulseviews:management:tabs:*	Permission to allow the user to access the pulseviews tabs.
	Pulse SSR Audit	View	(1) application:ssr_audit:privilegedView (2) application:ssr_audit:read	(1) Permission to read Self-Service Rule Audit entries in privileged views, for instance, retrieving the audit respective to all Rules present in a given application. (2) Permission to read self-service rule audit entries.
	Pulse SSR Test	View	application:ssr_test:read	Permission to read self-service rule test results.
		Run	application:ssr_test:run	Permission to run a self-service rule test.
		Update	application:ssr_test:update	Permission to update self-service rule test results.
	Pulse Security	Security	application:streams:read:*	Permission to read streams (stream id corresponds to a schema)
			security:tenants:read	Permission to read tenants.
			security:audit:*	Permission to read audit logs.
			userid:management	Permission to manage users
			security:roles:read	Permission to read role
			security:logging:update	Permission to update the logging level
			cm:resource:secure-metadata	Lets the user see encrypted metadata
			cm:element:tenant:read:*	Lets the user access UI elements according to landlords.
	Pulse Datascience Datasources	View	application:datascience_datasources:read	Permission to read data science data sources.
		Create	application:datascience_datasources:create	Permission to create data science data sources.
		Update	application:datascience_datasources:update	Permission to update data science data sources.
		Delete	application:datascience_datasources:delete	Permission to delete data science data sources.
	Pulse Datascience Evaluation Metrics	View	application:datascience_evaluationmetrics:read	Permission to read data science evaluation metrics.
		Create	application:datascience_evaluationmetrics:create	Permission to create data science evaluation metrics.
		Update	application:datascience_evaluationmetrics:update	

			Permission to update data science evaluation metrics.
	Delete	application:datascience_evaluationmetrics:delete	Permission to delete data science evaluation metrics.
Pulse Datascience Model Projects	View	application:datascience_modelprojects:read	Permission to read data science model projects.
	Create	application:datascience_modelprojects:create	Permission to create data science model projects.
	Update	application:datascience_modelprojects:update	Permission to update data science model projects.
	Delete	application:datascience_modelprojects:delete	Permission to delete data science model projects.
Pulse Datascience Model Projects Evaluations	View	application:datascience_modelprojects_evaluations:read	Permission to read data science model evaluations.
	Create	application:datascience_modelprojects_evaluations:create	Permission to create data science model evaluations.
	Update	application:datascience_modelprojects_evaluations:update	Permission to update data science model evaluations.
	Delete	application:datascience_modelprojects_evaluations:delete	Permission to delete data science model evaluations.
Pulse Datascience Model Projects Feature Importance	View	application:datascience_modelprojects_featureimportance:read	Permission to read feature importance.
	Create	application:datascience_modelprojects_featureimportance:create	Permission to create feature importance.
	Update	application:datascience_modelprojects_featureimportance:update	Permission to update feature importance.
	Delete	application:datascience_modelprojects_featureimportance:delete	Permission to delete feature importance.
Pulse Datascience Model Projects Hyperparameter Tuning	View	application:datascience_modelprojects_hyperparam_tuning:read	Permission to read hyperparameter tuning.
	Create	application:datascience_modelprojects_hyperparam_tuning:create	Permission to create hyperparameter tuning.
	Update	application:datascience_modelprojects_hyperparam_tuning:update	Permission to update hyperparameter tuning.
	Delete	application:datascience_modelprojects_hyperparam_tuning:delete	Permission to delete hyperparameter tuning.
Pulse Datascience Model Projects Hyperparameter Tuning Eval	View	application:datascience_modelprojects_hyperparam_tuning_eval:read	Permission to read hyperparameter tuning evaluation.
	Create	application:datascience_modelprojects_hyperparam_tuning_eval:create	Permission to create hyperparameter tuning evaluation.
	Update	application:datascience_modelprojects_hyperparam_tuning_eval:update	Permission to update hyperparameter tuning evaluation.
	Delete	application:datascience_modelprojects_hyperparam_tuning_eval:delete	Permission to delete hyperparameter tuning evaluation.
Pulse Datascience Model Projects Models	View	application:datascience_modelprojects_models:read	Permission to read Data Science models.
	Create	application:datascience_modelprojects_models:create	Permission to create Data Science models.
	Update	application:datascience_modelprojects_models:update	Permission to update Data Science models.
	Delete	application:datascience_modelprojects_models:delete	Permission to delete Data Science models.

Pulse Datascience Model Projects Targets	View	application:datascience_modelprojects_targets:read	Permission to read Data Science targets.
	Create	application:datascience_modelprojects_targets:create	Permission to create Data Science targets.
	Update	application:datascience_modelprojects_targets:update	Permission to update Data Science targets.
	Delete	application:datascience_modelprojects_targets:delete	Permission to delete Data Science targets.
Pulse Datascience Plans	View	application:datascience_plans:read	Permission to read Data Science Plans.
	Create	application:datascience_plans:create	Permission to create Data Science Plans.
	Update	application:datascience_plans:update	Permission to update Data Science Plans.
	Delete	application:datascience_plans:delete	Permission to delete Data Science Plans.
	Run	application:datascience_plans:run	Permission to run Data Science Plans.
Pulse Datascience Plans Executions	View	application:datascience_plans_executions:read	Permission to read Data Science Plans Execution.
	Create	application:datascience_plans_executions:create	Permission to create Data Science Plans Execution.
	Update	application:datascience_plans_executions:update	Permission to update Data Science Plans Execution.
	Delete	application:datascience_plans_executions:delete	Permission to delete Data Science Plans Execution.
Pulse Datascience Rules Projects	View	application:datascience_rulesprojects:read	Permission to read data science rules projects.
	Create	application:datascience_rulesprojects:create	Permission to create data science rules projects.
	Update	application:datascience_rulesprojects:update	Permission to update data science rules project.
	Delete	application:datascience_rulesprojects:delete	Permission to delete data science rules projects.
	Self Service Publish	application:datascience_rulesprojects:self-service-publish	Permission to publish self-service rules projects.
Pulse Datascience Rules Projects Evaluations	View	application:datascience_rulesprojects_evaluations:read	Permission to read data science rules evaluations.
	Create	application:datascience_rulesprojects_evaluations:create	Permission to create data science rules evaluations.
	Update	application:datascience_rulesprojects_evaluations:update	Permission to update data science rules project evaluations.
	Delete	application:datascience_rulesprojects_evaluations:delete	Permission to delete data science rules evaluations.
Pulse Datascience Rules Projects Rules	View	application:datascience_rulesprojects_rules:read	Permission to read data science rules.
	Create	application:datascience_rulesprojects_rules:create application:datascience_rulesprojects_rules:create:*	Permission to create Data Science Rules.
	Update	application:datascience_rulesprojects_rules:update application:datascience_rulesprojects_rules:update:*	Permission to update data science rules.
	Delete	application:datascience_rulesprojects_rules:delete	Permission to delete data science rules.
	View	application:datascience_rulesprojects_snapshots:read	Permission to read data science rules snapshots.

Pulse Datascience Rules Projects Snapshots	Create	application:datascience_rulesprojects_snapshots:create	Permission to create data science rule snapshots.
	Update	application:datascience_rulesprojects_snapshots:update	Permission to update data science rule project snapshots.
	Delete	application:datascience_rulesprojects_snapshots:delete	Permission to delete data science rule snapshots.
Pulse Datascience Rules Projects Templates	View	application:datascience_rulesprojects_templates:read	Permission to read data science rule templates.
	Create	application:datascience_rulesprojects_templates:create	Permission to create data science rule templates.
	Update	application:datascience_rulesprojects_templates:update	Permission to update data science rule project templates.
	Delete	application:datascience_rulesprojects_templates:delete	Permission to delete data science rule templates.
Pulse Datascience Schemas	View	application:datascience_schemas:read	Permission to read Data Science Schemas.
	Create	application:datascience_schemas:create	Permission to create Data Science Schemas.
	Update	application:datascience_schemas:update	Permission to update Data Science Schemas.
	Delete	application:datascience_schemas:delete	Permission to delete Data Science Schemas.
Pulse Datascience Tag Groups	View	application:datascience_tag_groups:read	Permission to read Data Science Tag Groups.
	Create	application:datascience_tag_groups:create	Permission to create Data Science Tag Groups.
	Update	application:datascience_tag_groups:update	Permission to update Data Science Tag Groups.
	Delete	application:datascience_tag_groups:delete	Permission to delete Data Science Tag Groups.
Pulse Datascience Tag Types	View	application:datascience_tag_types:read	Permission to read Data Science Tag Types.
	Create	application:datascience_tag_types:create	Permission to create Data Science Tag Types.
	Update	application:datascience_tag_types:update	Permission to update Data Science Tag Types.
	Delete	application:datascience_tag_types:delete	Permission to delete Data Science Tag Types.
Pulse Datascience White Box Explanations	View	application:datascience_white_box_explanations:read	Permissions to read White Box Explanations configuration.
	Create	application:datascience_white_box_explanations:create	Permissions to create White Box Explanations configuration.
	Update	application:datascience_white_box_explanations:update	Permissions to update White Box Explanations configuration.
	Delete	application:datascience_white_box_explanations:delete	Permissions to delete White Box Explanations configuration.