

On this page

Custom UDFs

Tmx

`Tmx.risk(String reasonCodes)`

Receives a String `reasonCodes`, which is a concatenation of 3 character reason codes, fetches the risk score of each and sums them all, returning a transaction risk score.

FivMarkers

```
/**
 * Checks whether the FIV marker is present and not expired.
 */
*
* @param fivMarkerCode The FIV marker code being looked for.
* @param fivMarkersJson Customer FIV markers list, encoded as JSON string.
*
* In practice this should always be the value of the same
* Pulse field - 'customer_fiv_markers'
* @return true if the FIV marker is part of the Customer FIV markers list and has not expired,
* false otherwise.
*/
FivMarkers.getIfNotExpired(String fivMarkerCode, String fivMarkersJson)
```

Copy

Checks whether the specified `FivMarker` exists in the customer's FIV markers JSON data and, if present, validates its expiration date if present.

Example

In Pulse Rule variables:

```
pip_fiv_marker_present = FivMarkers.getIfNotExpired("PIP", customer_fiv_markers)
```

Copy

Where "PIP" is the FIV marker code we're looking for in `customer_fiv_markers`.



In practice we always expect this UDF to be called with `customer_fiv_markers` as the second argument.

Implementation Notes

- A FIV marker is considered expired as soon as the current date reaches expiration date, meaning if its expiration date is today, it is considered expired.
- We don't expect multiple entries with the same FIV marker code in `customer_fiv_markers`, but, if we do and in order to have consistent behavior, we only consider it not expired if none of the entries have expired.
- In entries in the `customer_fiv_markers` list are malformed according to the expected schema they will be disregarded. In that case, we'll still make a best effort to consider other valid entries in the array.