

On this page

HSBC-3430-Add-support-for-distinct-RabbitMQ-brokers-for-Pulse-and-Case-Manager

Add support for distinct RabbitMQ brokers for Pulse and Case Manager

Feature HSBC-3430

We've added support for distinct RabbitMQ brokers for Pulse and Case Manager. The following Ansible variables were changed:

Component	New Ansible Variable	Old Ansible Variable
Pulse	<code>rabbitmq_casemanager_brokers</code>	N/A
Case Manager	<code>rabbitmq_casemanager_brokers</code>	<code>rabbitmq_brokers</code>
Logstash	<code>rabbitmq_casemanager_brokers</code>	<code>rabbitmq_brokers</code>
Logstash	<code>rabbitmq_casemanager_username</code>	<code>rabbitmq_insights_logstash_username</code>
Logstash	<code>rabbitmq_casemanager_password</code>	<code>rabbitmq_insights_logstash_password</code>
Logstash	<code>rabbitmq_casemanager_vhost_blue</code>	<code>rabbitmq_pulse_vhost_blue</code>
Logstash	<code>rabbitmq_casemanager_vhost_green</code>	<code>rabbitmq_pulse_vhost_green</code>

Note that `rabbitmq_brokers` is still required in Pulse and defines the RabbitMQ brokers for Pulse internal communication.

For more details please refer to:

- [Pulse Configuration Recommendations](#)
- [Case Manager Configuration Recommendations](#)
- [Data Extraction Pipelines Configurations](#)

⚠️ Default values for the new variables

The new Ansible variables default to the variables they are replacing (e.g. `rabbitmq_casemanager_brokers` defaults to `rabbitmq_brokers` , if not defined). This means that this change is backwards compatible and the default behaviour is to continue using a single RabbitMQ for all components.

For clarity, we recommend changing the variable names in the HSBC Ansible Variables files to use the new ones instead.