

On this page

Configuration Recommendations

Ansible



Available ansible variables for running the ansible playbook.

Variable	Default Value
ansible_user	feedzai
ansible_local_user	{{ ansible_user }}
batch_processor_install_path	"/opt/feedzai"
batch_processor_home_path	"{{ batch_processor_install_path }}/batch-processor-{{ batch_processor_version }}"
batch_processor_port	5567
batch_processor_jvmopts	""
database_batch_processor_engine	"com.feedzai.commons.sql.abstraction.engine.impl.PostgreSQLEngine"
database_batch_processor_jdbc	"jdbc:postgresql://{{ database_batch_processor_hostname }}:{{ database_batch_processor_port }}/{{ database_batch_processor_database }}"
database_batch_processor_jdbc_opts	[cancelSignalTimeout=2, connectTimeout=2, loadBalanceHosts=true, loginTimeout=10, socketTimeout=60, to

Variable	Default Value
database_batch_processor_username	"batchprocessor"
database_batch_processor_password	"secret"
database_batch_processor_schema	"batchprocessor"
database_batch_processor_hostname	"postgres"
database_batch_processor_port	"5432"
database_batch_processor_database_name	"feedzai"
database_batch_processor_schemapolicy	none
batch_processor_merc_static_tenants	["feedzai"]
batch_processor_merc_retry_cron	"0 0 ? *"
batch_processor_merc_retry_max_tries	3

Variable	Default Value
batch_processor_merc_cron	"0 30 2 * ? "
batch_processor_rds_config_host	reference-data
batch_processor_rds_config_port	8080
batch_processor_rds_default_jwt	"Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWUiOiIxMjM0NTY3ODkwIiwibmFtZSI6IkpvcyY8gU2FudG9zIiwiaWF0IjoiMTY4MjM0NTY3ODkwIn0="
batch_processor_rds_tenant_keys	{ key: feedzai, value: Bearer eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWUiOiIxMjM0NTY3ODkwIiwibmFtZSI6IkpvcyY8gU2FudG9zIiwiaWF0IjoiMTY4MjM0NTY3ODkwIn0="
batch_processor_pulse_jwt_private_key	Default value hidden due to length
batch_processor_pulse_jwt_algorithm	"RS512"

Variable	Default Value
batch_processor_pulse_jwt_kid	"feedzai-internal"
batch_processor_pulse_jwt_issuer	"feedzai"
pulse_batchprocessor_username	"batchprocessor"
pulse_batchprocessor_password	"Secret1!"
pulse_scheme	"http"
pulse_port	8080
pulse_elb	"pulse"
pulse_host	"{{ pulse_elb }}"
pulse_url	"{{ pulse_scheme }}://{{ pulse_elb }}:{{ pulse_port }}"

note

(*) More details on the supported algorithms can be found at [JWSAlgorithm](#). Only RS256, RS384 and RS512 are supported.

Quartz Cron Scheduling



For more details on Quartz Cron Scheduling expressions, refer to the [official Quartz CronTrigger Tutorial](#).

Field	Mandatory	Allowed Values	Description
Seconds	X	0-59	The cron expression for second
Minutes	X	0-59	The cron expression for minute
Hours	X	0-23	The cron expression for hour
Day of Month	X	1-31	The cron expression for day of month (**)
Month	X	1-12 or JAN-DEC	The cron expression for month
Day of Week	X	1-7 (1=SUN, 7=SAT) or SUN-SAT	The cron expression for day of week (**)
Year		blank, 1970-2099	The cron expression for year



(**) In Quartz, you must use the ? character in either the Day of Month or Day of Week field to indicate "no specific value". You cannot specify both fields simultaneously, as they conflict!
