

On this page

Configuration Recommendations



For a complete reference check the [official Configuration Guide](#).

Ansible



Available ansible variables for running the ansible playbook.

Variable	Default Value
ansible_user	feedzai
ansible_local_user	{{ ansible_user }}
cm_install_path	"/opt/feedzai"
cm_home_path	"{{ cm_install_path }}/product-cm-{{ cm_version }}"
cm_java_options	"-Xms4g -Xmx4g"
database_casemanager_engine	"com.feedzai.commons.sql.abstraction.engine.impl.PostgreSqlEngine"
database_casemanager_jdbc	"jdbc:postgresql://{{ database_casemanager_hostname }}:{{ database_casemanager_port }}/{{ database_casemanager_database }}"
database_casemanager_jdbc_opts	[currentSchema={{ database_casemanager_schema }}, loginTimeout=10, connectTimeout=2, cancelQueryTimeout=30, loadBalanceHosts=true, reWriteBatchedInserts=true]
database_casemanager_username	casemanager

Variable	Default Value
database_casemanager_password	secret
database_casemanager_schema	casemanager
database_casemanager_hostname	"postgres"
database_casemanager_port	"5432"
database_casemanager_database_name	"feedzai"
database_casemanager_schemapolicy	"none"
database_casemanager_pool_size	"24"
database_casemanager_pool_lazy	false
database_casemanager_reconnect_on_lost	true

Variable	Default Value
database_casemanager_max_number_retries	"30"
database_casemanager_retry_interval	"5000"
database_casemanager_ro_jdbc	"jdbc:postgresql://{{ database_casemanager_ro_hostname }}:{{ database_casemanager_ro_port }}/{{ database_casemanager_ro_schema }}"
database_casemanager_jdbc_ro_opts	[currentSchema={{ database_casemanager_schema }}, loginTimeout=10, connectTimeout=2, cancelQueryOnTimeout={{ database_casemanager_cancel_query_on_timeout }}, database_casemanager_jdbc_ro_target_server_type }, loadBalanceHosts=true]
database_casemanager_jdbc_ro_target_server_type	master
database_casemanager_ro_username	{{ database_casemanager_username }}
database_casemanager_ro_password	{{ database_casemanager_password }}
database_casemanager_ro_schema	{{ database_casemanager_schema }}
database_casemanager_ro_hostname	{{ database_casemanager_hostname }}
database_casemanager_ro_port	{{ database_casemanager_port }}

Variable	Default Value
database_casemanager_ro_database_name	{{ database_casemanager_database_name }}
database_casemanager_ro_schemapolicy	{{ database_casemanager_schemapolicy }}
database_casemanager_ro_pool_size	{{ database_casemanager_pool_size }}
database_casemanager_ro_pool_lazy	{{ database_casemanager_pool_lazy }}
database_casemanager_ro_reconnect_on_lost	{{ database_casemanager_reconnect_on_lost }}
database_casemanager_ro_max_number_retries	{{ database_casemanager_max_number_retries }}
database_casemanager_ro_retry_interval	{{ database_casemanager_retry_interval }}

Variable	Default Value
cm_url	"http://localhost:8090"
reference_data_servers	{{ groups['reference-data'] }}
reference_data_port	"{{ reference_data_app_port }}"
reference_data_url	"http://{{reference_data_servers}}:{{reference_data_port}}""
reference_data_casemanager_jwt_token	"eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJzdWUiOiIxMjY3ODkwIiwibmFtZSI6IkpvaGVyZW8gU2FiZXQxLnVudC5kaSIsImNpdCI6bnVudC5kaSIsImV4cCI6MTkxOTAwMDAwfQ=="
cm_jetty_http_port	8080
pulse_casemanager_username	casemanager
pulse_casemanager_password	Secret1!
rabbitmq_casemanager_brokers	{{ rabbitmq_brokers }}
rabbitmq_casemanager_username	cm
rabbitmq_casemanager_password	secret
rabbitmq_casemanager_vhost	cm
rabbitmq_casemanager_use_quorum_queues	false

Variable	Default Value
jks_store_password	
cm_truststore_path	
pulse_internal_url	{{ pulse_url }}
pulse_url	"{{ pulse_scheme }}://{{ pulse_elb }}:{{ pulse_port }}"
pulse_scheme	"http"
pulse_elb	"pulse"
pulse_port	8080
cm_secret_value	ed178d2d1b6e5d036b0aab4402212704
cm_properties_to_encrypt	[database_casemanager_password, database_casemanager_ro_password, pulse_casemanager_password, pulse_casemanager_ro_password, pulse_tokenizer_casemanager_jwt_token]
casemanager_api_url	{{ cm_url }}

Variable	Default Value
casemanager_api_username	{{ pulse_casemanager_username }}
casemanager_api_password	{{ pulse_casemanager_password }}
cm_liquibase_rollback	false
cm_multi_tenancy_enabled	true
cm_loggers	{}
cm_probes_log_level	"OFF"

Variable	Default Value
cm_probes_output_file_name	"cm-probes.log"

Performance configuration

With the inclusion of new use cases it is expected that Case Manager sizing to be updated. Aside from bare metal sizing updates, Case Manager also provides performance configurations that allow fine tuning of the various nodes.



Changing any of these configurations can have a performance impact in Case Manager. They should only be changed in agreement with the project team.

Please find below a description of each of the available configurations.

Variable	Default Value	Description
cm_performance_event_worker_threads	8	The number of workers that should be used to asynchronously store events into event storage.
cm_performance_queue_prefetch_size	200	The number of messages Case Manager fetches from RabbitMQ.
cm_performance_batch_storage_size	300	The size of the batch, i.e. the number of entries the batch can hold after which a flush will occur.
cm_performance_batch_storage_timeout	1000	The batch timeout, i.e. the time after which a batch flush will occur, regardless of the amount of entries present in it.
cm_performance_batch_flush_workers	4	The number of workers that should be used to asynchronously execute batch flush callback operations.
cm_performance_batch_flush_queue_size	5000	The size of the buffer that holds events to be added to the batch.
cm_performance_event_storage_queue_size	200	The size of the buffer that holds events to be added to the batch.
cm_performance_event_storage_batch_size	500	

Variable	Default Value	Description
		The size of the batch, i.e. the number of entries the batch can hold after which a flush will occur.
cm_performance_event_storage_batch_timeout	1000	The batch timeout, i.e. the time after which a batch flush will occur, regardless of the amount of entries present in it.
cm_performance_event_storage_batch_threads	1	The batch threads, i.e. the number of threads getting entries of the queue and writing to the batch.
cm_performance_related_max_last_flush_secs	10	Maximum period (in seconds) that notifier should wait before sending the RTS notification.
cm_performance_max_queued_explanations	5000	The Number of queued explanations for persistence by the explanations batch.
cm_performance_max_related_transactions	500	The maximum number of related transactions to an event to fetch.
cm_performance_explanations_queue_size	5000	The size of the buffer that holds events to be added to the batch.
cm_performance_explanations_batch_size	300	The size of the batch, i.e. the number of entries the batch can hold after which a flush will occur.
cm_performance_explanations_batch_timeout	1000	The batch timeout, i.e. the time after which a batch flush will occur, regardless of the amount of entries present in it.
cm_performance_explanations_batch_threads	1	The batch threads, i.e. the number of threads getting entries of the queue and writing to the batch.
cm_performance_automation_worker_threads	4	The batch threads, i.e. the number of threads getting entries of the queue and writing to the batch.
cm_performance_automation_batches_queue_size	200	The size of the buffer that holds events to be added to the batch.
cm_performance_automation_batches_batch_size	500	The size of the batch, i.e. the number of entries the batch can hold after which a flush will occur.
cm_performance_automation_batches_batch_timeout	1000	The batch timeout, i.e. the time after which a batch flush will occur, regardless of the amount of entries present in it.
cm_performance_automation_batches_batch_threads	1	The batch threads, i.e. the number of threads getting entries of the queue and writing to the batch.
cm_performance_automation_rule_cache	0	Automation cache value until automation rules are refreshed in memory.
cm_performance_max_queued_automations	5000	Maximum number of queued automations for execution by the automation worker threads
cm_performance_audit_batches_queue_size	200	The size of the buffer that holds events to be added to the batch.
cm_performance_audit_batches_batch_size	300	The size of the batch, i.e. the number of entries the batch can hold after which a flush will occur.
cm_performance_audit_batches_batch_timeout	1000	The batch timeout, i.e. the time after which a batch flush will occur, regardless of the amount of entries present in it.
cm_performance_audit_batches_batch_threads	1	The batch threads, i.e. the number of threads getting entries of the queue and writing to the batch.
cm_performance_ignore_event_updates	false	Whether event updates should be ignored, and thus, the event ingestion process optimized.

Variable	Default Value	Description
cm_performance_disable_auditing_without_users	false	Whether the audit for actions without users should be skipped in the database.
cm_performance_enable_db_heuristic_for_event_queue_search	false	Whether an explicit <code>queueId neq null</code> should be added to improve queue searches.

Quartz Cron Scheduling🔗



For more details on Quartz Cron Scheduling expressions, refer to the [official Quartz CronTrigger Tutorial](#).

Field	Mandatory	Allowed Values	Description
Seconds	X	0-59	The cron expression for <code>second</code>
Minutes	X	0-59	The cron expression for <code>minute</code>
Hours	X	0-23	The cron expression for <code>hour</code>
Day of Month	X	1-31	The cron expression for <code>day of month</code> (**)
Month	X	1-12 or JAN-DEC	The cron expression for <code>month</code>
Day of Week	X	1-7 (1=SUN, 7=SAT) or SUN-SAT	The cron expression for <code>day of week</code> (**)
Year		blank, 1970-2099	The cron expression for <code>year</code>



(**) In Quartz, you must use the `?` character in either the Day of Month or Day of Week field to indicate "no specific value". You cannot specify both fields simultaneously, as they conflict!