

On this page

Requirements



For a complete list of the Case Manager requirements, please refer to the [official product documentation](#).

Service Requirements

This service requires the following software to run.

Java Environment

OpenJDK SE Development Kit version 1.8, with the following vendors (with their latest hotfix versions):

- Azul Zulu [rpm](#) [zip](#) [tar.gz](#)
- Azul Platform Prime (formerly Zing)
- Amazon Corretto
- Oracle



Product tests are done with the **Azul Zulu JVM**.

The following versions are not supported, and are known to have problems:

- 1.8.0u242
- 1.8.0u121
- 1.8.0u60
- 1.8.0u45 and earlier

Non-listed releases are either not supported or haven't been put to extensive testing.

Setup Requirements

RDBMS

Case Manager uses [PulseDB](#) for database access, meaning that Case Manager can be deployed on top of:

- Oracle 19.3 (or higher)
- PostgreSQL 14.20 (or higher) - driver version 42.7.10 should be used.
- SQL Server 2017 GA (or higher)
- H2 1.4.200 (or higher) - only for test/evaluation purposes.



Feedzai validates the product primarily against H2 and PostgreSQL.



Before selecting a database engine, make sure you understand how different database systems are [supported by our PulseDB](#).

RabbitMQ

RabbitMQ is the messaging platform Case Manager uses to ingest events from Pulse, and also to propagate events to other downstream services.

The following RabbitMQ and Erlang versions are supported:

- RabbitMQ - 3.11.13 with Erlang - 25.3.2.21+
- RabbitMQ - 3.9.8 with Erlang - 24.0+

Before starting Pulse you must configure the messaging cluster:

1. Provision a RabbitMQ cluster and ensure that Pulse is able to establish a connection to that any node of the cluster.
2. Create a new vhost for Case Manager.

```
rabbitmqctl rabbitmqctl add_vhost casemanager
```

Copy

1. Create a new user for Case Manager.

```
rabbitmqctl add_user casemanager <password>
```

Copy

1. Update the vhost policies to grant all permissions to the Case Manager user.

```
# sets write and read permissions on every resource  
rabbitmqctl set_permissions casemanager -p casemanager ".*" ".*" ".*"
```

Copy

Pulse

Case Manager retrieves data from Pulse, and therefore requires an accessible Pulse cluster to start. Read more about how to install and configure Pulse in the [installation guide](#).