

On this page

Configuration Recommendations for Data Science Environment



For the full Pulse configuration refer to the official [Configuration Reference](#), the recommended [Production Setup](#) and [Data Science Setup](#).

Ansible



Available ansible variables for running the Data Science ansible playbook. These variables are an addition to the variables described in [Pulse Configuration Recommendations](#).

Variable	Default Value	Description
jupyterlab_docker_image	docker.feedzai.com/feedzai/jupyterlab: {{ jupyterlab_version }}	Feedzai JupyterLab Docker Image
hdfs_feedzai_user	pulse	User that will be the owner of the folders created on Hadoop master nodes
hadoop_master_node	"hadoop_master"	Hadoop master node hostname
hadoop_conf_path	"/etc/hadoop/conf"	Hadoop configuration folder in the master nodes
spark_libs_install_path	"{{ pulse_install_path }}/product-pulse-{{ pulse_version }}"	Source path to Spark libs on the Pulse node
pulse_jupyterlab_setup_docker	true	Flag to enable setup of JupyterLab
model_training_directory	"hdfs:///user/pulse/models"	The directory location where trained models should be saved. This directory can be a local or distributed (HDFS) filesystem.
model_storage_directory	"hdfs:///user/pulse/models"	The directory location where imported models through App Collaboration should be saved. This directory can be a local or distributed (HDFS) filesystem
model_hpt_directory	"hdfs:///user/pulse/hpt-models"	The directory location where the hyperparameter tuning models should be saved between model training and evaluation. This directory can be a local or distributed (HDFS) filesystem.
pulse_jupyterlab_container_max_memory	8589934592 (8GB)	The maximum memory (in KB) allowed for JupyterLab containers. Other units can be used instead, e.g. <code>512m</code> would set maximum memory to 512 MB.
pulse_loggers	{}	Controls extra loggers to be enabled in Pulse. Keys in this dictionary are the loggers and the values the log level for that logger.