

On this page

Network and Connectivity



This page is based on the architecture of Feedzai standard solutions. Specific clients or custom solutions may have additional requirements, so this is not a definitive guide.

Firewall Rules



For a complete list of the the Firewall Configurations required for Pulse, please refer to the product documentation.

Inbound



Inbound other services connect to this service.

Service	Port	Description
HTTP	TCP 8080	Pulse Server UI (HTTP)
HTTP	TCP 8443	Pulse Server UI (HTTPS)
HTTP	TCP 8081-8091	API HTTP Server (Feedzai Connectors)
YARN (Spark, HDFS)	TCP *	Job management
Pulse	TCP *	Communication between Pulse nodes (RMI)
SSH	TCP 22	SSH access (if available)

Outbound



Outbound this service connects to external services.

Service	Port	Description
RDBMS (PostgreSQL)	TCP 5432	Access to database
RabbitMQ	TCP 5671-5672	RabbitMQ AMQP (5671 for TLS)
YARN (Spark, HDFS)	TCP *	Job submission and management
Pulse	TCP *	Communication between Pulse nodes (RMI)
Reference Data Service	TCP 8080-8081	Communication with Reference Data Service
Profile Store (Cassandra)	9042	Fetch data from Profile Store
ZooKeeper	2181	Fetch data from Profile Store
Feedzai Enrichment Server (Public Network)	443	Connection to Feedzai Enrichment Service for specific Feedzai IP

Load Balancers

For high available environments Load Balancers must be set as follow:

Service	Description	Algorithm	Healthcheck URL	Response Codes	Policy Example
Pulse	Entry point used by end users to access the web UI and by Case Manager Processor to interact remotely with Pulse.	Follow the leader	HTTPS:8443/api/client/cluster/pulse/leader/global HTTP:8080/api/client/cluster/pulse/leader/global	200 - Node is global leader. 503 - Node is not global leader	Checks should be performed every 30 seconds with a timeout of 5 seconds. Nodes should be removed after the second failure.
Pulse Application API	Entry point used to send events for Pulse to score them.	Round robin	HTTP:8081/api/health	200 - Pulse received event and AppEngine workflow processed it successfully 500 - Some error occurred processing the event in the AppEngine workflow 503 - Input adapter is not available to receive the event	Checks should be performed every 6 seconds with a timeout of 5 seconds. Nodes should be removed after the second failure.