

On this page

Configuration Recommendations

Ansible



Available ansible variables for running the ansible playbook.

Variable	Default Value	Description
reference_data_install_path	"/opt/feedzai"	Reference Data Service (RDS) install path
reference_data_home_path	"{{ reference_data_install_path }}/reference-data-{{ reference_data_version }}"	RDS home path
reference_data_app_port	8080	RDS connection port
reference_data_admin_port	8081	RDS administration connection port
cassandra_rds_username	"rds"	RDS username in Cassandra
cassandra_rds_password	"secret"	RDS user password in Cassandra
cassandra_cluster_name	"project-hsbc cluster"	Profile store cluster name in Cassandra
cassandra_rds_consistency	"LOCAL_ONE"	Profile store consistency level in Cassandra
cassandra_rds_keyspace_replication	"{'class':'NetworkTopologyStrategy', 'dc1': {{ groups['cassandra'] }}"	length }}"
reference_data_cassandra.tableName	feedzai_reference_data	Cassandra profile store table name
reference_data_cassandra.keyspaceName	hsbc	Cassandra profile store keyspace name
reference_data_cassandra.username	{{ cassandra_rds_username }}	Cassandra RDS username
reference_data_cassandra.password	{{ cassandra_rds_password_encrypted }}	Cassandra RDS user password
reference_data_cassandra.cluster	{{ cassandra_cluster_name }}	Cassandra cluster name
reference_data_cassandra.contactPoints	{{ groups['cassandra'] }}	Cassandra contact points
reference_data_cassandra.consistencyLevel	{{ cassandra_rds_consistency }}	Cassandra consistency level
reference_data_cassandra.replicationStrategy	{{ cassandra_rds_keyspace_replication }}	Cassandra replication strategy
reference_data_jwt_secret	"0jd40327td208347t02k3487t23k40t87320t"	JWT secret, needs to be set
reference_data_use_https	false	When <code>true</code> RDS will use https for connection

Variable	Default Value	Description
reference_data_app_keystore_path	"{{ reference_data_home_path }}/conf/keystore.jks"	Keystore path, needs to be set when reference_data_use_https is <code>true</code>
reference_data_app_keystore_password	N/A	Keystore password, needs to be set when reference_data_use_https is <code>true</code>
reference_data_app_keystore_type	"JKS"	Key store type, needs to be set when reference_data_use_https is <code>true</code>
reference_data_app_keymanager_password	N/A	Key manager password, needs to be set when reference_data_use_https is <code>true</code>
reference_data_admin_keystore_path	"{{ reference_data_home_path }}/conf/keystore.jks"	Keystore path, needs to be set when reference_data_use_https is <code>true</code>
reference_data_admin_keystore_password	N/A	Keystore password, needs to be set when reference_data_use_https is <code>true</code>
reference_data_admin_keystore_type	"JKS"	Key store type, needs to be set when reference_data_use_https is <code>true</code>
reference_data_admin_keymanager_password	N/A	Key manager password, needs to be set when reference_data_use_https is <code>true</code>
reference_data_validate_certs	true	Set to validate certificates, needs to be set when reference_data_use_https is <code>true</code>
reference_data_validate_peers	true	Set to validate peers, needs to be set when reference_data_use_https is <code>true</code>
reference_data_allow_renegotiation	true	Set to allow renegotiation, needs to be set when reference_data_use_https is <code>true</code>
supportedProtocols	[TLSv1.2]	Set supported protocols, needs to be set when reference_data_use_https is <code>true</code>
supportedCipherSuites	[TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256]	Set supported ciphers, needs to be set when reference_data_use_https is <code>true</code>
reference_data_secret_value	"830ebea1212f74040dbab3506cad4ec3"	Value used to encrypt sensitive properties

Variable	Default Value	Description
reference_data_properties_to_encrypt	[cassandra_rds_password]	List of properties to encrypt. Encrypted properties can be used by adding the suffix <code>_encrypted</code> to the original property name, i.e. <code><PROPERTY_NAME>_encrypted</code> . Doesn't support dictionary variables
reference_data_log_level	INFO	Default log level for all components in RDS. Please note that changing this value may impact the amount of produced logs.
reference_data_loggers	{}	Controls extra loggers in RDS, allowing to override the default value per logger. Keys in this dictionary are the loggers and the values the log level for that logger.

RDS Service configuration

In addition to the above Ansible variables, some properties can be directly changed on the Reference Data Service's configuration file, `configuration.yml`.

Please find below a description of each of the available configurations.

Property	Default Value	Description
server.applicationConnectors.supportedProtocols	[TLSv1.2]	Set supported protocols, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
server.applicationConnectors.supportedCipherSuites	[TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256]	Set supported ciphers, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
server.adminConnectors.supportedProtocols	[TLSv1.2]	Set supported protocols, needs to be set when <code>reference_data_use_https</code> is <code>true</code>
server.adminConnectors.supportedCipherSuites	[TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256]	Set supported ciphers, needs to be set when <code>reference_data_use_https</code> is <code>true</code>



There are no configuration recommendations for this service besides the ones already described in the guide.