

On this page

Case Manager Database Table Structure

Find in this page a detailed guide on the important tables used for Case Manager.

AM_EVENT_STORAGE

- This table contains the referential records to all historical transactions, where the event request is stored in EVENT_DATA in raw json format. This includes all events for a given lifecycle_id, not just a single record per lifecycle_id.

Column Name	Column Type	Description
EVENT_ID	PRIMARY KEY	The event's unique identifier. Randomly generated UUID, generated for each event.
EVENT_VERSION_ID	PRIMARY KEY	It is usually equal to EVENT_ID. New Id gets generated in case the event is an update to the initial transaction.
EVENT_DATA	JSON	The field stores event data

AM_EVENT_DIGITAL_ACTIVITY

- The records in this table correspond to the Digital Activity events (e.g. Credentials Update, Device Update, New Payee, Alias, Profile Update, etc).
- The AM_EVENT_DIGITAL_ACTIVITY table only holds one record for all events with the same lifecycle_id. Subsequent events for the same lifecycle_id will update the record as opposed to creating a new record.
- Use this extract to find all the unique Digital Activity transactions uploaded using Digital Activity API

Column Name	Column Type	Description
EVENT_ID	PRIMARY KEY	Internal field. The event's unique identifier. Randomly generated UUID, equal to the corresponding FDZ_UUID in the Pulse's event storage.
EVENT_ALERT	BOOLEAN	Boolean for whether it is an alert or not.
EVENT_TENANT	STRING	Internal field which stores the tenant key.
QUEUE_ID	STRING	The ID of the current queue.
USER_ID	STRING	The ID of the current assignee.
ACCESS_GROUP_ID	STRING	The ID of the access group.
channelId	STRING	Channel identifier.
event_type	STRING	An internal field that indicates the endpoint from which the event entered.
fraud_score	STRING	Calculated fraud score.
outcome_decision	STRING	Event decision outcome.
amount	INTEGER	Transaction amount performed by the sender, in the currency specified by the currency field.
channel_type	STRING	Specifies the transaction payment channel.
currency_code	STRING	The local currency of the business.
customer_dob	STRING	Customer date of birth (YYYYMMDD).
customer_email	STRING	Customer's email.

Column Name	Column Type	Description
customer_id	STRING	Customer ID generated by the issuing bank.
customer_name	STRING	Customer's name.
customer_phone_number	STRING	Customer phone number.

AM_EVENT_TRANSFERS

- The records in this table correspond to the Transfer events (e.g. Initiation, Settlement, Info, Feedback, etc).
- The AM_EVENT_TRANSFERS database table only holds one record for all events with the same lifecycle_id. Subsequent events for the same lifecycle_id will update the record as opposed to creating a new record.
- Use this extract to find all the unique transfers uploaded using Transfers API

Column Name	Column Type	Description
EVENT_ID	PRIMARY KEY	Internal field. The event's unique identifier. Randomly generated UUID, equal to the corresponding FDZ_UUID in the Pulse's event storage.
EVENT_ALERT	BOOLEAN	Boolean for whether it is an alert or not.
EVENT_TENANT	STRING	Internal field which stores the tenant key.
QUEUE_ID	STRING	The ID of the current queue.
USER_ID	STRING	The ID of the current assignee.
ACCESS_GROUP_ID	STRING	The ID of the access group.
channelId	STRING	Channel identifier.
event_type	STRING	An internal field that indicates the endpoint from which the event entered.
fraud_score	STRING	Calculated fraud score.
outcome_decision	STRING	Event decision outcome.
merchant_city	STRING	Card acceptor city.
dispute_end_date	STRING	Timestamp corresponding to the moment when the dispute was closed.
dispute_feedback_notes	STRING	Contextual information associated with the dispute communication.
dispute_refunded	STRING	Whether the funds were refunded to the cardholder.
oob_feedback_notes	STRING	Contextual information associated with the out-of-band communication.
feedback_type	STRING	Identifies the different types of feedback.
dispute_notes	STRING	Contextual information left by the analyst at the time of the dispute opening.
dispute_reason	STRING	Why the dispute was opened.
dispute_start_date	STRING	Timestamp that corresponds to the time when the dispute was opened.
dispute_submitted_by	STRING	Who submitted the dispute.

AM_EVENT_STATUS

- Holds the history on status changes for events - previous state, new state, when the state change happened and who did it.

Column Name	Column Type	Description
EVENT_STATUS_ID	PRIMARY KEY	Internal field, randomly generated identifier for each status change.
OLD_STATUS_ID	STRING	The ID of the old status.
NEW_STATUS_ID	STRING	The ID of the new status.

Column Name	Column Type	Description
TIMESTAMP	INTEGER	Unix timestamp at which the event note was added.
USER_ID	STRING	ID of the user that added the note.

AM_EVENT_EXPLANATION

- This table contains the explanations of why the event triggered an alert, that is the Rules that triggered the alert. This contains the rules explanation for events in AM_EVENT table.

Column Name	Column Type	Description
EVENT_ID	STRING	The event's unique identifier. Randomly generated UUID, equal to the corresponding FDZ_UUID in the Pulse's event storage.
EVENT_TIMESTAMP	INTEGER	Corresponds to the FDZ_timestamp field in the Pulse's event storage for this particular EVENT_ID.
EVENT_VERSION_ID	STRING	It is equal to EVENT_ID.
EVENT_VERSION_TIMESTAMP	INTEGER	It is equal to EVENT_TIMESTAMP.
EVENT_EXPLANATION_GENERATOR_ID	STRING	Contains the internal rule ID. The primary key of this table is composed of the event ID and the rule ID.
EVENT_EXPLANATION_GEN_NAME	STRING	Contains the rule name.
EVENT_EXPLANATION_TYPE	STRING	The type of trigger that caused the alert.
EVENT_EXPLANATION_DESCRIPTION	STRING	The explanation provided by the risk engine for triggering the rule.

AM_EVENT_NOTE

- Notes added by analysts that may include personal information. The key is the EVENT_NOTE_ID column.

Column Name	Column Type	Description
EVENT_NOTE_ID	PRIMARY KEY	Randomly generated identifier for each note manually added by the analysts.
NOTE_MESSAGE	STRING	Note added by the analyst.
USER_ID	STRING	ID of the analyst that added the note.

AM_EVENT_STATUS_REASON

- This will provide the reason why the status of an event was changed as selected in the UI.
- The table is related to the AM_STATUS_REASON table via the column STATUS_REASON_ID as the foreign key. The possible values for STATUS_REASON_ID is a small set of mostly static values that correspond to a few options in a drop-down menu that a Case Manager user can choose from in the UI.

Column Name	Column Type	Description
EVENT_STATUS_ID	PRIMARY KEY	ID of the status associated with this reason change. Maps to the EVENT_STATUS_ID field in AM_EVENT_STATUS.
STATUS_REASON_ID	FOREIGN KEY	Foreign key to AM_STATUS_REASON table.
TIMESTAMP	PRIMARY KEY	Unix timestamp at which the event note was added.

AM_SLA

- The table stores the SLA definition or metadata that is created to automatically perform actions on events.

Column Name	Column Type	Description
SLA_ID	PRIMARY KEY	ID of the SLA.
SLA_NAME	PRIMARY KEY	Name of the SLA.
SLA_DESCRIPTION	STRING	Description of the SLA.
SLA_GOAL	STRING	Goal of the SLA.
SLA_CONDITIONS	STRING	Conditions of the SLA.
SLA_ACTIONS	STRING	SLA actions.

AM_EVENT_SLA

- The table links specific events to SLA's.

Column Name	Column Type	Description
EVENT_ID	PRIMARY KEY	Unique event id.
EVENT_SLA_ID	PRIMARY KEY	Event sla unique id.
SLA_ID	FOREIGN KEY	Foreign key to AM_SLA table.

AM_AUTOMATION

- The table stores the Automation rules created to automatically perform actions events and cases based on conditions.

Column Name	Column Type	Description
AUTOMATION_ID	PRIMARY KEY	ID of the service level agreement.
AUTOMATION_POSITION	UNIQUE KEY	Numeric position.
AUTOMATION_NAME	STRING	Name of Automation.
AUTOMATION_DESCRIPTION	STRING	Automation description.
AUTOMATION_CONDITIONS	STRING	Automation conditions.
AUTOMATION_ACTIONS	STRING	Automation actions.

AM_CASE_*



note

AM_CASE_* - They are not used by HSBC