

config_factory

logger module-attribute

```
logger = getLogger(__name__)
```

ConfigFactory

```
ConfigFactory(pyjnius_java)
```

Bases: [JavaWrapper](#)

A DataSource Configuration Factory representation.

configs_dict class-attribute instance-attribute

```
configs_dict = {CSV: partial(_set_csv_conf, config_ref=createCsvConf), PARQUET: partial(_set_parquet_conf, config_ref=createParquetConf), INFER: partial(_set_infer_schema_conf, config_ref=createInferSchemaConf)}
```

subclasses class-attribute instance-attribute

```
subclasses: List[JavaWrapper] = []
```

get_config staticmethod

```
get_config(config: ConfigType, **kwargs: Union[bool, str, int, Dict[str, str], Set[str]]) -> JavaWrapper
```

Getter for Pulse datasource configuration.

Parameters:

Name	Type	Description	Default
<code>config</code>	<code>str</code>	The desired Pulse configuration. Options are: <code>csv</code> , <code>parquet</code> , <code>infer</code> .	<i>required</i>
<code>kwargs</code>	<code>Dict</code>	Keyword arguments used for the configuration setup.	<code>{}</code>

Other Parameters:

Name	Type	Description
<code>has_header</code>	<code>bool</code>	Flags whether the dataset is to be read with header. Defaults to True.
<code>sep</code>	<code>str</code>	Delimiter to use. Should contain exactly one character. Defaults to ','.
<code>missing_values</code>	<code>set of str</code>	Set of strings with values for empty value. Defaults to { "", "NA", "NULL" }.
<code>quote</code>	<code>str</code>	The character used to denote the start and end of a quoted item. Defaults to ""

Name	Type	Description
<code>line_separator</code>	<code>str</code>	The string used mark the end of line. Defaults to '\n'.
<code>encoding</code>	<code>str</code>	Encoding to use for UTF when reading/writing. Defaults to 'UTF-8'.
<code>cat_threshold</code>	<code>int</code>	A value that represents the maximum number of distinct values on a given field for it to be inferred as categorical. Defaults to 15. Will only be used if no Schema is specified.
<code>job_properties</code>	<code>Dict</code>	The dictionary with the specific properties for the schema inference job. Will only be used if no Schema is specified.
<code>n_records</code>	<code>int</code>	The number of records that will be read per partition when performing datasource schema inference. Defaults to 15000. Will only be used if no Schema is specified.
<code>dtypes</code>	<code>Dict</code>	The dictionary with the field overriding information when inferring the datasource schema. Will only be used if no Schema is specified.
<code>merge_schemas</code>	<code>bool</code>	Specify if schema merging should be allowed. See: https://spark.apache.org/docs/latest/sql-data-sources-parquet.html#schema-merging

Returns:

Type	Description
JavaWrapper	Returns the requested datasource configuration depending on the config passed.

ConfigType

Bases: `str`, `Enum`

CSV `class-attribute` `instance-attribute` 

CSV = 'csv'

INFER `class-attribute` `instance-attribute` 

INFER = 'infer'

PARQUET `class-attribute` `instance-attribute` 

PARQUET = 'parquet'