

job_profile

Java ds-api counterpart in Java: `com.feedzai.commons.dsapi.JobProfile` .

logger

```
logger = getLogger(__name__)
```

JobProfile

```
JobProfile(pyjnius_java)
```

Bases: `JavaWrapper`

Represents a JobProfile in Pulse.

subclasses

```
subclasses: List[JavaWrapper] = []
```

create

```
create(app: App, desc: str, job_properties: Mapping[str, str]) -> JobProfile
```

Create a new JobProfile in `app` with the user facing name `desc` with and the specified spark `job_properties` , complementary to the default properties.

Parameters:

Name	Type	Description	Default
<code>app</code>	<code>App</code>	The App where the job profile will be created.	<i>required</i>
<code>desc</code>	<code>str</code>	The name of the job profile user faces in UI.	<i>required</i>
<code>job_properties</code>	<code>Dict</code>	Dictionary with Spark job configurations.	<i>required</i>

Returns:

Type	Description
<code>JobProfile</code>	JobProfile object corresponding to the Pulse job profile created.

get_job_config_dict

```
get_job_config_dict(job_properties: Optional[Mapping[str, str]] = None) -> Dict
```

Merges this job profile properties with job_properties.

Note

if there is intersection between the properties, the job_properties property will overwrite this job profile property.

Parameters:

Name	Type	Description	Default
<code>job_properties</code> A1	<code>dict</code>	Additional spark properties, eg. {"spark.executor.memory": "1g"}, by default dict()	<code>None</code>

Returns:

Type	Description
<code>dict</code>	Merged Pulse job config and spark properties. eg. {"spark.executor.memory": "1g"}