

lists

DS-API module to manage lists and list items in Pulse.

A List in Pulse is either Simple ([SimpleManagedListModel](#)) or Complex ([ComplexManagedListModel](#)). A Pulse List can contain items of the respective type: [SimpleManagedListItemModel](#) or [ComplexManagedListItemModel](#) .

Additionally, lists can have tags ([ManagedListTagModel](#)).

This module also provides a wrapper for [ManagedList](#) , to simplify list operations like `delete()` , and to provide an API that is more consistent with the rest of the DS-API.

ComplexManagedListItemModel module-attribute

```
ComplexManagedListItemModel = autoclass(MANAGED_LISTS_CLASSPATH + 'ComplexManagedListItemModel')
```

ComplexManagedListModel module-attribute

```
ComplexManagedListModel = autoclass(MODEL_CLASSPATH + 'ComplexManagedListModel')
```

FieldType module-attribute

```
FieldType = autoclass('com.feedzai.pulse.esp.FieldType')
```

Include module-attribute

```
Include = autoclass(PULSE_API_CLASSPATH + 'apps.enums.Include')
```

ManagedListTagModel module-attribute

```
ManagedListTagModel = autoclass(MANAGED_LISTS_CLASSPATH + 'ManagedListTagModel')
```

SimpleManagedListItemModel module-attribute

```
SimpleManagedListItemModel = autoclass(MANAGED_LISTS_CLASSPATH + 'SimpleManagedListItemModel')
```

SimpleManagedListModel module-attribute

```
SimpleManagedListModel = autoclass(MODEL_CLASSPATH + 'SimpleManagedListModel')
```

ManagedList

```
ManagedList(pyjnius_java)
```

Bases: [JavaWrapper](#)

Wrapper for Pulse's Lists. Can handle all list types.

Although one can use the Pulse API directly by accessing the methods of the managed list wrapped by this class with `getManagedList()` , this Python wrapper pulls all those methods to the main class.

Any method implemented by `ManagedList` takes precedence over exposed `self.getManagedList()._java_attributes()` members, to allow `ManagedList` to implement custom behaviour that overrides the wrapped class's members.

subclasses `class-attribute` `instance-attribute` [¶](#)

```
subclasses: List[JavaWrapper] = []
```

create_tag [¶](#)

```
create_tag(app: App, tag_name: str)
```

Creates a new tag (`ManagedListTagModel`) to use in a Pulse List.

Parameters:

Name	Type	Description	Default
<code>app</code> ¶	<code>App</code>	Pulse Application.	<i>required</i>
<code>tag_name</code> ¶	<code>str</code>	Name of the tag that will be used in the Pulse List.	<i>required</i>

Returns:

Type	Description
<code>ManagedListTagModel</code>	Pulse List Tag.

get_list_items_manager [¶](#)

```
get_list_items_manager(pulse: Server) -> JavaClass
```

Returns Pulse's list item manager.

Parameters:

Name	Type	Description	Default
<code>pulse</code> ¶	<code>Server</code>	The <code>ds_api.Server</code> used to communicate with Pulse.	<i>required</i>

Returns:

Type	Description
<code>AppManagedListItemManager</code>	List item manager to manage Pulse list items.

get_list_manager [¶](#)

```
get_list_manager(pulse: Server) -> JavaClass
```

Returns Pulse's list model manager.

Parameters:

Name	Type	Description	Default
<code>pulse</code> 	<code>Server</code>	The ds_api.Server used to communicate with Pulse.	<i>required</i>

Returns:

Type	Description
<code>ModelManager<ManagedListModel></code>	List manager to manage Pulse lists.