

model_eval_config

ModelEvalConfig

```
ModelEvalConfig(ignored_fields: set[str] | None = None, cost_field: str | None = None, scored_instances_filepath: str | None = None, sink_desc: str | None = None, breakdowns: list[dict[str, set[str]]] | None = None, target_variable: str | None = None, schema: Schema | None = None)
```

Bases: [JavaWrapper](#)

A configuration used for Model evaluation.

Parameters:

Name	Type	Description	Default
ignored_fields	set of str	Set of names corresponding to the fields to be ignored when evaluating a model.	None
cost_field	str	Additional cost field used as weight for evaluation metrics.	None
scored_instances_filepath	str	Path to file where scored instances should be saved.	None
sink_desc	str	The sink name for the model evaluation datasource. If not provided the new datasource will take the evaluation's name.	None
breakdowns	list of mappings of (str->{str...})	Each element of the list represents a breakdown analysis. Each element in the contained mapping represents a breakdown field, with -> .	None
target_variable	str	The name of the target variable to be used in the model evaluation. This is required for unsupervised models and optional for supervised models. When provided for supervised models, it overrides the model's target variable. The target variable must be a binary categorical field (exactly 2 values) from the evaluation datasource and should be included in ignored_fields.	None
schema	Schema	Pass a schema to enable conversion between descs and internal names. By not passing a schema, ds-api will assume field names are references to internal Pulse names, not the ones in the UI.	None

Examples:

```
>>> import ds_api
>>> model: ds_api.Model # Train model with a ds_api.ModelProject
>>> # Define ModelEvalConfig w/ breakdown per value of `caucasian`:
```

```

>>> test_datasource: ds_api.DataSource
>>> eval_config = ds_api.ModelEvalConfig(
...     breakdowns=[
...         {"Caucasian": {"true", "false"}},
...         # {"Age Group": {"-25", "26-46", "46-65", "66-"}},
...         # ...
...     ],
...     schema=test_datasource.getSchema(),
... )
>>> evaluation = model.evaluate("test_eval", test_datasource, eval_config)
>>> evaluation.waitForEvaluationFinished()
>>> (
...     (_, global_results),
...     ((non_caucasian_col_val,), non_caucasian_results),
...     ((caucasian_col_val,), caucasian_results),
... ) = evaluation.getResultForBreakdowns("true")
>>> assert non_caucasian_col_val == "false" and caucasian_col_val == "true"

```

breakdowns property [🔗](#)

breakdowns

cost_field property [🔗](#)

cost_field

ignored_fields property [🔗](#)

ignored_fields

scored_instances_filepath property [🔗](#)

scored_instances_filepath

sink_desc property [🔗](#)

sink_desc

subclasses class-attribute instance-attribute [🔗](#)

subclasses: List[[JavaWrapper](#)] = []

target_variable property [🔗](#)

target_variable

auto_cast staticmethod [🔗](#)

auto_cast(java_object) -> [ModelEvalConfig](#)

Helper method called when a return obj comes from java to be auto converted to python.

Warning

In this case the result will not have a schema attached.

builder classmethod [🔗](#)

builder()

duplicate [↗](#)

```
duplicate(ignored_fields: set[str] | None = None, cost_field: str | None = None, scored_instances_filepath: str | None = None, sink_desc: str | None = None, breakdowns: list[dict[str, set[str]]] | None = None, target_variable: str | None = None, schema: Schema | None = None) -> ModelEvalConfig
```

Duplicate current ModelEvalConfig, with the possibility of updating its properties.

Parameters:

Name	Type	Description	Default
ignored_fields ↗	set[str] None	Set of names corresponding to the fields to be ignored when evaluating a model.	None
cost_field ↗	str None	Additional cost field used as weight for evaluation metrics.	None
scored_instances_filepath ↗	str None	Path to file where scored instances should be saved.	None
sink_desc ↗	str None	The sink name for the model evaluation datasource. If not provided the new datasource will take the evaluation's name.	None
breakdowns ↗	list[dict[str, set[str]]] None	Each element of the list represents a breakdown analysis. Each element in the contained mapping represents a breakdown field, with -> .	None
target_variable ↗	str None	The name of the target variable to be used in the model evaluation. This is required for unsupervised models and optional for supervised models. When provided for supervised models, it overrides the model's target variable. The target variable must be a categorical field present in the evaluation datasource and should be included in ignored_fields.	None
schema ↗	Schema	Pass a schema to enable conversion between descs and internal names. By not passing a schema, ds-api will assume field names are references to internal Pulse names, not the ones in the UI.	None

Returns:

Type	Description
ModelEvalConfig	A model evaluation configuration.