

model_project

logger module-attribute

```
logger = getLogger(__name__)
```

ModelProject

```
ModelProject(pyjnius_java)
```

Bases: [JavaWrapper](#)

Represents a Model Project in Pulse.

subclasses class-attribute instance-attribute

```
subclasses: List[JavaWrapper] = []
```

create classmethod

```
create(app, name)
```

train

```
train(name: str, input_datasource: DataSource, target: str, model_config: TrainingConfig, job_profile: JobProfile | None = None, job_properties: dict[str, str] | None = None, wait: bool = False) -> Model
```

Creates and trains a given model with TrainingConfig using DataSource with target label field, with the option of using the default job profiles, a specific job profile, or custom spark_job_properties.

Note: if both job_properties and job_profile are specified and there is intersection between their properties, the job_properties property will prevail over the job_profile property.

Parameters:

Name	Type	Description	Default
<code>name</code> 	<code>str</code>	Model name visible to the user.	<i>required</i>
<code>input_datasource</code> 	DataSource	Datasource used in the model training.	<i>required</i>
<code>target</code> 	<code>str</code>	Name of the label field.	<i>required</i>
<code>model_config</code> 	TrainingConfig	Training configuration used in the model training.	<i>required</i>
<code>job_profile</code> 	JobProfile	Pulse UI custom job profile.	<code>None</code>

Name	Type	Description	Default
<code>job_properties</code> ¶	Mapping	Map containing spark job configurations. It will apply default configurations (Pulse Properties Profile) and job_properties.	None
<code>wait</code> ¶	bool	Whether to wait for the model training to finish. The training outcome will be logged. By default, False.	False

Returns:

Type	Description
<code>Model</code>	The trained model.