

models

Module that includes all available model training configurations.

MODELS_CLASSPATH module-attribute

MODELS_CLASSPATH: str = [DS_API_CLASSPATH](#) + 'models.'

TrainingConfig

TrainingConfig(builder, undersampling: float | None = None, oversampling: float | None = None, seed: int | None = None, ignored_fields: set[str] | None = None, schema: [Schema](#) | None = None)

Bases: [JavaWrapper](#)

The base class for a model training configuration. It takes care of the initialization of common parameters across all algorithms.

Parameters:

Name	Type	Description	Default
builder 		Builder that comes from the specific algorithm.	<i>required</i>
undersampling 	float	The value for undersampling. Only this or oversampling can be used.	None
oversampling 	float	The value for oversampling. Only this or undersampling can be used.	None
seed 	int	The seed value.	None
ignored_fields 	set of str	Set of names corresponding to the fields to be ignored when training a model.	None
schema 	Schema	Pass a schema to enable conversion between descs and internal names. By not passing a schema, ds-api will assume field names are references to internal Pulse names, not the ones in the UI.	None

ignored_fields property writable

ignored_fields

oversampling property writable

oversampling

seed property writable [¶](#)

seed

subclasses class-attribute instance-attribute [¶](#)

subclasses: List[[JavaWrapper](#)] = []

undersampling property writable [¶](#)

undersampling