

diff

Module to enable Plans diff creation.

DIFF_NAME_PLACEHOLDER module-attribute

```
DIFF_NAME_PLACEHOLDER = '{plan_a}_diff_{plan_b}_{datetime:%Y%m%d%H%M%S}'
```

LOGGER module-attribute

```
LOGGER = getLogger(__name__)
```

PlanDiff

```
PlanDiff(plan_a: Plan, plan_b: Plan)
```

Encapsulates the logic to find the difference between two plans.

Note

The generated diff plan allows the difference between two plans to be executed. This means it not only has the diff but also all the relevant ancestors required to make the plan valid, as well as any downstream features that would be impacted by upstream changes.

Let's say feature X changed. We need to include:

- Feature X's ancestors to allow the computation of X.
- Feature X's descendants because they need to be updated.
- Feature X's descendants ancestors to make the plan valid.

Parameters:

Name	Type	Description	Default
<code>plan_a</code> 	<code>Plan</code>	Base plan for the difference.	<i>required</i>
<code>plan_b</code> 	<code>Plan</code>	Secondary/"new" plan.	<i>required</i>

features_to_keep instance-attribute

```
features_to_keep: FeatureContainer = _diff()
```

new_feature_dependencies instance-attribute

```
new_feature_dependencies: FeatureContainer
```

new_features instance-attribute

```
new_features: FeatureContainer
```

to_pulse

```
to_pulse(name: Optional[str] = None) -> Plan
```

Create the diff plan and persist it in Pulse.

If no name is given, it will create a plan named after the two plans used to create the diff: `{plan_a}_diff_{plan_b}_{timestamp}`.

Parameters:

Name	Type	Description	Default
<code>name</code> 	<code>str</code>	Name of the diff plan.	<code>None</code>

Returns:

Type	Description
<code>Plan</code>	The diff plan.

validate_plan_compatibility

```
validate_plan_compatibility(a: Plan, b: Plan)
```

Validate if two plans are compatible.

Two conditions must be met for two plans to be compatible:

1. Same schema
2. Same timestamp field.

Parameters:

Name	Type	Description	Default
<code>a</code> 	<code>Plan</code>	One plan.	<i>required</i>
<code>b</code> 	<code>Plan</code>	Another plan.	<i>required</i>

Raises:

Type	Description
<code>ValueError</code>	When plans are incompatible.