

# list\_feature

## LIST\_DEP\_TYPE\_NAME module-attribute

LIST\_DEP\_TYPE\_NAME = 'list'

## LOGGER module-attribute

LOGGER = getLogger(\_\_name\_\_)

## ListFeature

ListFeature(name: str, list\_id: str, expression: str, \*, timestamp\_field: str | None = None, description: str | None = None)

Bases: BaseFeature, ABC

Base class for ListGetFeature and ListContainsFeature.

Parameters:

| Name        | Type | Description                                                                                                                                                          | Default  |
|-------------|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| name        | str  | Name of the feature.                                                                                                                                                 | required |
| list_id     | str  | id of the List in Pulse.                                                                                                                                             | required |
| expression  | str  | Feature expression. Fields must be enclosed with the pattern <code>\${field}</code> eg. <code>"com.feedzai.cloud.udf.Strings.normalize( \${MerchantName} )" .</code> | required |
| description | str  | Feature description, by default None.                                                                                                                                | None     |

## description property writable

description

## expression property writable

expression: str

## list\_id property writable

list\_id: str

## name property writable

name

**operator** **property** [¶](#)

operator

**timestamp\_field** **property** **writable** [¶](#)

timestamp\_field: str | None

**from\_dict** **abstractmethod** **classmethod** [¶](#)

from\_dict(feat\_dict: Dict[str, str]) -> [BaseFeature](#)

Creates a Feature from a dict type to facilitate importing features from a tabular format.

Parameters:

| Name                               | Type | Description                                            | Default         |
|------------------------------------|------|--------------------------------------------------------|-----------------|
| <b>feat_dict</b> <a href="#">¶</a> | dict | Dictionary containing the feature in a tabular format. | <i>required</i> |

Returns:

| Type                        | Description                                          |
|-----------------------------|------------------------------------------------------|
| <a href="#">BaseFeature</a> | Feature initiated with the attributes from the dict. |

**from\_java\_feature** **abstractmethod** **classmethod** [¶](#)

from\_java\_feature(feature: JavaClass, operator: [BaseFeaturesOperator](#)) -> [BaseFeature](#)

Converts a Java DS-API Feature to a Python feature class.

**get\_dependencies** [¶](#)

get\_dependencies() -> set[str]

**get\_dependencies\_by\_type** [¶](#)

get\_dependencies\_by\_type() -> dict[str, list[str]]

**rename\_dependencies** [¶](#)

rename\_dependencies(old\_name: str, new\_name: str)

**to\_dict** [¶](#)

to\_dict(with\_operator: bool = True) -> dict[str, str | float | int | bool | None]

**to\_java\_feature\_builder** **abstractmethod** [¶](#)

to\_java\_feature\_builder() -> JavaClass

Converts a Python feature class to a Java DS-API Feature Builder.