

list_get_feature

LOGGER module-attribute

```
LOGGER = getLogger(__name__)
```

ListGetFeatureBuilder module-attribute

```
ListGetFeatureBuilder = autoclass(DS_API_CLASSPATH + 'plan.features.ListGetFeature$Builder')
```

ListGetFeature

```
ListGetFeature(name: str, list_id: str, expression: str, list_field: str, *, timestamp_field: str | None = None, description: str | None = None)
```

Bases: [ListFeature](#)

Represents a ListGet feature in Pulse.

Parameters:

Name	Type	Description	Default
<code>name</code>	<code>str</code>	Name of the feature.	<i>required</i>
<code>list_id</code>	<code>str</code>	id of the List in Pulse.	<i>required</i>
<code>expression</code>	<code>str</code>	Feature expression. Fields must be enclosed with the pattern <code>\${field}</code> and the field type of the returned expression must match the type of the List key. eg. <code>"com.feedzai.cloud.udf.Strings.normalize(\${MerchantName})" .</code>	<i>required</i>
<code>list_field</code>	<code>str</code>	Field to be accessed from the complex list.	<i>required</i>
<code>description</code>	<code>str</code>	Feature description, by default None.	None

description property writable

```
description
```

expression property writable

```
expression: str
```

list_field property writable [¶](#)

```
list_field
```

list_id property writable [¶](#)

```
list_id: str
```

name property writable [¶](#)

```
name
```

operator property [¶](#)

```
operator
```

timestamp_field property writable [¶](#)

```
timestamp_field: str | None
```

from_dict classmethod [¶](#)

```
from_dict(feats_dict: Dict[str, str]) -> ListGetFeature
```

from_java_feature classmethod [¶](#)

```
from_java_feature(feature: JavaClass, operator: BaseFeaturesOperator) -> ListGetFeature
```

Creates a ListGetFeature from a Java DS-API ListGetFeature.

Parameters:

Name	Type	Description	Default
feature ¶	Java DS-API ListGetFeature		<i>required</i>
operator ¶	ListOperator		<i>required</i>

Returns:

Type	Description
ListGetFeature	ListGetFeature

get_dependencies [¶](#)

```
get_dependencies() -> set[str]
```

get_dependencies_by_type [¶](#)

```
get_dependencies_by_type() -> dict[str, list[str]]
```

rename_dependencies [¶](#)

```
rename_dependencies(old_name: str, new_name: str)
```

to_dict [¶](#)

```
to_dict(with_operator: bool = True) -> dict[str, str | float | int | bool | None]
```

to_java_feature_builder [¶](#)

```
to_java_feature_builder() -> JavaClass
```

From ListGetFeature to a Java DS-API ListGetFeature.Builder.

Returns:

Type	Description
<code>Builder</code>	ListGetFeature.Builder