

# omnichannel

Module with specific Omnichannel tooling.

New feature

Omnichannel plan manipulation is a new feature of the ds-api.

## LOGGER module-attribute

```
LOGGER = getLogger(__name__)
```

## PlanChannelConfig module-attribute

```
PlanChannelConfig = autoclass(MODEL_CLASSPATH + 'datascience.plan.PlanChannelConfig')
```

## SchemaModel module-attribute

```
SchemaModel = autoclass(MODEL_CLASSPATH + 'SchemaModel')
```

## Channel dataclass

```
Channel(name: str, schema_model: JavaWrapper, timestamp_field: str, id: str | None = None)
```

Immutable representation of a Channel configuration for Omnichannel Plans.

Note that this can be instantiated with a `SchemaModel` directly or with a `ds_api.schema.Schema`.

Examples:

```
>>> from ds_api.plans.omnichannel import Channel
>>> app = ...
>>> schema = app.pullSchemaByDesc("Cards Schema")
>>> channel = Channel("cards", schema, "event_occurred_at")
```

Attributes:

| Name                         | Type                         | Description                                                                                                          |
|------------------------------|------------------------------|----------------------------------------------------------------------------------------------------------------------|
| <code>name</code>            | <code>str</code>             | Name of the channel.                                                                                                 |
| <code>schema_model</code>    | <code>SchemaModel</code>     | Simple schema representation.                                                                                        |
| <code>timestamp_field</code> | <code>str</code>             | The name of the timestamp field as it appears in the UI.                                                             |
| <code>id</code>              | <code>(str, optional)</code> | Unique identifier for the channel. If none is passed, the ID is automatically generated when interacting with Pulse. |

## id class-attribute instance-attribute

```
id: str | None = None
```

**name** instance-attribute [¶](#)

```
name: str
```

**schema\_model** instance-attribute [¶](#)

```
schema_model: JavaWrapper
```

**timestamp\_field** instance-attribute [¶](#)

```
timestamp_field: str
```

**from\_config** classmethod [¶](#)

```
from_config(config: JavaWrapper) -> Channel
```

Create a Channel from a Pulse `PlanChannelConfig` .

**to\_config** [¶](#)

```
to_config() -> JavaWrapper
```

Return this Channel as a Pulse `PlanChannelConfig` .