

map_operator

LOGGER module-attribute

```
LOGGER = getLogger(__name__)
```

ProjectionFeature module-attribute

```
ProjectionFeature = autoclass(DS_API_CLASSPATH + 'plan.features.ProjectionFeature')
```

MapOperator

```
MapOperator(pyjnius_java)
```

Bases: [BaseFeaturesOperator](#)

Represents a Map Operator in Pulse.

subclasses class-attribute instance-attribute

```
subclasses: List[JavaWrapper] = []
```

add_feature

```
add_feature(feature: BaseFeature, logger: bool = True) -> BaseFeature
```

Adds a new Feature to this Operator.

Parameters:

Name	Type	Description	Default
<code>feature</code> 	BaseFeature	New Feature.	<i>required</i>
<code>logger</code> 	<code>bool</code>	Whether to log info message or not.	<code>True</code>

Returns:

Type	Description
BaseFeature	New Feature.

add_fields_to_remove

```
add_fields_to_remove(fields=Set[str])
```

Sets the fields to be removed in the Operator.

Parameters:

Name	Type	Description	Default
<code>fields</code> ¶	<code>set of str</code>	Names of the fields, by default <code>Set[str]</code> .	<code>Set[str]</code>

`diff` [¶](#)

```
diff(other: BaseFeaturesOperator, only_diff: bool = True)
```

Display the differences between the features from this Operator and another Operator.

Features are compared based on their feature name. The order of the features in the Operator is not taken into account.

Parameters:

Name	Type	Description	Default
<code>other</code> ¶	BaseFeaturesOperator	BaseFeaturesOperator to compare against.	<i>required</i>
<code>only_diff</code> ¶	<code>bool</code>	Show features with differences only. Defaults to 'true'.	<code>True</code>

Raises:

Type	Description
<code>NotImplementedError</code>	When not called from a Jupyter notebook.

`get_dependencies` [¶](#)

```
get_dependencies() -> Dict[FeatureUID, Set[str]]
```

`get_dependencies_by_type` [¶](#)

```
get_dependencies_by_type() -> Dict[FeatureUID, Dict[str, List[str]]]
```

`get_feature` [¶](#)

```
get_feature(name: str) -> MapFeature
```

Gets a Feature by a given name.

Parameters:

Name	Type	Description	Default
<code>name</code> ¶	<code>str</code>	Name of the feature.	<i>required</i>

Returns:

Type	Description
MapFeature	MapFeature

`get_features` [¶](#)

```
get_features() -> List[MapFeature]
```

Gets all the features in this Operator instance.

Returns:

Type	Description
list of MapFeature	List of MapFeature

`get_fields_to_remove` [¶](#)

```
get_fields_to_remove() -> Set[str]
```

Gets the fields to be removed on this Operator.

Returns:

Type	Description
set of optional str	Names of the fields to be removed.

`get_type` `staticmethod` [¶](#)

```
get_type() -> str
```

`remove_feature` [¶](#)

```
remove_feature(name: str) -> bool
```

Removes the features that match the name.

Parameters:

Name	Type	Description	Default
<code>name</code> ¶	str	Name of the feature to remove.	<i>required</i>

Returns:

Type	Description
bool	If the feature is removed.

`rename_feature` [¶](#)

```
rename_feature(old_name: str, new_name: str)
```

`to_csv` [¶](#)

```
to_csv(path: Union[Path, str])
```

Exports all the features in the operator as a csv file.

Parameters:

Name	Type	Description	Default
<code>path</code> ¶	Path or str	Path to where the csv will be written.	<i>required</i>

to_dict [↗](#)

```
to_dict() -> List[Dict]
```

to_pandas [↗](#)

```
to_pandas() -> DataFrame
```

Exports all the features in the operator as a pandas dataframe.

Returns:

Type	Description
DataFrame	Pandas dataframe containing features and all their editable attributes.

update_from_csv [↗](#)

```
update_from_csv(path: Union[Path, str])
```

Updates this Operator with the configuration from the csv file.

Parameters:

Name	Type	Description	Default
path ↗	Path or str	Path from where the csv will be read.	<i>required</i>

See Also

Plan.from_csv : For guidelines to input csv data in the right format.

update_from_dict [↗](#)

```
update_from_dict(dict_feats: List[Dict])
```

update_from_pandas [↗](#)

```
update_from_pandas(pd_df: DataFrame)
```

Updates this Operator with the configuration from the pandas dataframe.

Parameters:

Name	Type	Description	Default
pd_df ↗	DataFrame	Pandas dataframe with the operator features.	<i>required</i>

See Also

Plan.from_csv : For guidelines to input csv data in the right format.