

metric_operator

LOGGER module-attribute

LOGGER = getLogger(__name__)

MetricOperator

MetricOperator(pyjnius_java, filter_incomplete_instances: bool = DEFAULT_FILTER_INCOMPLETE_INSTANCES)

Bases: BaseFeaturesOperator

Represents a Metric Operator in Pulse.

Parameters:

Name	Type	Description	Default
filter_incomplete_instances	bool	If True, the instances from the input datasource that do not have a complete window, based on the largest window from all the MetricFeatures, will be filtered out, by default False.	DEFAULT_FILTER_INCOMPLETE_INSTANCES

filter_incomplete_instances property writable

filter_incomplete_instances

Warning

Defining the value of this property triggers an update in all 'MetricFeatures' that are part of this operator.

subclasses class-attribute instance-attribute

subclasses: List[JavaWrapper] = []

timestamp_field property

timestamp_field: str

Warning

Only works with deployable plans.

add_feature

add_feature(feature: BaseFeature, logger: bool = True) -> BaseFeature

Adds a new Feature to this Operator.

Parameters:

Name	Type	Description	Default
feature	BaseFeature	New Feature.	required

Name	Type	Description	Default
<code>logger</code> ¶	<code>bool</code>	Whether to log info message or not.	<code>True</code>

Returns:

Type	Description
<code>BaseFeature</code>	New Feature.

`diff` [¶](#)

```
diff(other: BaseFeaturesOperator, only_diff: bool = True)
```

Display the differences between the features from this Operator and another Operator.

Features are compared based on their feature name. The order of the features in the Operator is not taken into account.

Parameters:

Name	Type	Description	Default
<code>other</code> ¶	<code>BaseFeaturesOperator</code>	BaseFeaturesOperator to compare against.	<i>required</i>
<code>only_diff</code> ¶	<code>bool</code>	Show features with differences only. Defaults to 'true'.	<code>True</code>

Raises:

Type	Description
<code>NotImplementedError</code>	When not called from a Jupyter notebook.

`get_dependencies` [¶](#)

```
get_dependencies() -> Dict[FeatureUID, Set[str]]
```

`get_dependencies_by_type` [¶](#)

```
get_dependencies_by_type() -> Dict[FeatureUID, Dict[str, list[str]]]
```

`get_feature` [¶](#)

```
get_feature(name: str) -> MetricFeature | None
```

Gets a Feature by a given name.

Parameters:

Name	Type	Description	Default
<code>name</code> ¶	<code>str</code>	Name of the feature.	<i>required</i>

Returns:

Type	Description
MetricFeature	MetricFeature

`get_features` [¶](#)

```
get_features() -> List[MetricFeature]
```

Gets all the features in this Operator instance.

Returns:

Type	Description
list of MetricFeature	List of MetricFeature.

`get_type` [¶](#) staticmethod

```
get_type() -> str
```

`remove_feature` [¶](#)

```
remove_feature(name: str) -> bool
```

Removes the features that match the name.

Parameters:

Name	Type	Description	Default
<code>name</code> ¶	str	Name of the feature to remove.	<i>required</i>

Returns:

Type	Description
bool	If the feature is removed.

`rename_feature` [¶](#)

```
rename_feature(old_name: str, new_name: str)
```

`to_csv` [¶](#)

```
to_csv(path: Union[Path, str])
```

Exports all the features in the operator as a csv file.

Parameters:

Name	Type	Description	Default
<code>path</code> ¶	Path or str	Path to where the csv will be written.	<i>required</i>

`to_dict` [¶](#)

```
to_dict() -> List[Dict]
```

to_pandas [¶](#)

```
to_pandas() -> DataFrame
```

Exports all the features in the operator as a pandas dataframe.

Returns:

Type	Description
DataFrame	Pandas dataframe containing features and all their editable attributes.

update_from_csv [¶](#)

```
update_from_csv(path: Union[Path, str])
```

Updates this Operator with the configuration from the csv file.

Parameters:

Name	Type	Description	Default
path ¶	Path or str	Path from where the csv will be read.	<i>required</i>

See Also

Plan.from_csv : For guidelines to input csv data in the right format.

update_from_dict [¶](#)

```
update_from_dict(dict_feats: list[dict])
```

update_from_pandas [¶](#)

```
update_from_pandas(pd_df: DataFrame)
```

Updates this Operator with the configuration from the pandas dataframe.

Parameters:

Name	Type	Description	Default
pd_df ¶	DataFrame	Pandas dataframe with the operator features.	<i>required</i>

See Also

Plan.from_csv : For guidelines to input csv data in the right format.