

rules_project_evaluation_config

LOGGER module-attribute

```
LOGGER = getLogger(__name__)
```

RulesProjectEvaluationConfig

```
RulesProjectEvaluationConfig(output_datasource_uri: str, output_datasource_name: str, filter_expression: str | None = None, cost_field: str | None = None, breakdowns: dict[str, set[str]] | None = None, timestamp_field: str | None = None, output_datasource_config: DataSourceConfig | None = None, file_format: str | None = None, **kwargs)
```

Bases: [JavaWrapper](#)

A configuration used for Rules Project Snapshot evaluation.

Create a new Rules Project Snapshot evaluation configuration.

Parameters:

Name	Type	Description	Default
output_datasource_uri	str	The URI of the datasource with the exported evaluation.	required
output_datasource_name	str	The name of the datasource with the exported evaluation.	required
filter_expression	str	The expression that filters events from being evaluated.	None
cost_field	str	The cost field used in the evaluation.	None
breakdowns	dict[str, set[str]]	The breakdown fields and values.	None
timestamp_field	str	The timestamp field used in the evaluation.	None
output_datasource_config	DataSourceConfig	The datasource config that includes the .csv writing options, such as delimiter, and encoding, of the datasource with the exported evaluation. Deprecated: Please use file_format instead.	None
	str		None

Name	Type	Description	Default
<code>file_format</code> 🔗		Output file format. When not defined, it will reuse the format of the input data source. Possible options are: "parquet" (preferred) or "csv".	

Other Parameters:

Name	Type	Description
<code>has_header</code>	<code>bool</code>	Flags whether the dataset is to be read with header. Defaults to True. <i>CSV config</i> .
<code>sep</code>	<code>str</code>	Delimiter to use. Must contain exactly one character. Defaults to ','. <i>CSV config</i> .
<code>missing_values</code>	<code>set of str</code>	Set of strings with values for empty value. Defaults to {"", "NA", "NULL"}. <i>CSV config</i> .
<code>quote</code>	<code>str</code>	The character used to denote the start and end of a quoted item. Defaults to '"'. <i>CSV config</i> .
<code>line_separator</code>	<code>str</code>	The string used mark the end of line. Defaults to '\n'. <i>CSV config</i> .
<code>encoding</code>	<code>str</code>	Encoding to use for UTF when reading/writing. Defaults to 'UTF-8'. <i>CSV config</i> .
<code>merge_schemas</code>	<code>bool</code>	Specify if schema merging should be allowed. See: https://spark.apache.org/docs/latest/sql-data-sources-parquet.html#schema-merging <i>Parquet config</i> .

`breakdowns` `property` [🔗](#)

```
breakdowns: dict[str, set[str]]
```

Get the breakdown fields and values.

`cost_field` `property` [🔗](#)

```
cost_field: str | None
```

Get the cost field used in the evaluation.

`exported_datasource` `property` [🔗](#)

```
exported_datasource: DataSource | None
```

Get datasource with the exported evaluation data.

`exported_datasource_name` `property` [🔗](#)

```
exported_datasource_name: str | None
```

Get the name of the datasource with the exported evaluation.

`exported_datasource_uri` `property` [🔗](#)

```
exported_datasource_uri: str | None
```

Get the URI of the datasource with the exported evaluation.

filter_expression property [🔗](#)

```
filter_expression: str | None
```

Get the expression that filters events from being evaluated.

subclasses class-attribute instance-attribute [🔗](#)

```
subclasses: List[JavaWrapper] = []
```

timestamp_field property [🔗](#)

```
timestamp_field: str | None
```

Get the timestamp field used in the evaluation.