

rules_project_snapshot

Java ds-api counterpart in :java: `com.feedzai.commons.dsapi.RulesProjectSnapshot` .

LOGGER module-attribute

```
LOGGER = getLogger(__name__)
```

RulesProjectSnapshot

```
RulesProjectSnapshot(pyjnius_java)
```

Bases: [JavaWrapper](#)

Represents a Rules Project Snapshot in Pulse.

actions property

```
actions: Dict[str, Any]
```

Get the actions that the snapshot can take.

app property

```
app: App
```

desc property

```
desc: str
```

Gets the user visible name of this rules project snapshot.

evaluation property

```
evaluation: Optional[RulesProjectEvaluation]
```

Gets the last evaluation ran for this snapshot, if any.

id property

```
id: str
```

Gets the id of this rules project snapshot.

original_rules_project property

```
original_rules_project: RulesProject
```

Gets the rules project from which this snapshot was generated.

rules property

```
rules: List[Rule]
```

Gets the snapshot's rules.

schema property [¶](#)

schema: [Schema](#)

Gets the schema associated with the snapshot.

subclasses class-attribute instance-attribute [¶](#)

subclasses: List[[JavaWrapper](#)] = []

target_field property [¶](#)

target_field: str

Gets the target field of RulesProject associated to this snapshot.

evaluate [¶](#)

```
evaluate(input_datasource: DataSource, evaluation_config: RulesProjectEvaluationConfig, profile_name: Optional[str] = None, spark_job_properties: Optional[Mapping] = None, wait: bool = True) -> RulesProjectEvaluation
```

Run a snapshot evaluation on an input data source.

Both spark job profile name and profile properties can be passed at the same time, but the profile name is prioritized.

Parameters:

Name	Type	Description	Default
input_datasource ¶	DataSource	Data to run through the rules project to calculate alerts.	<i>required</i>
evaluation_config ¶	RulesProjectEvalC onfig	Configuration for the snapshot evaluation.	<i>required</i>
profile_name ¶	str	Job profile name, by default None.	None
spark_job_properties ¶	Mapping	Job profile properties, by default None.	None
wait ¶	bool	Waits for the snapshot evaluation to finish before returning the evaluation object.	True

Returns:

Type	Description
RulesProjectEvaluation	The evaluation object containing its status and results.