

server

KEYTAB_SPARK_PROP module-attribute

```
KEYTAB_SPARK_PROP = 'spark.yarn.keytab'
```

LOGGER module-attribute

```
LOGGER = getLogger(__name__)
```

PulseGlobalConfiguration module-attribute

```
PulseGlobalConfiguration = autoclass('com.feedzai.pulse.server.api.config.PulseGlobalConfigurati  
on')
```

Server

```
Server(pyjnius_java)
```

Bases: [JavaWrapper](#)

Server class that connects to the Pulse API.

subclasses class-attribute instance-attribute

```
subclasses: List[JavaWrapper] = []
```

connect classmethod

```
connect(address: str = 'localhost', port: int = 1099, timeout: int = 10000, **kwargs)
```

Creates a new instance of com.feedzai.commons.dsapi.Server to connect to Pulse

Parameters:

Name	Type	Description	Default
<code>address</code> 	<code>str</code>	The hostname.	<code>'localhost'</code>
<code>port</code> 	<code>int</code>	The RMI port.	<code>1099</code>
<code>timeout</code> 	<code>int</code>	Maximum time to wait until timeout.	<code>10000</code>

Returns:

Type	Description
<code>Server</code>	The reference to the Pulse API.

get_datascience_config [↗](#)

```
get_datascience_config()
```

Return the DataScienceConfig object.

get_distributed_job_config [↗](#)

```
get_distributed_job_config()
```

Return the DistributedJobServiceConfig object.

get_kerberos_config [↗](#)

```
get_kerberos_config() -> dict
```

Return the DataScience Kerberos configuration as a dict.