

-



- [Out-of-the-Box Resources](#)
- Rules Projects
- Decision Rules

On this page

Decision Rules

Description🔍📄

Decision Rules are triggered based on the score value produced by a machine learning model. If your application workflow does not have a model, the `fraud_score` field remains empty, and thus the rules inside the Decision Rules project are not triggered.

Rules Project Metadata

- *Target Variable:* decision
- *Tenancy Type:* SINGLE_TENANT

Rules in this rules project:

Score-Denial-DR1

Comment

Decline a payment if it scored above a set threshold.

Actions

- [Score-Denial-DR1]

Variables

```
HIGH_SCORE_THRESHOLD = global_default__rules_thresholds["model_high_score"].threshold;

score = event.fraud_score * 1000;
```

Condition

```
(score ?? 0) >= HIGH_SCORE_THRESHOLD
```

Explanation

Model score ({localvar.score}) was equal or above the threshold
({localvar.HIGH_SCORE_THRESHOLD}).

Mark As

The outcome of this rule is: **decline**

Score-Review-DR2

Comment

Alert a payment if it scored between a set threshold.

Actions

- [Score-Review-DR2]
- Alert

Variables

```
LOW_SCORE_THRESHOLD = global_default__rules_thresholds["model_low_score"].threshold;
HIGH_SCORE_THRESHOLD = global_default__rules_thresholds["model_high_score"].threshold;

score = event.fraud_score * 1000;
```

Condition

```
(score ?? 0) > LOW_SCORE_THRESHOLD
and (score ?? 0) < HIGH_SCORE_THRESHOLD
```

Explanation

Model score ({localvar.score}) was between the low score threshold
({localvar.LOW_SCORE_THRESHOLD}) and the high score threshold
({localvar.HIGH_SCORE_THRESHOLD}).

Mark As

N/A