


•



- [About TFB](#)
- [Fraud Scenarios](#)
- Device and Behavior

On this page

## Device and Behavior

Was this page helpful? 

This page covers the account takeover scenario and its threats, and how to detect them by using device and behavioral data points.

### Account takeover

Account takeover (ATO) is the act of obtaining access to a person's bank account, typically by logging into their online account. Once they have control, fraudsters can easily transfer or wire money out of the victim's account into their own.

The most common threats leading to this fraud scenario are as follows:

**Phishing** is the act of sending fraudulent emails to extract account credentials from the victims. In these emails fraudsters pretend to be from a legitimate source by using an official company's logo and wording. Usually, the content of the email varies in nature (e.g. email compromise, urgent requests, bank account irregular activity, etc.). Fraudsters succeed at phishing when victims access a seemingly legitimate link, which in reality is a cloned version of the official company's link. In an ATO fraud scenario, the purpose of phishing is to obtain as much information about the victim as possible to take over their account.

Here's an example of a rule that captures user patterns associated with this threat:

- Risky activity with a "phishing" flag and device with high Session Risk Score.



info

**Session Risk Score** is a score generated by Digital Trust. It considers all the behavioral, device, and network indicators into a single score. The total risk score ranges from 0 (extremely low risk) to 100 (extremely high risk).

**Malware** is any software intentionally designed to cause damage or perform a fraudulent activity. Malware can get installed into the victim's device without them noticing. Once installed, criminals can access useful data such as passwords or PII to perform ATO.


Here's an example of a rule that captures user patterns associated with this threat:

- Decline transaction if the device is infected with malware.

**Suspicious network activity.** Some aspects of network activity provide Feedzai with important information regarding risky users. Typically, suspicious network activity is detected via a combination of anonymous web routing, TOR, Proxy, VPN, or Remote Access Tool (RAT) connections with the right intelligence.

Here's an example of a rule that captures user patterns associated with this threat:

- Login attempt from a dormant account with Session Risk Score and suspicious network activity above threshold.



tip

Feedzai recommends that data scientists combine data points such as phishing, malware, suspicious network, etc, with Session Risk Score to obtain solid detection results with low false positive rates. By combining data points with Session Risk Score, it is possible to confirm, for instance, that an online banking session with data points such as malware and/or VPN is suspicious.