# Distributive Law of Boolean Algebra

Meer Tabres Ali and G V V Sharma

# I. ABSTRACT

Distributive law of Boolean Algebra is expressed by "X.(Y+Z) = X.Y + X.Z". In this program, Two LEDs are used for checking the output. The outputs of both RHS and LHS parts must be same with random inputs.

# A. Truth Table for Distributive Law

Truth Table for Distributive Law is given in Table 1.

X	Y	Z	Y+Z	X(Y+Z)	XY	XZ	XY+XZ		
0	0	0	0	0	0	0	0		
0	0	1	0	0	0	0	0		
0	1	0	0	0	0	0	0		
0	1	1	0	0	0	0	0		
1	0	0	0	0	0	0	0		
1	0	1	1	1	0	1	1		
1	1	0	1	1	1	0	1		
1	1	1	1	1	1	1	1		
TABLE I									

TRUTH TABLE FOR DISTRIBUTIVE LAW

#### II. COMPONENTS

Required components list has been given in Table 2

Components	Value	Quantity				
Resistors	220 ohm	2				
LEDs		2				
Arduino	UNO	1				
Jumper Wires		20				
Breadboard		1				
TABLE II						

COMPONENTS

#### III. HARDWARE

Make the connections between Arduino and LEDs as per the Table 3.

	INPUT	INPUT	INPUT	OUTPUT	OUTPUT
	X	Y	Z	X(Y+Z)	XY+XZ
Arduino	2	3	4	5	6
LEDs				LED1	LED2
		Т	ABLE III		

# IV. SOFTWARE

1. Download the codes given in the link below and execute them.

https://github.com/meertabresali-FWC-IITH/project/blob/main/main.cpp

2. Apply the inputs X, Y, and Z (either HIGH or LOW) to the Digital Pin no.s 2, 3 and 4 of Arduino as per the Truth table (Table 1).

#### V. FINDINGS

After the execution of codes, for different input variables (X, Y and Z), the output pins (5 and 6) of Arduino will be at the same level (both output pins will be at either HIGH or LOW simultaneously), and it causes both LEDs either to glow or off.

# VI. CONCLUSION

- 1. Distributive law is expressed by "X(Y+Z)=XY+XZ", and here LHS = X(Y+Z), RHS = XY+XZ.
- 2. Codes are written for Distributive law and are executed.
- Result has been displayed on Two LEDs (i.e. LED1 and LED2).
- 4. LED1 is assigned for LHS of the Boolean expression of Distributive Law.
- 5. LED2 is assigned for RHS of the Boolean expression of Distributive Law.
- 6. For random digital inputs X, Y and Z as per Truth table (at Arduino digital pins 2, 3 and 4), it has been noticed that the output pins (5 and 6) of Arduino are at the same level.

Meer Tabres Ali was an intern with FWC IIT Hyderabad. \*The author is with the Department of Electrical Engineering, Indian Institute of Technology, Hyderabad 502285 India e-mail: gadepall@iith.ac.in. All content in this manual is released under GNU GPL. Free and open source.