

oops level-2

In old method

```
function people() {
  this.name = "meet";
  this.age = 19;
  this.say = function() {
    //code
  }
}
let p1 = new people();
let p2 = new people();
```

constructor

↳ find same value
like price

same in all
p1, p2, p3 --- etc.

to make this
property in constructor
is wrong way.

→ for that make in prototype
by default hold the proto's
value all p1, p2, p3, p4 --- etc.

This function
can not
share memory
take separately
in p1, p2.

like :-

```
function Toffee(name) {
  this.name = name;
}
Toffee.prototype.price = 120;
let t1 = new Toffee("Amm");
let t2 = new Toffee("Charlotte");
```

→ But one more think when we use of prototype than
first of all value find in object (function) if value
is there then include the value but value is not present
in object after that find in prototype and then include.

→ one more think in java script every array
object --- etc. have prototype.

→ Array also one type of object.

```
function CarModel(name, price, model) {
  this.name = "#" + name;
  this.price = price;
  this.model = "#1:" + model;
  this.PrintName = function() {
    console.log(this.name);
  }
  this.PrintModel = function() {
    console.log(model);
  }
}
let c1 = new CarModel('BMW', '7000 USD', 'M5 CS');
console.log(c1);
c1.PrintName();
c1.PrintModel();
```

Print name using this. it's print updated name value.

without using this. it's print parameter's name value.

```
function Employee(name, age, salary, id) {
  this.name = "#" + name;
  this.age = age;
  this.salary = "#" + salary;
  this.id = "#1" + id;
}
Employee.prototype.PrintDetails = function() {
  console.log('MY NAME IS ${this.name} AND I AM ${this.age} YEARS OLD AND MY SALARY IS ${this.salary} AND THIS IS MY ID ${this.id}.');
}
let e1 = new Employee('MEET', '19', '100000', 7);
console.log(e1);
e1.PrintDetails();
```

```
`${this.name}` = #1 MEET
`${this.age}` = 19
`${this.id}` = #1 7
`${this.salary}` = 100000
```