

FSD-2 Practice Book SEM-IV-2026 — Answers

Chapter 7 & Chapter 8 — Complete Solutions

Chapter 7 – React Basics (MCQ Answers, Q243–320)

243. **{}** missing at: `<Example fname={abc} age="30"/>`
244. **It will give an error regarding prop** — (Prop.Price is a typo of props.Price)
245. **npm create vite@latest myApp**
246. **Faster development server startup**
247. **Frontend build tool and development server**
248. **It will show an alert box once page will be loaded for first time, and it will perform nothing while clicking on button** (because handleClick() is invoked immediately, not passed as reference)
249. `<button onDoubleClick={doubleClickHandler}>Double Click here</button>`
250. **3000**
251. **Props**

```
<>
  <div></div>
  <h1>LJU</h1>
  <input type="text" className="demo"/>
</>
```

253. **Welcome To LJU**
254. **=>**
255. **error, since sum=sum+v statement must be specified using JSX** (side-effect statement not allowed directly inside JSX expression)

```
const a=1;
const b=1;
return(
  <p>{a+b}</p>)
```

257. **What is your name? My name is ABC!**
258. **SyntaxError** (because `<contact >` should be `<contact />`, and contact should be capitalized — `<Contact/>`)
259. **1**
260. **Using the Array.map() method**
261. **Inside the src folder**
262. **Error will be generated** (cannot concatenate strings as prop value without {})
263. **LJU / age** (heading “LJU” and “age” text with blue background — second option as written)
264. ****{ /* */ }****

265. **2 Images will be displayed vertically on browser.**

266. **Error as JSX fragment tag must required** (two sibling divs returned without a wrapping fragment)

267. **“car” is printed successfully by referring props.name.type**

268. **Returns array having only small letters**

269. **images, src={val.pic}**

```
map function
array values= A
array values= JAVA
array values= FULL STACK
array values= 567
array values= PYTHON
```

271. **<p style={css}>This is my data</p>**

272. **2,3**

```
function changeCssAttr(e)
{
  e.target.innerHTML="Thanks buddy";
  e.target.style.fontFamily="times new roman";
  e.target.align="center";
}
return (
<>
  <p onClick={changeCssAttr}>This is my para</p>
</>)

```

274. **Cause of error is Router/Route/Routes/Link is imported from react** (should be imported from react-router-dom)

275. **dataArr.filter(item => item.id === 1)**

276. **<p>{props.username}</p>**

277. **<Button></Button>**

278. **map**

279. **{ expression }**

280. **<div>Hello, World!</div>**

281. **<h1>{display()}</h1>**

282. **onSubmit**

283. **Output: banana,orange**

284. **<Route path="/about" element={<About />} />**

285. **Hello, John! and “You are 30 years old.” with an unordered list item “You are an adult”**

286. **CSE will be printed on browser in <h1> tag**

287. **Output: “The addition is: Hello28” with green background color in <h1> tag**

Chapter 7 – Programming Questions (296–320)

Q296: Basic “Hello World” React App

```
// App.js
import React from 'react';

function App() {
  return (
    <div>
      <h1>Hello World</h1>
    </div>
  );
}

export default App;
```

Q297: Pass and Read Data Using Props

```
// Child.js
import React from 'react';

const Child = (props) => {
  return (
    <div>
      <h2>Name: {props.name}</h2>
      <h2>Age: {props.age}</h2>
    </div>
  );
};

export default Child;
```

```
// App.js
import React from 'react';
import Child from './Child';

function App() {
  return (
    <div>
      <Child name="John" age="25" />
    </div>
  );
}

export default App;
```

Q298: Car’s Brand and Model Name via JSON Props

```
// Car.js
import React from 'react';
```

```

const Car = (props) => {
  return (
    <div>
      <h2>Brand: {props.carInfo.brand}</h2>
      <h2>Model: {props.carInfo.model}</h2>
    </div>
  );
};

export default Car;

// App.js
import React from 'react';
import Car from './Car';

function App() {
  const car = { brand: "Toyota", model: "Innova" };
  return (
    <div>
      <Car carInfo={car} />
    </div>
  );
}

export default App;

```

Q299: Alert Box on Button Click

```

// App.js
import React from 'react';

function App() {
  const handleClick = () => {
    alert("Welcome to LJU");
  };

  return (
    <div>
      <button onClick={handleClick}>Click Me</button>
    </div>
  );
}

export default App;

```

Q300: Display Values in Console While Changing Text Box

```

// App.js
import React, { useState } from 'react';

function App() {

```

```

const [text, setText] = useState("");

const handleChange = (e) => {
  setText(e.target.value);
  console.log(e.target.value);
};

return (
  <div>
    <input type="text" value={text} onChange={handleChange} />
  </div>
);
}

export default App;

```

Q301: Alert Box on Double Click

```

// App.js
import React from 'react';

function App() {
  const handleDoubleClick = () => {
    alert("welcome to lju");
  };

  return (
    <div>
      <button onDoubleClick={handleDoubleClick}>Click Me</button>
    </div>
  );
}

export default App;

```

Q302: Routing with Home, Shop, Contact, Nopage

```

// Home.js
import React from 'react';
const Home = () => <h2>Welcome to Home Page</h2>;
export default Home;

// Shop.js
import React from 'react';
const Shop = () => <h2>Welcome to Shop Page</h2>;
export default Shop;

// Contact.js
import React from 'react';
const Contact = () => <h2>Welcome to Contact Page</h2>;
export default Contact;

```

```

// Nopage.js
import React from 'react';
const Nopage = () => <h2>Page Not Found</h2>;
export default Nopage;

// Main.js
import React from 'react';
import { BrowserRouter, Routes, Route, Link } from 'react-router-dom';
import Home from './Home';
import Shop from './Shop';
import Contact from './Contact';
import Nopage from './Nopage';

const Main = () => {
  return (
    <BrowserRouter>
      <nav>
        <Link to="/">Home</Link> |{" "}
        <Link to="/shop">Shop</Link> |{" "}
        <Link to="/contact">Contact</Link>
      </nav>
      <Routes>
        <Route path="/" element={<Home />} />
        <Route path="/shop" element={<Shop />} />
        <Route path="/contact" element={<Contact />} />
        <Route path="*" element={<Nopage />} />
      </Routes>
    </BrowserRouter>
  );
};

export default Main;

// App.js
import React from 'react';
import Main from './Main';

function App() {
  return <Main />;
}

export default App;

```

Q303: Student Data Table Using Props

```

// StudentTable.js
import React from 'react';

const StudentTable = (props) => {

```

```

    return (
      <tr>
        <td>{props.name}</td>
        <td>{props.roll}</td>
        <td>{props.t1}</td>
        <td>{props.t2}</td>
      </tr>
    );
  };
};

export default StudentTable;

// App.js
import React from 'react';
import StudentTable from './StudentTable';

function App() {
  return (
    <table border="1">
      <thead>
        <tr>
          <th>Name</th><th>Roll No</th><th>T1</th><th>T2</th>
        </tr>
      </thead>
      <tbody>
        <StudentTable name="Amit" roll="1" t1="20" t2="22" />
        <StudentTable name="Riya" roll="2" t1="18" t2="25" />
      </tbody>
    </table>
  );
}

export default App;

```

Q304: Routing with Home (Image+Heading) and About (Branch List)

```

// Home.js
import React from 'react';
import logo from './logo.png';

const Home = () => {
  return (
    <div>
      <img src={logo} alt="logo" width="150" />
      <h1>LJ University</h1>
    </div>
  );
};

export default Home;

```

// About.js

```
import React from 'react';
```

```
const About = () => {  
  return (  
    <div>  
      <ul>  
        <li>CSE</li>  
        <li>IT</li>  
        <li>CE</li>  
      </ul>  
    </div>  
  );  
};
```

```
export default About;
```

// Main.js

```
import React from 'react';
```

```
import { BrowserRouter, Routes, Route, Link } from 'react-router-dom';
```

```
import Home from './Home';
```

```
import About from './About';
```

```
const Main = () => {  
  return (  
    <BrowserRouter>  
      <nav>  
        <Link to="/">Home</Link> | <Link to="/about">About</Link>  
      </nav>  
      <Routes>  
        <Route path="/" element={<Home />} />  
        <Route path="/about" element={<About />} />  
      </Routes>  
    </BrowserRouter>  
  );  
};
```

```
export default Main;
```

// App.js

```
import React from 'react';
```

```
import Main from './Main';
```

```
function App() {  
  return <Main />;  
}
```

```
export default App;
```

Q305: Filter Digits Less Than 10 — Pass Values as Props

```
// Numbers.js
import React from 'react';

const Numbers = (props) => {
  const result = props.arr.filter((num) => num >= 10);
  return (
    <div>
      {result.map((val, index) => (
        <span key={index}>{val} </span>
      ))}
    </div>
  );
};

export default Numbers;

// App.js
import React from 'react';
import Numbers from './Numbers';

function App() {
  const arr = [3, 5, 11, 4, 17, 8, 21, 2, 26, 13, 8];
  return (
    <div>
      <h2>Numbers >= 10:</h2>
      <Numbers arr={arr} />
    </div>
  );
}

export default App;
```

Q306: Apply CSS Props (color, bg, fontSize, fontStyle) to “Lj Students”

```
// Example.js
import React from 'react';

const Example = (props) => {
  const style = {
    color: props.color,
    backgroundColor: props.bgcolor,
    fontSize: props.fsize,
    fontStyle: props.fstyle
  };
  return (
    <div>
      <p style={style}>Lj Students</p>
    </div>
  );
};
```

```

};

export default Example;

// App.js
import React from 'react';
import Example from './Example';

function App() {
  return (
    <div>
      <Example color="red" bgcolor="yellow" fsize="25px" fstyle="italic" />
    </div>
  );
}

export default App;

```

Q307: Filter People Age < 40 and Display Names (LJU-2023)

```

// People.js
import React from 'react';

const People = (props) => {
  const result = props.data.filter((person) => person.age < 40);
  return (
    <div>
      {result.map((person, index) => (
        <p key={index}>{person.name}</p>
      ))}
    </div>
  );
};

export default People;

// App.js
import React from 'react';
import People from './People';

function App() {
  const data = [
    { name: "Amit", age: 35 },
    { name: "Suresh", age: 45 },
    { name: "Riya", age: 28 },
    { name: "Karan", age: 50 }
  ];
  return (
    <div>
      <h2>People under 40:</h2>

```

```

        <People data={data} />
      </div>
    );
  }

```

```
export default App;
```

Q308: Filter Students from CSE Branch

// Students.js

```
import React from 'react';
```

```

const Students = (props) => {
  const cseStudents = props.data.filter((student) => student.branch ===
"CSE");
  return (
    <div>
      {cseStudents.map((student, index) => (
        <p key={index}>{student.name}</p>
      ))}
    </div>
  );
};

```

```
export default Students;
```

// App.js

```
import React from 'react';
```

```
import Students from './Students';
```

```

function App() {
  const data = [
    { name: "Amit", branch: "CSE" },
    { name: "Riya", branch: "IT" },
    { name: "Karan", branch: "CSE" },
    { name: "Neha", branch: "CE" }
  ];
  return (
    <div>
      <h2>CSE Students:</h2>
      <Students data={data} />
    </div>
  );
}

```

```
export default App;
```

Q309: Routing for React JS, Node JS, Express JS

// Ex1.js

```
import React from 'react';
```

```

const Ex1 = () => <h1>React JS</h1>;
export default Ex1;

// Ex2.js
import React from 'react';
const Ex2 = () => <h1>Node JS</h1>;
export default Ex2;

// Ex3.js
import React from 'react';
const Ex3 = () => <h1>Express JS</h1>;
export default Ex3;

// Main.js
import React from 'react';
import { BrowserRouter, Routes, Route, Link } from 'react-router-dom';
import Ex1 from './Ex1';
import Ex2 from './Ex2';
import Ex3 from './Ex3';

const Main = () => {
  return (
    <BrowserRouter>
      <nav>
        <Link to="/react">React JS</Link> |{" "}
        <Link to="/node">Node JS</Link> |{" "}
        <Link to="/express">Express JS</Link>
      </nav>
      <Routes>
        <Route path="/react" element={<Ex1 />} />
        <Route path="/node" element={<Ex2 />} />
        <Route path="/express" element={<Ex3 />} />
      </Routes>
    </BrowserRouter>
  );
};

export default Main;

// App.js
import React from 'react';
import Main from './Main';

function App() {
  return <Main />;
}

export default App;

```

Q310: Routing — Home, Food Items, Contact (LJU-2025)

```
// Home.js
import React from 'react';
const Home = () => <h1><b>Welcome to LJU</b></h1>;
export default Home;

// FoodItems.js
import React from 'react';

const FoodItems = () => {
  const products = [
    { name: "Pizza", price: 200, description: "Cheesy delight" },
    { name: "Burger", price: 100, description: "Juicy and tasty" },
    { name: "Pasta", price: 150, description: "Italian style pasta" }
  ];
  return (
    <div>
      {products.map((p, i) => (
        <div key={i}>
          <h3>{p.name}</h3>
          <p>Price: {p.price}</p>
          <p>Description: {p.description}</p>
        </div>
      ))}
    </div>
  );
};

export default FoodItems;

// Contact.js
import React from 'react';
const Contact = () => (
  <p style={{ color: "blue" }}>Email: contact@lju.edu.in, Phone:
  1234567890</p>
);
export default Contact;

// Main.js
import React from 'react';
import { BrowserRouter, Routes, Route, Link } from 'react-router-dom';
import Home from './Home';
import FoodItems from './FoodItems';
import Contact from './Contact';

const Main = () => {
  return (
    <BrowserRouter>
      <nav>
```

```

    <Link to="/">Home</Link> |{" "}
    <Link to="/food">Food Items</Link> |{" "}
    <Link to="/contact">Contact</Link>
  </nav>
  <Routes>
    <Route path="/" element={<Home />} />
    <Route path="/food" element={<FoodItems />} />
    <Route path="/contact" element={<Contact />} />
  </Routes>
</BrowserRouter>
);
};

export default Main;

// App.js
import React from 'react';
import Main from './Main';

function App() {
  return <Main />;
}

export default App;

```

Q311: Pass Product Image, Name, Price via Array (map method)

```

// Product.js
import React from 'react';

const Product = (props) => {
  return (
    <div>
      <img src={props.pic} alt={props.name} width="100" />
      <p>Name: {props.name}</p>
      <p>Price: {props.price}</p>
    </div>
  );
};

export default Product;

// App.js
import React from 'react';
import Product from './Product';
import img1 from './p1.jpg';
import img2 from './p2.jpg';

function App() {
  const products = [

```

```

    { pic: img1, name: "Shoes", price: 1200 },
    { pic: img2, name: "Watch", price: 1500 }
  ];

  return (
    <div>
      {products.map((p, index) => (
        <Product key={index} pic={p.pic} name={p.name} price={p.price} />
      ))}
    </div>
  );
}

export default App;

```

Q312: CSS Props (bg color, font size, font style, text transform) Through Nested Components

```

// Example2.js
import React from 'react';

const Example2 = (props) => {
  const style = {
    backgroundColor: props.bgcolor,
    fontSize: props.fsize,
    fontStyle: props.fstyle,
    textTransform: props.ttransform
  };
  return <h1 style={style}>This is an React Application</h1>;
};

export default Example2;

// Example.js
import React from 'react';
import Example2 from './Example2';

const Example = () => {
  return (
    <Example2
      bgcolor="green"
      fsize="50px"
      fstyle="italic"
      ttransform="uppercase"
    />
  );
};

export default Example;

// App.js

```

```
import React from 'react';
import Example from './Example';
```

```
function App() {
  return <Example />;
}
```

```
export default App;
```

Q313: Routing for Login, Product, Contact, About

```
// component/Login.js
```

```
import React from 'react';
const Login = () => <h2>Login Page</h2>;
export default Login;
```

```
// component/Product.js
```

```
import React from 'react';
const Product = () => <h2>Product Page</h2>;
export default Product;
```

```
// component/Contact.js
```

```
import React from 'react';
const Contact = () => <h2>Contact Page</h2>;
export default Contact;
```

```
// component/About.js
```

```
import React from 'react';
const About = () => <h2>About Page</h2>;
export default About;
```

```
// Home.js
```

```
import React from 'react';
import { BrowserRouter, Routes, Route, Link } from 'react-router-dom';
import Login from './component/Login';
import Product from './component/Product';
import Contact from './component/Contact';
import About from './component/About';
```

```
const Home = () => {
  return (
    <BrowserRouter>
      <nav>
        <Link to="/login">Login</Link> |{" "}
        <Link to="/product">Product</Link> |{" "}
        <Link to="/contact">Contact</Link> |{" "}
        <Link to="/about">About</Link>
      </nav>
      <Routes>
        <Route path="/login" element={<Login />} />

```

```

        <Route path="/product" element={<Product />} />
        <Route path="/contact" element={<Contact />} />
        <Route path="/about" element={<About />} />
    </Routes>
  </BrowserRouter>
);
};

export default Home;

// App.js
import React from 'react';
import Home from './Home';

function App() {
  return <Home />;
}

export default App;

```

Q314: Pass Integer to Component, Print Table on Console

```

// Component.js
import React from 'react';

const Component = (props) => {
  let n = props.num;
  for (let i = 1; i <= 10; i++) {
    console.log(`${n} x ${i} = ${n * i}`);
  }
  return <h2>Table of {n} printed on console</h2>;
};

export default Component;

// App.js
import React from 'react';
import Component from './Component';

function App() {
  return (
    <div>
      <Component num={5} />
    </div>
  );
}

export default App;

```

Q315: Three Products Side by Side (Title, Image, Price, Description)

```
// Product.js
import React from 'react';

const Product = (props) => {
  return (
    <div style={{ display: "inline-block", margin: "10px", border: "1px solid gray", padding: "10px" }}>
      <h3>{props.title}</h3>
      <img src={props.image} alt={props.title} width="100" />
      <p>Price: {props.price}</p>
      <p>{props.description}</p>
    </div>
  );
};

export default Product;

// App.js
import React from 'react';
import Product from './Product';
import img1 from './p1.jpg';
import img2 from './p2.jpg';
import img3 from './p3.jpg';

function App() {
  return (
    <div>
      <Product title="Shoes" image={img1} price="1200"
description="Comfortable running shoes" />
      <Product title="Watch" image={img2} price="1500" description="Stylish
wrist watch" />
      <Product title="Bag" image={img3} price="800" description="Leather hand
bag" />
    </div>
  );
}

export default App;
```

Q316: Filter People Age < 40 (Functional Component)

```
// People.js
import React from 'react';

const People = (props) => {
  const result = props.data.filter((person) => person.age < 40);
  return (
    <div>
      {result.map((person, index) => (
```

```

        <p key={index}>{person.name}</p>
      )}}
    </div>
  );
};

```

```
export default People;
```

```
// App.js
```

```
import React from 'react';
import People from './People';
```

```
function App() {
  const data = [
    { name: "Amit", age: 35 },
    { name: "Suresh", age: 45 },
    { name: "Riya", age: 28 }
  ];
  return <People data={data} />;
}
```

```
export default App;
```

Q317: Routing — Home, Product, Contact (LJU-2023)

```
// Home.js
```

```
import React from 'react';
const Home = () => <h1><b>Welcome to LJU</b></h1>;
export default Home;
```

```
// Product.js
```

```
import React from 'react';

const Product = () => {
  const products = [
    { price: 200, description: "Item 1 description" },
    { price: 300, description: "Item 2 description" },
    { price: 400, description: "Item 3 description" }
  ];
  return (
    <div>
      {products.map((p, i) => (
        <div key={i}>
          <p>Price: {p.price}</p>
          <p>Description: {p.description}</p>
        </div>
      ))}
    </div>
  );
};

```

```

export default Product;

// Contact.js
import React from 'react';
const Contact = () => (
  <p style={{ color: "blue" }}>Email: contact@lju.edu.in</p>
);
export default Contact;

// Main.js
import React from 'react';
import { BrowserRouter, Routes, Route, Link } from 'react-router-dom';
import Home from './Home';
import Product from './Product';
import Contact from './Contact';

const Main = () => {
  return (
    <BrowserRouter>
      <nav>
        <Link to="/">Home</Link> |{" "}
        <Link to="/product">Product</Link> |{" "}
        <Link to="/contact">Contact</Link>
      </nav>
      <Routes>
        <Route path="/" element={<Home />} />
        <Route path="/product" element={<Product />} />
        <Route path="/contact" element={<Contact />} />
      </Routes>
    </BrowserRouter>
  );
};

export default Main;

// App.js
import React from 'react';
import Main from './Main';

function App() {
  return <Main />;
}

export default App;

```

Q318: Filter People with Age > 60 and Display Count

```

// People.js
import React from 'react';

```

```

const People = (props) => {
  const result = props.ages.filter((age) => age > 60);
  return (
    <div>
      <h3>People with age > 60:</h3>
      {result.map((age, index) => (
        <p key={index}>{age}</p>
      ))}
      <h4>Total count: {result.length}</h4>
    </div>
  );
};

```

```
export default People;
```

// App.js

```

import React from 'react';
import People from './People';

```

```

function App() {
  const ages = [70, 83, 38, 65, 49, 94];
  return <People ages={ages} />;
}

```

```
export default App;
```

Q319: File1 Component — productName, price, Add to Cart Alert

// File1.js

```
import React from 'react';
```

```

const File1 = (props) => {
  const handleClick = () => {
    alert("Your Product is Added to cart!");
  };

  return (
    <div>
      <h3>Product: {props.productName}</h3>
      <p>Price: {props.price}</p>
      <button onClick={handleClick}>Add to cart</button>
    </div>
  );
};

```

```
export default File1;
```

// App.js

```
import React from 'react';
```

```
import File1 from './File1';

function App() {
  return <File1 productName="Laptop" price="55000" />;
}

export default App;
```

Q320: Display id & name of Persons from Ahmedabad (Function Component, No App.js)

```
// Persons.js
import React from 'react';

const Persons = (props) => {
  const result = props.data.filter((person) => person.city === "Ahmedabad");
  return (
    <div>
      {result.map((person) => (
        <p key={person.id}>ID: {person.id}, Name: {person.name}</p>
      ))}
    </div>
  );
};

const data = [
  { id: 1, name: "Amit", city: "Ahmedabad" },
  { id: 2, name: "Riya", city: "Surat" },
  { id: 3, name: "Karan", city: "Ahmedabad" }
];

const App = () => <Persons data={data} />;

export default App;
```

Chapter 8 – React Hooks & Axios (MCQ Answers, Q321–355)

321. `axios.get("url").then(response).catch(error)`
322. **Used to create global variables** (more precisely: share data across components without prop drilling — given as correct option)
323. **e is not defined** (handleChange function did not receive parameter e)
324. **FALSE**
325. **Both "Male" and "Female" will be printed by selecting respective radio buttons**
326. **useState**
327. `const [state, dispatch] = useReducer(reducerFunction, initialState);`
328. **Share state and data between components without prop drilling.**
329. **An array with two elements: the current state value and a function to update the state.**

- 330. `const [count, setCount] = useState(0);`
- 331. `const theme = useContext(ThemeContext);`
- 332. It displays number 20 and increase the number by 5 each time when DoubleClick on button
- 333. `const contextValue = useContext(myContext);`
- 334. By using the `.catch()` method on the promise returned by Axios
- 335. `useEffect(() => { setTxt(true); }, []);`
- 336. It increments the seconds state every second
- 337. Initially the button text “Hide” and the text “Hello” will be displayed in the browser. Clicking that button will change button text to “Show” and the text will be hidden.

```
function fetchactivity(){
  axios
    .get(siteURL)
    .then((data) => console.log(data.data))
    .catch((error) => console.log(error))
}
```

- 339. It increments the count value by 1 on each click
- 340. `const [name, setName] = useState('John');`
- 341. Hello
- 342. `setShow(!show);`
- 343. `const user = useContext(UserContext);`
- 344. They automatically re-render with new theme value
- 345. Create Context in Parent and consume it using `useContext` in Child
- 346. The default value passed while creating `MyContext`
- 347. `dispatch({type:'increment'});`
- 348. Increase state by 5
- 349. When state logic is complex with multiple actions
- 350. Current state and dispatch function
- 351. Return current state
- 352. `useEffect(()=>{}, []);`
- 353. Inside `useEffect` with empty dependency array
- 354. Whenever count value changes
- 355. It runs after every render

Chapter 8 – Programming Questions (356–388)

Q356: Three Buttons – Change Text, Change Color, Hide/Show (`useState`)

```
// App.js
import React, { useState } from 'react';

function App() {
```

```

const [text, setText] = useState("React Js Hooks");
const [color, setColor] = useState("blue");
const [visible, setVisible] = useState(true);
const [btnLabel, setBtnLabel] = useState("Hide");

const changeText = () => {
  setText(text === "React Js Hooks" ? "Welcome students" : "React Js Hooks");
};

const changeColor = () => {
  setColor(color === "blue" ? "red" : "blue");
};

const toggleVisibility = () => {
  setVisible(!visible);
  setBtnLabel(visible ? "Show" : "Hide");
};

return (
  <div>
    <h1 style={{ color: "red" }}>LJ University</h1>
    {visible && <h2 style={{ color: color }}>{text}</h2>}
    <button onClick={changeText}>Change Text</button>
    <button onDoubleClick={changeColor}>Change Color</button>
    <button onClick={toggleVisibility}>{btnLabel}</button>
  </div>
);
}

export default App;

```

Q357: Change Image on Button Click

```

// App.js
import React, { useState } from 'react';
import img1 from './img1.jpg';
import img2 from './img2.jpg';

function App() {
  const [image, setImage] = useState(img1);

  const changeImage = () => {
    setImage(image === img1 ? img2 : img1);
  };

  return (
    <div>
      <img src={image} alt="img" width="200" />
      <br />
    </div>
  );
}

```

```

        <button onClick={changeImage}>Change Image</button>
      </div>
    );
  }

export default App;

```

Q358: Two Input Fields (First & Last Name) Display Entered Values

```

// App.js
import React, { useState } from 'react';

function App() {
  const [firstName, setFirstName] = useState("");
  const [lastName, setLastName] = useState("");

  return (
    <div>
      <input type="text" placeholder="First Name" onChange={(e) =>
setFirstName(e.target.value)} />
      <input type="text" placeholder="Last Name" onChange={(e) =>
setLastName(e.target.value)} />
      <h2>First Name: {firstName}</h2>
      <h2>Last Name: {lastName}</h2>
    </div>
  );
}

export default App;

```

Q359: To-Do List with Delete Button

```

// App.js
import React, { useState } from 'react';

function App() {
  const [task, setTask] = useState("");
  const [tasks, setTasks] = useState([]);

  const addTask = () => {
    if (task.trim() !== "") {
      setTasks([...tasks, task]);
      setTask("");
    }
  };

  const deleteTask = (index) => {
    const newTasks = tasks.filter((_, i) => i !== index);
    setTasks(newTasks);
  };
}

```

```

    return (
      <div>
        <input type="text" value={task} onChange={(e) =>
setTask(e.target.value)} />
        <button onClick={addTask}>Add Task</button>
        <ul>
          {tasks.map((t, index) => (
            <li key={index}>
              {t} <button onClick={() => deleteTask(index)}>Delete</button>
            </li>
          ))}
        </ul>
      </div>
    );
  }
}

export default App;

```

Q360: Show/Hide Text Using Button

```

// App.js
import React, { useState } from 'react';

function App() {
  const [show, setShow] = useState(true);

  return (
    <div>
      <button onClick={() => setShow(!show)}>{show ? "Hide" :
"Show"}</button>
      {show && <p>This is the text to show or hide.</p>}
    </div>
  );
}

export default App;

```

Q361: Two Number Inputs, Add Button, Display Sum

```

// App.js
import React, { useState } from 'react';

function App() {
  const [num1, setNum1] = useState(0);
  const [num2, setNum2] = useState(0);
  const [sum, setSum] = useState(0);

  const addNumbers = () => {
    setSum(Number(num1) + Number(num2));
  };
}

```

```

    return (
      <div>
        <input type="number" placeholder="Number 1" onChange={(e) =>
setNum1(e.target.value)} />
        <input type="number" placeholder="Number 2" onChange={(e) =>
setNum2(e.target.value)} />
        <button onClick={addNumbers}>Add</button>
        <h2>Sum: {sum}</h2>
      </div>
    );
  }
}

export default App;

```

Q362: Button “Change Text” Toggles “Hello” / “How are you?”

```

// App.js
import React, { useState } from 'react';

function App() {
  const [text, setText] = useState("Hello");

  const changeText = () => {
    setText(text === "Hello" ? "How are you?" : "Hello");
  };

  return (
    <div>
      <h2>{text}</h2>
      <button onClick={changeText}>Change Text</button>
    </div>
  );
}

export default App;

```

Q363: Increase Count by 1 Using useState

```

// App.js
import React, { useState } from 'react';

function App() {
  const [count, setCount] = useState(0);

  return (
    <div>
      <h2>Count: {count}</h2>
      <button onClick={() => setCount(count + 1)}>Increment</button>
    </div>
  );
}

```

```
export default App;
```

Q364: Increment/Decrement with Limit (0 to 10)

// App.js

```
import React, { useState } from 'react';

function App() {
  const [count, setCount] = useState(0);

  const increment = () => {
    if (count < 10) setCount(count + 1);
  };

  const decrement = () => {
    if (count > 0) setCount(count - 1);
  };

  return (
    <div>
      <h2>Count: {count}</h2>
      <button onClick={increment}>Increment</button>
      <button onClick={decrement}>Decrement</button>
    </div>
  );
}

export default App;
```

Q365: Digital Clock (useEffect)

// App.js

```
import React, { useState, useEffect } from 'react';

function App() {
  const [time, setTime] = useState(new Date());

  useEffect(() => {
    const timer = setInterval(() => {
      setTime(new Date());
    }, 1000);
    return () => clearInterval(timer);
  }, []);

  return (
    <div>
      <h1>{time.toLocaleTimeString()}</h1>
    </div>
  );
}
```

```
export default App;
```

Q366: Multiply Two Numbers Using useContext (Comp.js → Comp1, Comp2, Comp3)

```
// NumberContext.js
```

```
import React from 'react';  
export const NumberContext = React.createContext();
```

```
// Comp1.js
```

```
import React from 'react';  
import Comp2 from './Comp2';
```

```
const Comp1 = () => {  
  return <Comp2 />;  
};
```

```
export default Comp1;
```

```
// Comp2.js
```

```
import React from 'react';  
import Comp3 from './Comp3';
```

```
const Comp2 = () => {  
  return <Comp3 />;  
};
```

```
export default Comp2;
```

```
// Comp3.js
```

```
import React, { useContext } from 'react';  
import { NumberContext } from './NumberContext';
```

```
const Comp3 = () => {  
  const { num1, num2 } = useContext(NumberContext);  
  return <h2>Multiplication: {num1 * num2}</h2>;  
};
```

```
export default Comp3;
```

```
// Comp.js
```

```
import React from 'react';  
import { NumberContext } from './NumberContext';  
import Comp1 from './Comp1';
```

```
const Comp = () => {  
  const num1 = 5;  
  const num2 = 10;  
  
  return (  
    <div>  
      <h1>React Context</h1>  
      <div>  
        <div>NumberContext</div>  
        <div>Comp1</div>  
        <div>Comp2</div>  
        <div>Comp3</div>  
      </div>  
    </div>  
  );  
};
```

```

    <NumberContext.Provider value={{ num1, num2 }}>
      <Comp1 />
    </NumberContext.Provider>
  );
};

export default Comp;

```

Q367: Pass Username from Main.js to Comp2.js (Display in Blue)

```

// UserContext.js
import React from 'react';
export const UserContext = React.createContext();

// Comp1.js
import React from 'react';
import Comp2 from './Comp2';

const Comp1 = () => {
  return <Comp2 />;
};

export default Comp1;

// Comp2.js
import React, { useContext } from 'react';
import { UserContext } from './UserContext';

const Comp2 = () => {
  const username = useContext(UserContext);
  return <h2 style={{ color: "blue" }}>{username}</h2>;
};

export default Comp2;

// Main.js
import React from 'react';
import { UserContext } from './UserContext';
import Comp1 from './Comp1';

const Main = () => {
  const username = "Ravi";

  return (
    <UserContext.Provider value={username}>
      <Comp1 />
    </UserContext.Provider>
  );
};

```

```

export default Main;

// App.js
import React from 'react';
import Main from './Main';

function App() {
  return <Main />;
}

export default App;

```

Q368: Sign-up Form with Alert on Submit

```

// App.js
import React, { useState } from 'react';

function App() {
  const [username, setUsername] = useState("");
  const [age, setAge] = useState("");
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [confirmPassword, setConfirmPassword] = useState("");

  const handleSubmit = () => {
    alert(`Username: ${username}, Age: ${age}, Email: ${email}`);
  };

  return (
    <div>
      <input type="text" placeholder="Username" onChange={(e) =>
setUsername(e.target.value)} />
      <input type="number" placeholder="Age" onChange={(e) =>
setAge(e.target.value)} />
      <input type="email" placeholder="Email" onChange={(e) =>
setEmail(e.target.value)} />
      <input type="password" placeholder="Password" onChange={(e) =>
setPassword(e.target.value)} />
      <input type="password" placeholder="Confirm Password" onChange={(e) =>
setConfirmPassword(e.target.value)} />
      <button onClick={handleSubmit}>Submit</button>
    </div>
  );
}

export default App;

```

Q369: Email and Password Validation Form

```

// App.js
import React, { useState } from 'react';

```

```

function App() {
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [message, setMessage] = useState("");

  const validate = () => {
    const emailRegex = /^[^\s@]+@[^\s@]+\.[^\s@]+$/;
    if (!emailRegex.test(email)) {
      setMessage("Invalid Email");
    } else if (password.length < 6) {
      setMessage("Password must be at least 6 characters");
    } else {
      setMessage("Valid Input");
    }
  };

  return (
    <div>
      <input type="email" placeholder="Email" onChange={(e) =>
setEmail(e.target.value)} />
      <input type="password" placeholder="Password" onChange={(e) =>
setPassword(e.target.value)} />
      <button onClick={validate}>Submit</button>
      <p>{message}</p>
    </div>
  );
}

export default App;

```

Q370: Pizza Size Selection Using Radio Buttons

```

// App.js
import React, { useState } from 'react';

function App() {
  const [size, setSize] = useState("");

  return (
    <div>
      <input type="radio" name="size" value="Small" onChange={(e) =>
setSize(e.target.value)} /> Small
      <input type="radio" name="size" value="Medium" onChange={(e) =>
setSize(e.target.value)} /> Medium
      <input type="radio" name="size" value="Large" onChange={(e) =>
setSize(e.target.value)} /> Large
      <p>Selected Size: {size}</p>
    </div>
  );
}

```

```
}  
  
export default App;
```

Q371: Increment/Decrement Using useReducer

```
// App.js  
import React, { useReducer } from 'react';  
  
const reducer = (state, action) => {  
  switch (action.type) {  
    case 'increment':  
      return state + 1;  
    case 'decrement':  
      return state - 1;  
    default:  
      return state;  
  }  
};  
  
function App() {  
  const [count, dispatch] = useReducer(reducer, 0);  
  
  return (  
    <div>  
      <h2>Count: {count}</h2>  
      <button onClick={() => dispatch({ type: 'increment'  
    })}>Increment</button>  
      <button onClick={() => dispatch({ type: 'decrement'  
    })}>Decrement</button>  
    </div>  
  );  
}  
  
export default App;
```

Q372: Button “Click” Increments by 5, Initial Value 20 (useReducer)

```
// App.js  
import React, { useReducer } from 'react';  
  
const reducer = (state, action) => {  
  return state + action;  
};  
  
function App() {  
  const [value, dispatch] = useReducer(reducer, 20);  
  
  return (  
    <div>  
      <h2>Value: {value}</h2>
```

```

        <button onClick={() => dispatch(5)}>Click</button>
      </div>
    );
  }

export default App;

```

Q373: Random Joke Using Axios

```

// App.js
import React, { useState } from 'react';
import axios from 'axios';

function App() {
  const [joke, setJoke] = useState("");

  const getJoke = () => {
    axios.get("https://official-joke-api.appspot.com/random_joke")
      .then((response) => {
        setJoke(response.data.setup + " - " + response.data.punchline);
      })
      .catch((error) => console.log(error));
  };

  return (
    <div>
      <button onClick={getJoke}>Get Joke</button>
      <p>{joke}</p>
    </div>
  );
}

export default App;

```

Q374: Exam Form with useState and Validation (LJU2023, LJU2025)

```

// App.js
import React, { useState } from 'react';

function App() {
  const [name, setName] = useState("");
  const [email, setEmail] = useState("");
  const [password, setPassword] = useState("");
  const [gender, setGender] = useState("");
  const [examDate, setExamDate] = useState("");
  const [examCenter, setExamCenter] = useState("");
  const [submitted, setSubmitted] = useState(null);
  const [error, setError] = useState("");

  const handleSubmit = () => {
    const emailRegex = /^[^\s@]+@[^\s@]+\.[^\s@]+$/;

```

```

    if (!emailRegex.test(email)) {
        setError("Invalid email");
        return;
    }
    if (password.length < 6) {
        setError("Password must be at least 6 characters");
        return;
    }
    setError("");
    setSubmitted({ name, email, password, gender, examDate, examCenter });
};

return (
    <div>
        <input type="text" placeholder="Name" onChange={(e) =>
setName(e.target.value)} />
        <input type="email" placeholder="Email" onChange={(e) =>
setEmail(e.target.value)} />
        <input type="password" placeholder="Password" onChange={(e) =>
setPassword(e.target.value)} />

        <input type="radio" name="gender" value="Male" onChange={(e) =>
setGender(e.target.value)} /> Male
        <input type="radio" name="gender" value="Female" onChange={(e) =>
setGender(e.target.value)} /> Female

        <input type="date" onChange={(e) => setExamDate(e.target.value)} />

        <select onChange={(e) => setExamCenter(e.target.value)}>
            <option value="">Select Center</option>
            <option value="Ahmedabad">Ahmedabad</option>
            <option value="Surat">Surat</option>
            <option value="Vadodara">Vadodara</option>
        </select>

        <button onClick={handleSubmit}>Submit</button>

        {error && <p style={{ color: "red" }}>{error}</p>}
        {submitted && (
            <div>
                <p>Name: {submitted.name}</p>
                <p>Email: {submitted.email}</p>
                <p>Gender: {submitted.gender}</p>
                <p>Exam Date: {submitted.examDate}</p>
                <p>Exam Center: {submitted.examCenter}</p>
            </div>
        )}
    </div>
);

```

```
}
```

```
export default App;
```

Q375: Display Random Flower Image Using Axios

```
// App.js
```

```
import React, { useState, useEffect } from 'react';  
import axios from 'axios';
```

```
function App() {  
  const [image, setImage] = useState("");  
  
  useEffect(() => {  
    axios.get("https://flower.ceo/api/image/random")  
      .then((response) => {  
        setImage(response.data.sample);  
      })  
      .catch((error) => console.log(error));  
  }, []);  
  
  return (  
    <div>  
      <h2>Random Flower</h2>  
      {image && <img src={image} alt="flower" width="300" />}  
    </div>  
  );  
}
```

```
export default App;
```

Q376: Student Data Entry Form with Alert (useState)

```
// App.js
```

```
import React, { useState } from 'react';
```

```
function App() {  
  const [name, setName] = useState("");  
  const [gender, setGender] = useState("");  
  const [subject, setSubject] = useState("");  
  const [comments, setComments] = useState("");  
  
  const handleSubmit = () => {  
    alert(`Name: ${name}, Gender: ${gender}, Subject: ${subject}, Comments: ${comments}`);  
  };  
  
  return (  
    <div>  
      <input type="text" placeholder="Student Name" onChange={(e) =>  
        setName(e.target.value)} />  
    </div>  
  );  
}
```

```

    <input type="radio" name="gender" value="Boy" onChange={(e) =>
setGender(e.target.value)} /> Boy
    <input type="radio" name="gender" value="Girl" onChange={(e) =>
setGender(e.target.value)} /> Girl

    <select onChange={(e) => setSubject(e.target.value)}>
      <option value="">Select Subject</option>
      <option value="English">English</option>
      <option value="Gujarati">Gujarati</option>
    </select>

    <textarea placeholder="Comments" onChange={(e) =>
setComments(e.target.value)}></textarea>

    <button onClick={handleSubmit}>Submit</button>
  </div>
);
}

export default App;

```

Q377: Survey Form with Radio Buttons & Dropdowns, Display in Alert (No App.js needed)

```

// Survey.js
import React, { useState } from 'react';

const Survey = () => {
  const [gender, setGender] = useState("");
  const [course, setCourse] = useState("");
  const [feedback, setFeedback] = useState("");

  const handleSubmit = () => {
    alert(`Gender: ${gender}\nCourse: ${course}\nFeedback: ${feedback}`);
  };

  return (
    <div>
      <p>Gender:</p>
      <input type="radio" name="gender" value="Male" onChange={(e) =>
setGender(e.target.value)} /> Male
      <input type="radio" name="gender" value="Female" onChange={(e) =>
setGender(e.target.value)} /> Female

      <p>Course:</p>
      <select onChange={(e) => setCourse(e.target.value)}>
        <option value="">Select</option>
        <option value="FSD">FSD</option>
        <option value="Python">Python</option>
        <option value="Java">Java</option>
      </select>
    </div>
  );
}

```

```

    </select>

    <p>Feedback:</p>
    <select onChange={(e) => setFeedback(e.target.value)}>
      <option value="">Select</option>
      <option value="Excellent">Excellent</option>
      <option value="Good">Good</option>
      <option value="Average">Average</option>
    </select>

    <br />
    <button onClick={handleSubmit}>Submit</button>
  </div>
);
};

export default Survey;

```

Q378: useContext Passes Two Colors (Parent/Child) — Background & Font

```

// ColorContext.js
import React from 'react';
export const ColorContext = React.createContext();

// Child.js
import React, { useContext } from 'react';
import { ColorContext } from './ColorContext';

const Child = () => {
  const { bgColor, textColor } = useContext(ColorContext);
  return (
    <div style={{ backgroundColor: bgColor }}>
      <h2 style={{ color: textColor }}>Welcome to LJU</h2>
    </div>
  );
};

export default Child;

// Parent.js
import React from 'react';
import { ColorContext } from './ColorContext';
import Child from './Child';

const Parent = () => {
  return (
    <ColorContext.Provider value={{ bgColor: "red", textColor: "green" }}>
      <Child />
    </ColorContext.Provider>
  );
};

```

```

};

export default Parent;

// App.js
import React from 'react';
import Parent from './Parent';

function App() {
  return <Parent />;
}

export default App;

```

Q379: useContext to Pass Two Colors (P.js → C2.js via C1.js)

```

// ColorContext.js
import React from 'react';
export const ColorContext = React.createContext();

// C2.js
import React, { useContext } from 'react';
import { ColorContext } from './ColorContext';

const C2 = () => {
  const { fontColor, bgColor } = useContext(ColorContext);
  return (
    <h1 style={{ color: fontColor, backgroundColor: bgColor }}>
      Full stack Development
    </h1>
  );
};

export default C2;

// C1.js
import React from 'react';
import C2 from './C2';

const C1 = () => {
  return <C2 />;
};

export default C1;

// P.js
import React from 'react';
import { ColorContext } from './ColorContext';
import C1 from './C1';

```

```

const P = () => {
  return (
    <ColorContext.Provider value={{ fontColor: "yellow", bgColor: "blue" }}>
      <C1 />
    </ColorContext.Provider>
  );
};

export default P;

// App.js
import React from 'react';
import P from './P';

function App() {
  return <P />;
}

export default App;

```

Q380: Two Numbers — Add/Subtract with useState, Alert on Add (useEffect)

```

// App.js
import React, { useState, useEffect } from 'react';

function App() {
  const [num1, setNum1] = useState(0);
  const [num2, setNum2] = useState(0);
  const [sum, setSum] = useState(0);
  const [diff, setDiff] = useState(0);
  const [addClicked, setAddClicked] = useState(false);

  const handleAdd = () => {
    setSum(Number(num1) + Number(num2));
    setAddClicked(true);
  };

  const handleSubtract = () => {
    setDiff(Number(num1) - Number(num2));
  };

  useEffect(() => {
    if (addClicked) {
      alert("Addition button clicked!");
      setAddClicked(false);
    }
  }, [addClicked]);

  return (
    <div>

```

```

        <input type="number" onChange={(e) => setNum1(e.target.value)}
placeholder="Number 1" />
        <input type="number" onChange={(e) => setNum2(e.target.value)}
placeholder="Number 2" />
        <button onClick={handleAdd}>Add</button>
        <button onClick={handleSubtract}>Subtract</button>
        <p>Sum: {sum}</p>
        <p>Difference: {diff}</p>
    </div>
  );
}

export default App;

```

Q381: Form (F1.js) with Multiple Fields, Display All Values via useContext + useState

```

// FormContext.js
import React from 'react';
export const FormContext = React.createContext();

// F3.js
import React, { useContext } from 'react';
import { FormContext } from './FormContext';

const F3 = () => {
  const data = useContext(FormContext);
  alert(`First Name: ${data.firstName}\nLast Name: ${data.lastName}\nMessage:
${data.message}\nCity: ${data.city}\nGender: ${data.gender}`);
  return <h3>Submitted data shown in alert.</h3>;
};

export default F3;

// F2.js
import React from 'react';
import F3 from './F3';

const F2 = () => {
  return <F3 />;
};

export default F2;

// F1.js
import React, { useState } from 'react';
import { FormContext } from './FormContext';
import F2 from './F2';

const F1 = () => {
  const [firstName, setFirstName] = useState("");

```

```

const [lastName, setLastName] = useState("");
const [message, setMessage] = useState("");
const [city, setCity] = useState("");
const [gender, setGender] = useState("");
const [submitted, setSubmitted] = useState(false);

const handleSubmit = () => {
  setSubmitted(true);
};

const data = { firstName, lastName, message, city, gender };

return (
  <div>
    <input type="text" placeholder="First Name" onChange={(e) =>
setFirstName(e.target.value)} />
    <input type="text" placeholder="Last Name" onChange={(e) =>
setLastName(e.target.value)} />
    <textarea placeholder="Message" onChange={(e) =>
setMessage(e.target.value)}></textarea>

    <select onChange={(e) => setCity(e.target.value)}>
      <option value="">Select City</option>
      <option value="Ahmedabad">Ahmedabad</option>
      <option value="Surat">Surat</option>
    </select>

    <input type="radio" name="gender" value="Male" onChange={(e) =>
setGender(e.target.value)} /> Male
    <input type="radio" name="gender" value="Female" onChange={(e) =>
setGender(e.target.value)} /> Female

    <button onClick={handleSubmit}>Submit</button>

    {submitted && (
      <FormContext.Provider value={data}>
        <F2 />
      </FormContext.Provider>
    )}
  </div>
);
};

export default F1;

```

Q382: useContext Pass fontStyle and fontSize (P.js → C2.js via C1.js)

```

// FontContext.js
import React from 'react';
export const FontContext = React.createContext();

```

```

// C2.js
import React, { useContext } from 'react';
import { FontContext } from './FontContext';

const C2 = () => {
  const { fontStyle, fontSize } = useContext(FontContext);
  return (
    <h1 style={{ fontStyle: fontStyle, fontSize: fontSize }}>
      Full stack Development
    </h1>
  );
};

export default C2;

// C1.js
import React from 'react';
import C2 from './C2';

const C1 = () => {
  return <C2 />;
};

export default C1;

// P.js
import React from 'react';
import { FontContext } from './FontContext';
import C1 from './C1';

const P = () => {
  return (
    <FontContext.Provider value={{ fontStyle: "italic", fontSize: "30px" }}>
      <C1 />
    </FontContext.Provider>
  );
};

export default P;

// App.js
import React from 'react';
import P from './P';

function App() {
  return <P />;
}

```

```
export default App;
```

Q383: Dark Mode / Light Mode Toggle

// App.js

```
import React, { useState } from 'react';
```

```
function App() {
  const [darkMode, setDarkMode] = useState(false);

  const style = {
    backgroundColor: darkMode ? "black" : "white",
    color: darkMode ? "white" : "black",
    height: "100vh"
  };

  return (
    <div style={style}>
      <button onClick={() => setDarkMode(true)}>Dark Mode</button>
      <button onClick={() => setDarkMode(false)}>Light Mode</button>
      <p>This is sample text content.</p>
    </div>
  );
}
```

```
export default App;
```

Q384: Textarea with Live Character Count (Red if > 100)

// App.js

```
import React, { useState } from 'react';
```

```
function App() {
  const [text, setText] = useState("");

  return (
    <div>
      <textarea
        rows="5"
        cols="40"
        onChange={(e) => setText(e.target.value)}
      ></textarea>
      <p style={{ color: text.length > 100 ? "red" : "black" }}>
        Character count: {text.length}
      </p>
    </div>
  );
}
```

```
export default App;
```

Q385: Start/Stop Buttons with Counter (useEffect Cleanup)

```
// App.js
import React, { useState, useEffect } from 'react';

function App() {
  const [count, setCount] = useState(0);
  const [running, setRunning] = useState(false);

  useEffect(() => {
    let timer;
    if (running) {
      timer = setInterval(() => {
        setCount((prev) => prev + 1);
      }, 1000);
    }
    return () => clearInterval(timer);
  }, [running]);

  return (
    <div>
      <h2>Counter: {count}</h2>
      <button onClick={() => setRunning(true)}>Start</button>
      <button onClick={() => setRunning(false)}>Stop</button>
    </div>
  );
}

export default App;
```

Q386: Product Quantity with Add/Remove (useReducer, Min 0)

```
// App.js
import React, { useReducer } from 'react';

const reducer = (state, action) => {
  switch (action.type) {
    case 'add':
      return state + 1;
    case 'remove':
      return state > 0 ? state - 1 : 0;
    default:
      return state;
  }
};

function App() {
  const [quantity, dispatch] = useReducer(reducer, 0);

  return (
    <div>
```

```

        <h2>Quantity: {quantity}</h2>
        <button onClick={() => dispatch({ type: 'add' })}>Add Item</button>
        <button onClick={() => dispatch({ type: 'remove' })}>Remove
Item</button>
      </div>
    );
  }

export default App;

```

Q387: Language Toggle (English/Hindi) via useContext

```

// LanguageContext.js
import React from 'react';
export const LanguageContext = React.createContext();

// Child.js
import React, { useContext } from 'react';
import { LanguageContext } from './LanguageContext';

const Child = () => {
  const language = useContext(LanguageContext);
  return (
    <h2>{language === "English" ? "Welcome" : "□□□□□□"}</h2>
  );
};

export default Child;

// Parent.js
import React, { useState } from 'react';
import { LanguageContext } from './LanguageContext';
import Child from './Child';

const Parent = () => {
  const [language, setLanguage] = useState("English");

  const toggleLanguage = () => {
    setLanguage(language === "English" ? "Hindi" : "English");
  };

  return (
    <LanguageContext.Provider value={language}>
      <button onClick={toggleLanguage}>Toggle Language</button>
      <Child />
    </LanguageContext.Provider>
  );
};

export default Parent;

```

```
// App.js
import React from 'react';
import Parent from './Parent';

function App() {
  return <Parent />;
}

export default App;
```

Q388: Weather App Using Axios (Input City, Display Temp/Humidity/Description)

```
// App.js
import React, { useState } from 'react';
import axios from 'axios';

function App() {
  const [city, setCity] = useState("");
  const [weather, setWeather] = useState(null);
  const [error, setError] = useState("");
  const [loading, setLoading] = useState(false);

  const apiKey = "YOUR_API_KEY";

  const getWeather = () => {
    setLoading(true);
    setError("");
    setWeather(null);

    axios.get(`https://api.openweathermap.org/data/2.5/weather?q=${city}&appid=${apiKey}&units=metric`)
      .then((response) => {
        setWeather(response.data);
        setLoading(false);
      })
      .catch(() => {
        setError("City not found");
        setLoading(false);
      });
  };

  return (
    <div>
      <input type="text" placeholder="Enter city name" onChange={(e) => setCity(e.target.value)} />
      <button onClick={getWeather}>Get Weather</button>

      {loading && <p>Loading...</p>}
      {error && <p style={{ color: "red" }}>{error}</p>}
    </div>
  );
}
```

```
    {weather && (  
      <div>  
        <p>Temperature: {weather.main.temp} °C</p>  
        <p>Humidity: {weather.main.humidity}%</p>  
        <p>Description: {weather.weather[0].description}</p>  
      </div>  
    )}  
  </div>  
);  
}  
  
export default App;
```