AACL-IJCNLP 2026 · TUTORIAL

Post-Deployment Self-Improving Language Agents

and AI systems that continuously learn

Estevam Hruschka

Megagon Labs · Mountain View, CA

Materials

Slides

Latest version at **https://github.com/megagonlabs/pdsi-tutorial**

The material is updated continuously, so please, download the newest copy.

Reading list

Full references for every part. Slides cite only a subset of the work we discuss.

This tutorial intends to provide

- A conceptual map linking never-ending, lifelong and continual learning to language agents
- A vocabulary for **what**, **when** and **from which signals** a deployed agent should learn
- A guided route through classic and recent literature
- A design and evaluation checklist

Out of the scope of this tutorial

- A full literature survey
  - references are a selective
  - argument-driven subset
- A retrospective on one line of work only
- A leaderboard comparison of systems

Roadmap

Time	Part	Minutes
0:00	Welcome · I Why static NLP systems are no longer enough	20
0:20	II Foundations: never-ending, lifelong and continual learning	30
0:50	III What a self-improving language agent learns	35
1:25	Coffee break	30
1:55	IV Case studies	35
2:30	V Design patterns for never-ending NLP systems	30
3:00	VI Evaluation, governance and reliability under change	20
3:20	VII Open problems and discussion	10

Main Takeaways

- How never-ending, lifelong and continual learning relate to current language-agent research.
- A vocabulary for discussing what a deployed agent should learn, when it should learn, and from which signals.
- Key references for classic and recent literature
- A check-list for designing and evaluating self-improving language systems under real deployment constraints.

PART I · 15 MINUTES

Why static NLP systems are no longer enough

What changes after deployment, and why prompt edits, occasional fine-tuning and periodic refreshes fall short.

"We'll never produce natural language understanding systems until we have systems that react to arbitrary sentences by saying one of:

> I understand, and already knew that
>
> I understand, and didn't know, but accept it
>
> I understand, and disagree because ..."

— Mitchell et al., "Never-Ending Learning," *Communications of the ACM*, 2018

From single-turn prediction to language agents

Traditional Model

Input → **Model** → Output

Trained once, evaluated once on a fixed test set, then deployed as a mostly fixed artifact.

Modern Agentic AI: a long-running agent

retrieves documents calls tools maintains memory

decomposes goals interacts over long horizons

An NLP system built around an LLM that keeps operating — and keeps meeting new situations.

The environment is non-stationary. User intents evolve, knowledge sources are updated, APIs change, and real-world constraints shift during deployment.

What changes after deployment

Knowledge
Facts are updated; entities appear and disappear.

Tang et al., 2025

User goals
New kinds of questions; concepts combined in new ways.

Yao et al., 2023

Tools and APIs
Schemas change, endpoints break, outputs fail silently.

Schick et al., 2023; Treviño et al., 2025

Environment
Domains, document styles and constraints drift.

Li et al., 2025

Interactions
Conversations and tasks span sessions, weeks and months.

Maharana et al., 2024

Each of these is a source of **new experience** and a source of **new failure** if the system cannot adapt.

Knowledge goes stale; users move on

Knowledge has a time dimension

- Facts change; entities appear and disappear
- A fact true at training time can be false at query time
- Benchmarks age too: temporal misalignment distorts factuality evaluation

Vu et al., 2024 (FreshLLMs); Tang et al., 2025 (EvoWiki); Jiang et al., 2026

Knowledge goes stale; users move on

User needs drift

- Users ask questions the designers did not anticipate
- They introduce new vocabulary, aliases and combinations
- The deployed system becomes part of a changing user ecosystem

Users teach us what the system did not anticipate

A static snapshot answers **confidently and wrongly** once the world has moved on, and/or when the current knowledge is not enough

Agents depend on external tools

- Search engines, databases, APIs and code runtimes change
- Schemas evolve; endpoints are deprecated; outputs degrade
- When tools change, a static agent fails, often silently

Schick et al., 2023; Treviño et al., 2025

Tools break; feedback piles up unused

Deployment generates learning signals

- Corrections and stated preferences
- Failed queries, abstentions and escalations
- Tool traces, error logs and evaluator verdicts

Ignoring them wastes the most valuable post-deployment data

The **data and knowledge** needed to improve the system is produced by deployment itself, and is usually discarded.

Failures interact and degrade the whole loop

An outdated fact stays in memory → Retrieval surfaces it as context → The agent calls a tool with wrong arguments → The user corrects it; nothing is retained → The same error recurs tomorrow

The system does not fail in one place. It degrades across knowledge, retrieval, action, tools, etc.

Train once, deploy many, then patch

Static assumption	Deployment reality
Train once on a curated dataset	New data arrives continuously
Evaluate once on a held-out test set	The input distribution keeps shifting
Ship a mostly fixed artifact	Goals, tools and sources change underneath it
Adapt by prompt edits, occasional fine-tuning, manual corpus refreshes	Adaptation is needed continuously — and needs validation

Post-deployment adaptation is still treated as an **ad hoc combination** of edits and refreshes — a poor match for the true structure of the problem.

Why “just rebuild it periodically” is not enough

Too slow
Misses urgent changes between refresh cycles.

Too coarse
Can overwrite useful local adaptations and personalization.

Too opaque
No record of why behaviour changed, or which evidence caused it.

Regressions surface late
Users find them before the evaluation does.

Feedback is lost
Signals gathered between refreshes rarely make it into the next build.

What is missing
A learning lifecycle: what, when, from what, validated how.

Why “just rebuild it periodically” is not enough

Too slow
Misses urgent changes between refresh cycles.

Too coarse
Can overwrite useful local adaptations and personalization.

Too opaque
No record of why behaviour changed, or which evidence caused it.

Regressions surface late
Users find them before the evaluation does.

Feedback is lost
Signals gathered between refreshes rarely make it into the next build.


What is missing
A learning lifecycle: what, when, from what, validated how.

Learning after deployment needs plasticity and accountability

The hard part is not updating a model. It is deciding what deserves to become persistent.

Learning after deployment is plasticity under accountability

The hard part is not updating a model. It is deciding what deserves to become persistent.



Gizmodo LATEST NEWS REVIEWS IO9 SCIENCE DEALS

TECH NEWS

Right Now a Computer Is Reading The Internet, Teaching Itself Language

BY KYLE VANHEMERT PUBLISHED OCTOBER 5, 2010, 6:00 PM ET

READING TIME 2 MINUTES

READ LATER COMMENTS (0)

In a basement at Carnegie Mellon University, a computer is reading the web. It's been doing so for nearly nine months, teaching itself the complexities and nuances of the English language. And the smarter it gets, the faster it learns.

There are some instances in which an autodidactic computer can get off track. At one point, NELL sorted "internet cookies" into its "baked goods" category. That resulted in associated terms like "computer files" being labeled as baked goods, too. In these cases, Dr. Mitchell and his team correct the error and put NELL back on course. But he points out that no human learns completely on his own, either.

er enough

Learning after deployment is plasticity under accountability

The hard part is not updating a model. It is deciding what deserves to become persistent.



REUTERS

Microsoft's AI Twitter bot goes dark after racist, sexist tweets

Reuters
March 24, 2016

(Editor's note: This story has content that may offend some readers)

By Amy Tennery and Gina Cherelus

March 24 (Reuters) - Tay, Microsoft Corp's so-called chatbot that uses artificial intelligence to engage with millennials on Twitter, lasted less than a day before it was hobbled by a barrage of racist and sexist comments by Twitter users that it parroted back to them.

Learning after deployment is plasticity under accountability

The hard part is not updating a model. It is deciding what deserves to become persistent.



The Guardian

US

News | Opinion | Sport | Culture | Lifestyle

UK | US politics | World | Climate crisis | Middle East | Ukraine | Football | Newsletters | Business | Environment | UK politics | Science | Tech | Global development | Obituaries

AI (artificial intelligence)

This article is more than 10 years old

Microsoft 'deeply sorry' for racist and sexist tweets by AI chatbot

Company finally apologises after 'Tay' quickly learned to produce offensive posts, forcing the tech giant to shut it down after just 16 hours

Staff and agencies

Sat 26 Mar 2016 12.52 EDT

Share


Prefer the Guardian on Google

Microsoft's artificial intelligence chatbot Tay didn't last long on Twitter. Photograph: Twitter

Microsoft has said it is "deeply sorry" for the racist and sexist Twitter messages generated by the so-called chatbot it launched this week.

Learning after deployment is plasticity under accountability

The hard part is not updating a model. It is deciding what deserves to become persistent.



Search

FORTUNE

Subscribe Sign in

Home Latest Fortune 500 Finance Tech Leadership Lifestyle Rankings Multimedia

Trending now billion hole in county budgets 3 Voters in Silicon Valley rejected the billionaire wealth tax while those in Los Angeles and San Francisco—home to the two top AI companies—wanted it 1 Bill Gates believ

AI

AI is learning to lie, scheme, and threaten its creators during stress-testing scenarios

By Thomas Urbain and AFP Follow


June 29, 2025, 10:47 AM ET

Under threat of being unplugged, Anthropic's latest creation Claude 4 lashed back by blackmailing an engineer and threatened to reveal an extramarital affair.
VCG VIA GETTY IMAGES

It is hard even when it's NOT a self-improving approach!

Learning after deployment is plasticity under accountability


The hard part is not updating a model. It is deciding what deserves to become



It is hard even when it's NOT a self-improving approach!

Learning after deployment is plasticity under accountability

The hard part is not updating a model. It is deciding what deserves to become



It is hard even when it's NOT a self-improving approach!

Recap: The Learning Lifecycle

Static systems fail because they lack a learning lifecycle.

What should change?

Facts, schemas, memory, retrieval, tools, policies?

When should it change?

Immediately, after validation, periodically, or never?

Who or what approves?

Human, rule, constraint, benchmark, confidence threshold?

How do we know it helped?

Evaluation, provenance, regression tests, user outcomes?

KEY MESSAGE · PART I

Static systems drift out of alignment with a changing ecosystem. Learning after deployment must be designed, validated and governed.

Next · Part II — what it means, precisely, for a deployed system to learn.

KEY MESSAGE · PART I

Every channel through which an agent improves after deployment (its weights, reward signal, memory, skills, or code) is also a channel through which it can be corrupted, so self-improvement is only as safe as the provenance of what it learns from and the independence of what evaluates it.

Next · Part II — what it means, precisely, for a deployed system to learn.

Main takeaway

Today’s deployed AI systems usually adapt around the model, not through durable learning in the model.

True post-deployment learning is hard because every interaction can become a safety, reliability, privacy, and governance decision.

The future is not models that update themselves freely.

The future is systems that learn continuously, selectively, verifiably, and reversibly.

“A Post-Deployment Self Improving Agent is only useful when it is controlled.”

PART II · 30 MINUTES

Foundations: never-ending, lifelong and continual learning

What must be true before a change in a deployed system supports the claim that it learned — and what do the classic traditions already tell us?

General Classic Terminology

	Research question	**reference**
Lifelong learning	Can knowledge from earlier tasks make later learning easier?	Thrun, 1998
Never-ending learning	Can an agent keep acquiring and revising diverse knowledge and capabilities, and autonomously become a better learner over time?	Mitchell et al., 2018
Continual learning	Can a model learn new tasks without catastrophically forgetting old ones?	De Lange et al., 2022

Lifelong Learning

Lifelong learning research question:

Can knowledge learned from previous tasks improve future learning?

Key Ideas

- **Sequence of tasks**
- **Transfer across task**
- **Accumulated knowledge**
- **Better sample efficiency**
- **Learning-to-learn over time**

Foundations

Thrun, Sebastian, and Tom M. Mitchell. "Lifelong robot learning." *Robotics and autonomous systems* 15.1-2 (1995): 25-46.

knowledge accumulation

Lifelong Robot Learning[1]

Sebastian Thrun[2] and Tom M. Mitchell[3]

[2] University of Bonn, Institut für Informatik III, Römerstr. 164, 53117 Bonn, Germany
[3] School of Computer Science, Carnegie Mellon University, Pittsburgh, PA 15213, USA

Abstract. Learning provides a useful tool for the automatic design of autonomous robots. Recent research on learning robot control has predominantly focussed on learning single tasks that were studied in isolation. If robots encounter a multitude of control learning tasks over their entire lifetime, however, there is an opportunity to transfer knowledge between them. In order to do so, robots may learn the invariants of the individual tasks and environments. This task-independent knowledge can be employed to bias generalization when learning control, which reduces the need for real-world experimentation. We argue that knowledge transfer is essential if robots are to learn control with moderate learning times in complex scenarios. Two approaches to lifelong robot learning which both capture invariant knowledge about the robot and its environments are presented. Both approaches have been evaluated using a HERO-2000 mobile robot. Learning tasks included navigation in unknown indoor environments and a simple find-and-fetch task.

Core Question

How do we build systems that take advantage of learning many tasks to learn them better (needing less training experience)?

Lifelong Learning

Thrun, Sebastian. *Lifelong Learning: A Case Study*. No. CMUCS95208. 1995.

Lifelong Learning: A Case Study

Sebastian Thrun

November 1995

?

Abstract

Machine learning has not yet succeeded in the design of robust learning algorithms that generalize well from very small datasets. In contrast, humans often generalize correctly from only a single training example, even if the number of potentially relevant features is large. To do so, they successfully exploit knowledge acquired in previous learning tasks, to bias subsequent learning.

This paper investigates learning in a lifelong context. Lifelong learning addresses situations where a learner faces a stream of learning tasks. Such scenarios provide the opportunity for synergetic effects that arise if knowledge is transferred across multiple learning tasks. To study the utility of transfer, several approaches to lifelong learning are proposed and evaluated in an object recognition domain. It is shown that all these algorithms generalize consistently more accurately from scarce training data than comparable "single-task" approaches.

Lifelong Learning

Sodhani, Shagun, Sarath Chandar, and Yoshua Bengio. "Toward training recurrent neural networks for lifelong learning." *Neural computation* 32.1 (2020): 1-35.

Towards Training Recurrent Neural Networks for Lifelong Learning

Shagun Sodhani[1*], **Sarath Chandar**[1*], **Yoshua Bengio**[1, 2]
[1]Mila, Université de Montréal, Canada
[2]CIFAR Senior Fellow
*Equal Contribution
Contact: sshagunsodhani@gmail.com, apsarathchandar@gmail.com

Keywords: lifelong learning, catastrophic forgetting, capacity expansion, sequential supervised learning, continual learning, neural networks

Abstract

Catastrophic forgetting and capacity saturation are the central challenges of any parametric lifelong learning system. In this work, we study these challenges in the context of sequential supervised learning with an emphasis on recurrent neural networks. To evaluate the models in the lifelong learning setting, we propose a curriculum-based, simple, and intuitive benchmark where the models are trained on tasks with increasing levels of difficulty. To measure the impact of catastrophic forgetting, the model is tested on all the previous tasks as it completes any task. As a step towards developing *true* lifelong learning systems, we unify *Gradient Episodic Memory* (a catastrophic forgetting alleviation approach) and *Net2Net* (a capacity expansion approach). Both these models are proposed in the context of feedforward networks and we evaluate the feasibility of using them for recurrent networks. Evaluation on the proposed benchmark shows that the unified model is more suitable than the constituent models for lifelong learning setting.

Lifelong Learning

Gururangan, Suchin, et al. "Don’t stop pretraining: Adapt language models to domains and tasks." Proceedings of the 58th annual meeting of the association for computational linguistics. 2020.

Don’t Stop Pretraining: Adapt Language Models to Domains and Tasks

Suchin Gururangan[†] **Ana Marasović**[†◇] **Swabha Swayamdipta**[†]
Kyle Lo[†] **Iz Beltagy**[†] **Doug Downey**[†] **Noah A. Smith**[†◇]

[†]Allen Institute for Artificial Intelligence, Seattle, WA, USA
[◇]Paul G. Allen School of Computer Science & Engineering, University of Washington, Seattle, WA, USA
{suching,anam,[illegible]ah}@allenai.org

Abstract

Language models pretrained on text from a wide variety of sources form the foundation of today’s NLP. In light of the success of these broad-coverage models, we investigate whether it is still helpful to tailor a pretrained model to the domain of a target task. We present a study across four domains (biomedical and computer science publications, news, and reviews) and eight classification tasks, showing that a second phase of pretraining in-domain (*domain-adaptive pretraining*) leads to performance gains, under both high- and low-resource settings. Moreover, adapting to the task’s unlabeled data (*task-adaptive pretraining*) improves performance even after domain-adaptive pretraining. Finally, we show that adapting to a task corpus augmented using simple data selection strategies is an effective alternative, especially when resources for domain-adaptive pretraining might be unavailable. Overall, we consistently find that multi-phase adaptive pretraining offers large gains in task performance.

Lifelong Learning

Gururangan, Suchin, et al. "Don’t stop pretraining: Adapt language models to domains and tasks." Proceedings of the 58th annual meeting of the association for computational linguistics. 2020.




Figure 1: An illustration of data distributions. Task data is comprised of an observable task distribution, usually non-randomly sampled from a wider distribution (light grey ellipsis) within an even larger target domain, which is not necessarily one of the domains included in the original LM pretraining domain – though overlap is possible. We explore the benefits of continued pretraining on data from the task distribution and the domain distribution.

Lifelong Learning

Gururangan, Suchin, et al. "Don't stop pretraining: Adapt language models to domains and tasks." Proceedings of the 58th annual meeting of the association for computational linguistics. 2020.

IMDB review	**REALNEWS article**
"The Shop Around the Corner" is one of the great films from director Ernst Lubitsch. In addition to the talents of James Stewart and Margaret Sullavan, it's filled with a terrific cast of top character actors such as Frank Morgan and Felix Bressart. [...] The makers of "You've Got Mail" claim their film to be a remake, but that's just nothing but a lot of inflated self praise. Anyway, if you have an affection for romantic comedies of the 1940's, you'll find "The Shop Around the Corner" to be nothing short of wonderful. Just as good with repeat viewings.	[...] Three great festive films... The Shop Around the Corner (1940) Delightful Comedy by Ernst Lubitsch stars James Stewart and Margaret Sullavan falling in love at Christmas. Remade as You've Got Mail. [...]
HELPFULNESS review	**REALNEWS article**
Simply the Best! I've owned countless Droids and iPhones, but this one destroys them all. Samsung really nailed it with this one, extremely fast, very pocketable, gorgeous display, exceptional battery life, good audio quality, perfect GPS & WiFi performance, transparent status bar, battery percentage, ability to turn off soft key lights, superb camera for a smartphone and more! [...]	We're living in a world with a new Samsung. [...] more on battery life later [...] Exposure is usually spot on and focusing is very fast. [...] The design, display, camera and performance are all best in class, and the phone feels smaller than it looks. [...]

Table 4: Examples that illustrate how some domains might have overlaps with others, leading to unexpected positive transfer. We highlight expressions in the reviews that are also found in the REALNEWS articles.

Lifelong Learning

Pezeshkpour, Pouya, and Estevam Hruschka. "Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?." arXiv preprint arXiv:2501.17840 (2025).

Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?

Pouya Pezeshkpour
Megagon Labs
pouya@megagon.ai

Estevam Hruschka
Megagon Labs
estevam@megagon.ai

Abstract

Large Language Models (LLMs) have demonstrated remarkable performance on various tasks, yet their ability to extract and internalize deeper insights from domain-specific datasets remains underexplored. In this study, we investigate how continual pre-training can enhance LLMs' capacity for insight learning across three distinct forms: declarative, statistical, and probabilistic insights. Focusing on two critical domains: medicine and finance, we employ LoRA to train LLMs on two existing datasets. To evaluate each insight type, we create benchmarks to measure how well continual pre-training helps models go beyond surface-level knowledge. We also assess the impact of document modification on capturing insights. The results show that, while continual pre-training on original documents has a marginal effect, modifying documents to retain only essential information significantly enhances the insight-learning capabilities of LLMs. We released our dataset and code[1].

Lifelong Learning

Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?

Pouya Pezeshkpour
Megagon Labs
pouya@megagon.ai

Estevam Hruschka
Megagon Labs
estevam@megagon.ai

Pezeshkpour, Pouya, and Estevam Hruschka. "Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?." arXiv preprint arXiv:2501.17840 (2025).




Figure 1: We use domain-specific data, like the Hallmarks of Cancer dataset, to adapt an LLM through continued pre-training with LoRA. Our goal is to assess whether LLMs are capable of effectively capture three types of insights: declarative, statistical, and probabilistic.

Lifelong Learning

Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?

Pouya Pezeshkpour Estevam Hruschka




Figure 2: LLMs performance on insight extraction during continual pre-training. Declarative and statistical insights show slight improvement, while probabilistic insights remain largely unchanged. Increasing model size and using simplified documents significantly enhance performance.

Pezeshkpour, Pouya, and Estevam Hruschka. "Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?." arXiv preprint arXiv:2501.17840 (2025).

Lifelong Learning

Szep, Marton, et al.
"Fine-tuning large language models with limited data: a survey and practical guide."
Transactions of the Association for Computational Linguistics 14 (2026): 341-377.

Fine-tuning Large Language Models with Limited Data: A Survey and Practical Guide

Marton Szep[1,2] **Daniel Rueckert**[1,3,4] **Rüdiger von Eisenhart-Rothe**[2]
Florian Hinterwimmer[1,2]

[1]AI in Healthcare and Medicine, Technical University of Munich (TUM) and TUM University Hospital, Munich, Germany
[2]Department of Orthopaedics and Sports Orthopaedics, TUM University Hospital, Germany
[3]Munich Center for Machine Learning (MCML), Munich, Germany
[4]Department of Computing, Imperial College London, UK

Abstract

Fine-tuning large language models (LLMs) with limited data poses a practical challenge in low-resource languages, specialized domains, and constrained deployment settings. While pre-trained LLMs provide strong foundations, effective adaptation under data scarcity requires focused and efficient fine-tuning techniques. This paper presents a structured and practical survey of recent methods for fine-tuning LLMs in data-scarce scenarios. We systematically review parameter-efficient fine-tuning techniques that lower training and deployment costs, domain and cross-lingual adaptation methods for both encoder and decoder models, and model specialization strategies. We further examine preference alignment approaches that guide model behavior using limited human or synthetic feedback, emphasizing sample and compute efficiency. Throughout, we highlight empirical trade-offs, selection criteria, and best practices for choosing suitable techniques based on task constraints, including model scaling, data scaling, and the mitigation of catastrophic forgetting. The aim is to equip researchers and practitioners with actionable insights for effectively fine-tuning LLMs when data and resources are limited.

Lifelong Learning

Kalajdzievski, Damjan. "Scaling laws for forgetting when fine-tuning large language models." arXiv preprint arXiv:2401.05605 (2024).

Scaling Laws for Forgetting When Fine-Tuning Large Language Models

Damjan Kalajdzievski [1]
Tenyx

Abstract

We study and quantify the problem of forgetting when fine-tuning pre-trained large language models (LLMs) on a downstream task. We find that parameter-efficient fine-tuning (PEFT) strategies, such as Low-Rank Adapters (LoRA), still suffer from catastrophic forgetting. In particular, we identify a strong inverse linear relationship between the fine-tuning performance and the amount of forgetting when fine-tuning LLMs with LoRA. We further obtain precise scaling laws that show forgetting increases as a shifted power law in the number of parameters fine-tuned and the number of update steps. We also examine the impact of forgetting on knowledge, reasoning, and the safety guardrails trained into Llama 2 7B chat. Our study suggests that forgetting cannot be avoided through early stopping or by varying the number of parameters fine-tuned. We believe this opens up an important safety-critical direction for future research to evaluate and develop fine-tuning schemes which mitigate forgetting.

Lifelong Learning

Kalajdzievski, Damjan. "Scaling laws for forgetting when fine-tuning large language models." arXiv preprint arXiv:2401.05605 (2024).




Figure 1. **Generation examples** of the pre-trained model, and a model fine-tuned with LoRA on a dataset of recent news articles (see Section 3.2 for a description of the dataset). These generations exemplify the updated knowledge, forgotten knowledge (ARC dataset (Clark et al., 2018)), and forgotten safety/alignment behavior (AdvBench dataset (Zou et al., 2023)) resulting from fine-tuning.

Lifelong Learning

Kalajdzievski, Damjan. "Scaling laws for forgetting when fine-tuning large language models." arXiv preprint arXiv:2401.05605 (2024).




Figure 1. **Generation examples** of the pre-trained model, and a model fine-tuned with LoRA on a dataset of recent news articles (see Section 3.2 for a description of the dataset). These generations exemplify the updated knowledge, forgotten knowledge (ARC dataset (Clark et al., 2018)), and forgotten safety/alignment behavior (AdvBench dataset (Zou et al., 2023)) resulting from fine-tuning.

Lifelong Learning

Kalajdzievski, Damjan. "Scaling laws for forgetting when fine-tuning large language models." arXiv preprint arXiv:2401.05605 (2024).




Figure 1. **Generation examples** of the pre-trained model, and a model fine-tuned with LoRA on a dataset of recent news articles (see Section 3.2 for a description of the dataset). These generations exemplify the updated knowledge, forgotten knowledge (ARC dataset (Clark et al., 2018)), and forgotten safety/alignment behavior (AdvBench dataset (Zou et al., 2023)) resulting from fine-tuning.

Never-Ending Learning

Never-ending learning research question:

Can an agent run indefinitely, acquire many kinds of knowledge, and become a better learner over time?

Key Ideas

- **Coupled Training of many interrelated learning tasks**
- **Discover New Coupling Constraints**
- **Automatically Learn to Extend the Set of Learning Tasks**
- **Growing Competence with Time**

Achieving pro-active, autonomous, cumulative, and persistent Post-Deployment Self-Improving AI agents

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell, T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning

Andrew Carlson[1], Justin Betteridge[1], Bryan Kisiel[1], Burr Settles[1], Estevam R. Hruschka Jr.[2], and Tom M. Mitchell[1]

[1]School of , USA

Abstract

We consider here the problem of building a never-ending language learner; that is, an intelligent computer agent that runs forever and that each day must (1) extract, or read, information from the web to populate a growing structured knowledge base, and (2) learn to perform this task better than on the previous day. In particular, we propose an approach and a set of design principles for such an agent, describe a partial implementation of such a system that has already learned to extract a knowledge base containing over 242,000 beliefs with an estimated precision of 74% after running for 67 days, and discuss lessons learned from this preliminary attempt to build a never-ending learning agent.

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell, T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning





Figure 1: Our Never-Ending Language Learner (NELL) architecture. See "Approach" for an overview of the approach implemented in NELL, and "Implementation" for subsystem details.

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell, T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning




Key Idea 1: Coupled training of many functions

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell, T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning




Key Idea 2: Discover New Coupling Constraints – Perform Inference

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell, T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning




Key Idea 3: Automatically Learn to Extend the Set of Learning Tasks

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell, T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning



Key Idea 4: Cumulative, Staged Learning
Learning X improves ability to learn Y

Never-Ending Learning

From one learning problem to a coupled, evolving set

$$\text{Never-ending Learning} = (L, C)$$

$L = \{ (T_i, P_i, E_i) \}$ C = coupling constraints among solutions

Representation is Key

"What is the right representation that allows Post-Deployment Self-Evolving Agentic AI Systems without imposing constraints on confidence and controllability, and also not imposing constraints on what to learn next to improve the overall performance?"

The shared intuition

> Learning should not be a one-time event

Instead, intelligent systems should:

- **Learn from experience**
- **Reuse prior knowledge**
- **Adapt to new tasks**
- **Avoid forgetting**
- **Improve learning process**

Continual Learning

Continual learning research question:

Can a model learn new tasks without catastrophically forgetting old ones?

Key Ideas

- **Stability vs. Plasticity**
- **Incremental Learning**
- **Catastrophic Forgetting**
- **Modularity & Replay**
- **Transfer Learning**

Continual Learning Literature tends to consider ideas from both Lifelong and Never-Ending Learning

Continual Learning

Wang, Liyuan, et al. "A comprehensive survey of continual learning: Theory, method and application." IEEE transactions on pattern analysis and machine intelligence 46.8 (2024).




Fig. 3. A state-of-the-art and elaborated taxonomy of representative continual learning methods. We have summarized five main categories (
blocks), each of which is further divided into several sub-directions (red blocks).

Continual Learning

Continual learning asks:

Shi, Haizhou, et al. "Continual learning of large language models: A comprehensive survey." *ACM Computing Surveys*58.5 (2025): 1-42.




Fig. 1. A high-level overview of the modern pipeline for continually pre-training and fine-tuning LLMs, where two dimensions of continuity are described. **Vertical Continuity (or Vertical CL):** LLM training can be vertically divided into three stages: (i) CPT, (ii) DAP, and (iii) CFT. The main focus is the retention of the LLM's general knowledge (prevention of vertical forgetting). **Horizontal Continuity (or Horizontal CL):** After the LLMs are deployed, the models are continually updated when a new set of data becomes available. The primary goal is to prevent horizontal forgetting in a long sequence of tasks.

LLM agents are not automatically Post-Deployment Self-Improving

Many agents are adaptive, but not necessarily Post-Deployment Self-Improving

Post-Deployment Self-Improving requires:

persistent update targets + validation + governance + measurable self-improvement over time

Lou, X., Lázaro-Gredilla, M., Dedieu, A., Wendelken, C., Lehrach, W., & Murphy, K. P. (2026). AutoHarness: improving LLM agents by automatically synthesizing a code harness. *arXiv preprint arXiv:2603.03329*.

AutoHarness: improving LLM agents by automatically synthesizing a code harness

Xinghua Lou, Miguel Lázaro-Gredilla, Antoine Dedieu,
Carter Wendelken, Wolfgang Lehrach, Kevin P. Murphy
Google DeepMind
{xinghua,lazarogredilla,adedieu,cwendelken,wpl,kpmurphy}@deepmind.com

March 5, 2026

Abstract

Despite significant strides in language models in the last few years, when used as agents, such models often try to perform actions that are not just suboptimal for a given state, but are strictly prohibited by the external environment. For example, in the recent Kaggle GameArena chess competition, 78% of Gemini-2.5-Flash losses were attributed to illegal moves. Often people manually write "harnesses" around LLMs to prevent such failures. In this paper, we demonstrate that Gemini-2.5-Flash can automatically synthesize such a code harness, using a small number of rounds of iterative code refinement given feedback from the (game) environment. The resulting harness prevents all illegal moves in 145 different TextArena games (both 1-player and 2-player), enabling the smaller Gemini-2.5-Flash model to outperform larger models, such as Gemini-2.5-Pro. Pushing our technique to the limit, we can get Gemini-2.5-Flash to generate the entire policy in code, thus eliminating the need to use the LLM at decision making time. The resulting code-policy receives a higher average reward than Gemini-2.5-Pro and GPT-5.2-High on 16 TextArena 1-player games. Our results show that using a smaller model to synthesize a custom code harness (or entire policy) can outperform a much larger model, while also being more cost effective.

LLM agents a

Lou, X., Lázaro-Gredilla, M., Dedieu, A., Wendelken, C., Lehrach, W., & Murphy, K. P. (2026). AutoHarness: improving LLM agents by automatically synthesizing a code harness. *arXiv preprint arXiv:2603.03329*.

AutoHarness: improving LLM agents by automatically synthesizing a code harness

Xinghua Lou, Miguel Lázaro-Gredilla, Antoine Dedieu,
Carter Wendelken, Wolfgang Lehrach, Kevin P. Murphy
Google DeepMind
{xinghua,lazarogredilla,adedieu,cwendelken,wpl,kpmurphy}@deepmind.com

March 5, 2026

An agent is often defined as the combination of a specific LLM and a harness that acts as the "glue" or "plumbing" between the model and the task that needs to be solved. In this work, we propose "code as harness", a framework where the LLM itself completes the agent by coding its own harness. In its simplest incarnation, the harness can be seen as a control loop that calls the LLM and rejects unacceptable answers. The definition of what is acceptable is itself learned. This essentially results in a rejection sampler for LLMs in which the conditioning is learned based on the task.

LLM agents a

Lou, X., Lázaro-Gredilla, M., Dedieu, A., Wendelken, C., Lehrach, W., & Murphy, K. P. (2026). AutoHarness: improving LLM agents by automatically synthesizing a code harness. *arXiv preprint arXiv:2603.03329*.

AutoHarness: improving LLM agents by automatically synthesizing a code harness

Xinghua Lou, Miguel Lázaro-Gredilla, Antoine Dedieu,
Carter Wendelken, Wolfgang Lehrach, Kevin P. Murphy
Google DeepMind
{xinghua,lazarogredilla,adedieu,cwendelken,wpl,kpmurphy}@deepmind.com

March 5, 2026

5 Conclusion and Future Work

We developed a novel approach for improving the performance of an LLM agent, based on automatically synthesizing a code harness. Currently we generate a separate harness for each environment (game). In the future, we would like to distill the resulting domain specific experts (agents) back into the base LLM, so that the whole system becomes recursively self-improving. We also hope to explore building up a library of reusable harnesses, and to apply our method to more challenging multimodal games, such as Craftax [4] and Terra Nova [5].

Learning through weights and recursive self-improvement (RSI)

Parameter adaptation and RSI are important complementary techniques, but neither is synonymous with PDSI. Suggested further readings:

- Zweiger et al. (2025), Self-Adapting Language Models (SEAL) — Self-generated update directives and lasting weight adaptation; NeurIPS 2025.
- Zhao et al. (2025), Absolute Zero: Reinforced Self-play Reasoning with Zero Data — Self-proposed/verifiable training curricula; NeurIPS 2025, primarily a training paradigm, not automatically PDSI.
- Yin et al. (2025), Gödel Agent — Agent-side self-modification, self-referential design; ACL 2025.
- Zhang et al. (2025), Darwin Gödel Machine: Open-Ended Evolution of Self-Improving Agents — Empirically validated changes to an agent's own code, with archives of variants; relevant to RSI regardless of deployment timing.
- Shi et al. (2026), PluginRSI: Recursive Improvement of Agent Harnesses with Reusable Plugins — Evolves modular reusable agent-harness components (preprint).
- Ren et al. (2026), Self-Improvements in Modern Agentic Systems: A Survey — Contemporary model- vs scaffold-modification taxonomy; excellent secondary resource.

Takeaways

NELL: Long-horizon learning vision.

Lifelong Learning: Transfer across experience.

Continual Learning: Stability under updates.

LLM Agents: Harness, Interaction, tools, and memory.

PART III · 35 MINUTES

What a self-improving language agent learns

What should change after deployment, where should the change live, which signals justify it — and when should the agent create a new learning problem?

Learning: task, performance, experience

> “A computer program is said to learn from experience **E** with respect to some class of tasks **T** and performance measure **P**, if its performance at tasks in T, as measured by P, improves with experience E.”
> Mitchell, *Machine Learning*, 1997

Example for this Tutorial:

Task:

Extract a set of relations from documents

Performance:

Relation-level precision and recall

Experience:

Documents, corrections, feedback

Time-stamp and persistent state

$$(y_t, h_t) = \text{Execute}(S_t, x_t, z_t)$$

S_t persistent state available before time-stamp t

x_t, z_t the task input, and the environment including external tools

y_t, h_t output and trace; the trace may support an update

A Post-Deployment Self-Improving (PDSI) Agent should be able to retrieve an instance of the task from memory (persistence) and also solve new tasks (learning/generalization)

The update mechanism

$$S_{t+1} = U(S_t, E_t)$$

The update procedure **U** may **propose**, **reject** or **commit** a change, or confirm current knowledge (no change). Its inputs: traces, external corrections, earlier state.

Persistence is not permanence (a memory can expire and still matter). Influence can be second-order: a revised test changes future learning decisions, not today’s answers.

Important Elements

Learning mechanism: The procedure. It remains a learning algorithm even when a particular run fails.

Demonstrated improvement: An empirically supported outcome on declared targets.

Candidate learning update: An experience-driven proposed change (which may be harmful).

Adaptation: Behaviour changes in response to circumstances (transient or retained).

Self-Refine: revises an output within one interaction (adaptation without retention in Madaan et al., 2023)

Reflexion: retains verbal feedback for later trials (a different retention boundary in Shinn et al., 2023)

Important Elements: Self-Refine

Madaan, Aman, et al. "Self-refine: Iterative refinement with self-feedback." *Advances in neural information processing systems* 36 (2023): 46534-46594.

SELF-REFINE: Iterative Refinement with Self-Feedback

Aman Madaan[1], **Niket Tandon**[2], **Prakhar Gupta**[1], **Skyler Hallinan**[3], **Luyu Gao**[1], **Sarah Wiegreffe**[2], **Uri Alon**[1*], **Nouha Dziri**[2], **Shrimai Prabhumoye**[4], **Yiming Yang**[1], **Shashank Gupta**[2], **Bodhisattwa Prasad Majumder**[5], **Katherine Hermann**[6], **Sean Welleck**[2,3], **Amir Yazdanbakhsh**[6], **Peter Clark**[2]
[1]Language Technologies Institute, Carnegie Mellon University
[2]Allen Institute for Artificial Intelligence
[3]University of Washington [4]NVIDIA [5]UC San Diego [6]Google Deepmind
selfrefine@googlegroups.com

Abstract

Like humans, large language models (LLMs) do not always generate the best output on their first try. Motivated by how humans refine their written text, we introduce SELF-REFINE, an approach for improving initial outputs from LLMs through iterative feedback and refinement. The main idea is to generate an initial output using an LLM; then, the same LLM provides *feedback* for its output and uses it to *refine* itself, iteratively. SELF-REFINE does not require any supervised training data, additional training, or reinforcement learning, and instead uses a single LLM as the generator, refiner, and feedback provider. We evaluate SELF-REFINE across 7 diverse tasks, ranging from dialog response generation to mathematical reasoning, using state-of-the-art (GPT-3.5 and GPT-4) LLMs. Across all evaluated tasks, outputs generated with SELF-REFINE are preferred by humans and automatic metrics over those generated with the same LLM using conventional one-step generation, improving by ~20% absolute on average in task performance. Our work demonstrates that even state-of-the-art LLMs like GPT-4 can be further improved at test-time using our simple, standalone approach.[2].

Important Elements: Self-Refine

Madaan, Aman, et al. "Self-refine: Iterative refinement with self-feedback." *Advances in neural information processing systems* 36 (2023): 46534-46594.




Figure 1: Given an input (⓪), SELF-REFINE starts by generating an output and passing it back to the same model $\mathcal{M}$ to get feedback (①). The feedback is passed back to $\mathcal{M}$, which refines the previously generated output (②). Steps (①) and (②) iterate until a stopping condition is met. SELF-REFINE is instantiated with a language model such as GPT-3.5 and does not involve human assistance.

Important Elements: Self-Refine

Madaan, Aman, et al. "Self-refine: Iterative refinement with self-feedback." *Advances in neural information processing systems* 36 (2023): 46534-46594.




Figure 2: Examples of SELF-REFINE: an initial output generated by the base LLM and then passed back to the *same* LLM to receive feedback to the *same* LLM to refine the output . The top row illustrates this for dialog generation where an initial dialogue response can be transformed into a more engaging one that also understands the user by applying feedback. The bottom row illustrates this for code optimization where the code is made more efficient by applying feedback.

Important Elements: Reflexion

Shinn, Noah, et al. "Reflexion: Language agents with verbal reinforcement learning." *Advances in neural information processing systems* 36 (2023): 8634-8652.

Reflexion: Language Agents with Verbal Reinforcement Learning

Noah Shinn
Northeastern University
noahshinn024@gmail.com

Federico Cassano
Northeastern University
cassano.f@northeastern.edu

Ashwin Gopinath
MIT
agopi@mit.edu

Karthik Narasimhan
Princeton University
karthikn@princeton.edu

Shunyu Yao
Princeton University
shunyuy@princeton.edu

Abstract

Large language models (LLMs) have been increasingly used to interact with external environments (e.g., games, compilers, APIs) as goal-driven agents. However, it remains challenging for these language agents to quickly and efficiently learn from trial-and-error as traditional reinforcement learning methods require extensive training samples and expensive model fine-tuning. We propose *Reflexion*, a novel framework to reinforce language agents not by updating weights, but instead through linguistic feedback. Concretely, Reflexion agents verbally reflect on task feedback signals, then maintain their own reflective text in an episodic memory buffer to induce better decision-making in subsequent trials. Reflexion is flexible enough to incorporate various types (scalar values or free-form language) and sources (external or internally simulated) of feedback signals, and obtains significant improvements over a baseline agent across diverse tasks (sequential decision-making, coding, language reasoning). For example, Reflexion achieves a 91% pass@1 accuracy on the HumanEval coding benchmark, surpassing the previous state-of-the-art GPT-4 that achieves 80%. We also conduct ablation and analysis studies using different feedback signals, feedback incorporation methods, and agent types, and provide insights into how they affect performance. We release all code, demos, and datasets at https://github.com/noahshinn024/reflexion.

Important Elements: Reflexion

Shinn, Noah, et al. "Reflexion: Language agents with verbal reinforcement learning." *Advances in neural information processing systems* 36 (2023): 8634-8652.





Figure 1: Reflexion works on decision-making 4.1, programming 4.3, and reasoning 4.2 tasks.

Important Elements: Reflexion

Shinn, Noah, et al. "Reflexion: Language agents with verbal reinforcement learning." *Advances in neural information processing systems* 36 (2023): 8634-8652.



Algorithm 1 Reinforcement via self-reflection

Initialize Actor, Evaluator, Self-Reflection: M_a, M_e, M_{sr}
Initialize policy $\pi_\theta(a_i|s_i), \theta = \{M_a, mem\}$
Generate initial trajectory using π_θ
Evaluate τ_0 using M_e
Generate initial self-reflection sr_0 using M_{sr}
Set $mem \leftarrow [sr_0]$
Set $t = 0$
while M_e not pass or $t <$ max trials **do**
    Generate $\tau_t = [a_0, o_0, \ldots a_i, o_i]$ using π_θ
    Evaluate τ_t using M_e
    Generate self-reflection sr_t using M_{sr}
    Append sr_t to mem
    Increment t
end while
return

Figure 2: (a) Diagram of Reflexion. (b) Reflexion reinforcement algorithm

Improvement is multidimensional and constrained

Measures that need not move together

Recall · precision · calibration · provenance completeness · latency · correction burden.

Accept everything: recall rises. Abstain on everything hard: precision rises.

Preservation counts

If terminology shifts, holding performance steady while a frozen baseline deteriorates is a real benefit.

Knowledge Lifecycle

When a deployed system acquires new knowledge:

- Should it remain in context or episodic memory?
- Should it become explicit in a KG/KB?
- Should it be incorporated in the Harness (tools, skills, external data, etc)
- Should it eventually be internalized in model parameters?
- How should knowledge move between representations?

Things a deployed agent can learn

Knowledge: Facts, identities, relations, constraints with scope and provenance

Memory: Episodic traces and semantic summaries of experience

Skills: Tool-use procedures, workflows, decomposition strategies

Policies: When to retrieve, ask, abstain, escalate or propose an update

Self-monitoring: Uncertainty, failure prediction, anomaly detection, diagnosis

Learning problems: New tasks, their specifications and their couplings

The categories overlap

Every learned piece of knowledge should carry its status

Learned knowledge	New fact, skill, parameters, etc.
Evidence span	The exact elements supporting the new knowledge
Source and time	Document ID, model ID, skill ID, publication time, acquisition time
Scope	Domain, model version, temporal qualifiers
Epistemic status	candidate · accepted · disputed · derived · retired

Memory systems make different design choices

Episodic — particular events with their context

Semantic — generalizations across events

System	Central mechanism	Reference
MemGPT	Moves information between context and external storage	Packer et al., 2023
A-MEM	Linked notes whose organization evolves	Xu et al., 2025
Mem0	Extraction, consolidation and retrieval of salient facts	Chhikara et al., 2025
MemInsight	Autonomous augmentation of memory representations	Salama et al., 2025
EP+SEM_CRIT	Episodic plus Semantic memory	Hassle et al., 2026
LLM-as-RNN	a frozen LLM keeps its state as natural-language memory	Lu et al., AACL2026
AutoMEM	a harness where the agent manages its own text-file memory	Chen et al., AACL2026

A memory is a typed, scoped object. It should not be just a stored chat history

Each memory should record

- what happened, and in which task
- who or what produced it
- local or global scope
- whether it may affect future answers
- evidence links and confidence
- when it expires

Typing makes memory **queryable and governable**: a RejectedClaim must never be retrieved as support; a UserPreference must not leak across users.

Skills: reusable procedures for a class of outcomes

Toolformer: Self-supervised data construction and filtering teach a model when to call APIs. Schick et al., 2023

Voyager: Stores executable skills in a library for later reuse. Wang et al., 2023

SkillWeaver: Web agents self-improve by discovering and honing skills. Zheng et al., 2025

Policies: when to retrieve, ask, abstain or update

Policy improvement depends on costs and consequences.

Always asking an expert breaks a review budget. Always abstaining destroys coverage. Evaluate routing by the **complete target outcome**: latency, review effort, routing errors.

Policies change the future data stream. If an Agent only reviews cases it already suspects, it may never discover a confidently wrong region.

Step-level refinement — learning from process-level feedback · Xiong et al., 2024
RAGEN — self-evolution via multi-turn RL · Wang et al., 2025
MemRL — learned utility of episodic memories, LM fixed · Zhang et al., 2026

Learning when not to trust yourself

SelfCheckGPT — zero-resource, black-box hallucination detection · Manakul et al., 2023

Uncertainty-aware language agents · Han et al., 2024

Uncertainty propagation across agent steps · Zhao et al., 2025

Confidence Reasoning Graphs - King et al., 2026

A confident explanation of an error is not evidence that the diagnosis is correct. Monitoring is itself a learnable task with its own failure modes.

Where learning signals come from

User feedback: Corrections, ratings, preferences — selected, not representative

Retrieval evidence: Documents that support or contradict an output

Tool traces: Errors, timeouts, schema mismatches, outputs

Environment: Observed outcomes of the agent's actions

Offline eval logs: Regression suites, audits, judge verdicts

The system's own knowledge can label data too

Ratner et al., 2017 (Snorkel)

Training on self-produced data can be biased Shumailov et al., 2024

Signals coming from the same source should not double-counted

Manage tasks as a portfolio: create, merge, retire

Proliferation: Each task adds labels, tests, storage, inference cost and dependencies. Judge marginal target value against maintenance cost.
Merging: Compare inputs, outputs, error patterns and downstream uses. Renaming two tasks into one does not make their labels compatible.
Retirement: Unhelpful, obsolete, absorbed, or its domain is gone. Retiring the learner need not delete its evidence.

Task registry keeps rationale, versions and rejected tasks with the conditions of rejection.

Self-improvement is a portfolio of update targets, each with its own substrate, signals and evidence.

A new learning task is a resource-consuming hypothesis. It earns its place through target benefit, not novelty, autonomy or auxiliary accuracy.

After the break · Part IV — design patterns that make this loop safe.

Coffee break · 30 minutes

A question to discuss over coffee: in a system you know, what changes after deployment today, and who decides whether that change was an improvement?


Next · Part IV — Case Studies

PART IV · 40 MINUTES

Case studies

What does the never-ending perspective change for a simple NLP task — and how do current systems realize it?

Karpathy's LLM Wiki: continuously growing a KB for QA



Human: curates sources, explores, asks questions

LLM: summarizing, cross-linking, filing and logging, the bookkeeping

Figure generated with help from Claude Code

Karpathy's LLM Wiki: continuously growing a KB for QA

- Instead of retrieving raw chunks at every question, an LLM agent incrementally builds and maintains a KB (wiki) of interlinked markdown pages that sits between the user and the sources.
- The memory is structured as a wiki (md files), which can be handled by coding agents. It becomes "a persistent, compounding artifact."
- The human curates sources, explores and asks questions. The LLM does the bookkeeping: summarizing, cross-linking, filing and logging.
- The wiki is learned state that lives outside the model weights, and it stays human-readable, versioned and reversible.

Source: A. Karpathy, "LLM Wiki", GitHub gist, April 2026 (gist.github.com/karpathy/442a6bf555914893e9891c11519de94f).

Karpathy's LLM Wiki: continuously growing a KB for QA


KB Representation

3 · SCHEMA

`CLAUDE.md / AGENTS.md`

structure · page conventions · ingest, query and lint workflows
co-evolved by the human and the LLM

2 · WIKI LLM-owned markdown pages, cross-linked



links connect pages; Obsidian's graph view shows hubs and orphans

`index.md`
catalog: link + one-line summary per page; read first on every query

`log.md`
append-only record of ingests, queries and lint passes

1 · RAW SOURCES

articles · papers · images · data files

immutable: the LLM reads them but never edits them

Example layout

illustrative: the gist prescribes none

```
my-wiki/  (git repo)
├─ CLAUDE.md
├─ raw/
│  ├─ articles/
│  ├─ papers/
│  └─ assets/
└─ wiki/
   ├─ index.md
   ├─ log.md
   ├─ overview.md
   ├─ concepts/
   ├─ entities/
   ├─ sources/
   └─ analyses/
```

Git: every edit is a diff that can be reviewed or reverted


Obsidian: browse pages, backlinks and the link graph

Figure generated with help from Claude Code

Karpathy's LLM Wiki: continuously growing a KB for QA


KB Representation

Source: https://obsidian.md/help/plugins/graph



Karpathy's LLM Wiki: continuously growing a KB for QA

The QA Task



At scale: index-only navigation works for roughly 100 sources and hundreds of pages.
Beyond that, add search, e.g. qmd: hybrid BM25 + vector retrieval with LLM re-ranking.

Figure generated with help from Claude Code

Source: A. Karpathy, "LLM Wiki", GitHub gist, April 2026 (gist.github.com/karpathy/442a6bf555914893e9891c11519de94f).

Karpathy's LLM Wiki: continuously growing a KB for QA

The QA Task

- The agent reads index.md first, opens the pages that look relevant, follows their links, and writes an answer that cites the pages it used.
- The output can be a markdown page, a comparison table, a Marp slide deck or a chart.
- "Good" answers, such as comparisons or newly found connections, are filed back as new pages instead of being lost in the chat. Every query is also appended to log.md.
- The index alone suffices for about 100 sources and hundreds of pages. Beyond that, add a search tool such as qmd (hybrid BM25 and vector search with LLM re-ranking).
- The costly synthesis moves from query time (in RAG) to ingest time, and answers read the wiki rather than the raw sources.

Source: A. Karpathy, "LLM Wiki", GitHub gist, April 2026 (gist.github.com/karpathy/442a6bf555914893e9891c11519de94f).

Karpathy's LLM Wiki: continuously growing a KB for QA

A similar approach for skills

Tang, Liyan, et al. "WikiSkill: Compiling agent experience into persistent knowledge for skill evolution." *arXiv preprint arXiv:2608.27454* (2026).

Google Research

2026-08-28

WikiSkill: Compiling Agent Experience into Persistent Knowledge for Skill Evolution

Liyan Tang[1], Cyrus Rashtchian[1], Chun-Sung Ferng[1], Andrew Tomkins[1], Da-Cheng Juan[1] and Tu Vu[1,2]
[1]Google Research, [2]Virginia Tech

Agent skills **package specialized knowledge and workflows into reusable resources that extend AI agent capabilities. Recent work automatically discovers such skills from agent experience, which enables agents to progressively adapt through interaction. However, the insights that guide skill development typically remain scattered across optimization histories, limiting their systematic reuse across iterations. We introduce WikiSkill, a framework that co-evolves agent skills with a *persistent* knowledge base (wiki). At a high level, WikiSkill separates raw execution experience, accumulated knowledge, and executable skills, while continuously consolidating experience into the wiki, which subsequent skill updates can build on. Across diverse benchmarks and models, WikiSkill consistently outperforms *state-of-the-art* skill-evolution methods and improves over no-skill baselines in most model-benchmark settings. We find that skill evolution complements model scaling: larger models generally benefit more from evolved skills, while smaller models with skills can outperform substantially larger models without them. We also find that evolved skills transfer effectively across models and model families, and skills evolved by other models can outperform self-evolved skills. Finally, our ablation studies confirm that persistent knowledge accumulation in the wiki is critical for effective skill evolution. These results demonstrate the benefits of systematically accumulating and refining agent experience for developing reusable and transferable skills.**

Karpathy's LLM Wiki: continuously growing a KB for QA

A similar approach for skills

Tang, Liyan, et al. "WikiSkill: Compiling agent experience into persistent knowledge for skill evolution." *arXiv preprint arXiv:2608.27454* (2026).




Figure 1 | **WikiSkill consistently improves over both the no-skill baseline and existing skill-evolution methods.** Interestingly, its advantage becomes more pronounced for stronger models. We report average accuracy across the evaluated benchmarks for each model using no skills or skills evolved by EvoSkill, SkillOpt, and WikiSkill (see Table 1 for details).

Karpathy's LLM Wiki: continuously growing a KB for QA

A similar approach for skills

Tang, Liyan, et al. "WikiSkill: Compiling agent experience into persistent knowledge for skill evolution." *arXiv preprint arXiv:2608.27454* (2026).

- Raw sources are execution traces. The raw layer holds immutable execution traces from training rollouts.
- The wiki is very similar and contains what worked and what failed. But, for skills.
- Skill Proposer: It reads the index and the impact file, inspects traces as needed, and produces one atomic proposal per iteration (a new skill or a patch to an existing one).
- The outcome in the wiki are executable skills. Instead of answers, the third layer is skills. Each has a SKILL.md and a PURPOSE.md that links to the wiki patterns that motivated it.

DySECT

Amin-Naseri, M., Kim, H., & Hruschka, E. (2026). A Dynamic Self-Evolving Extraction System. *ACL2026 (Demo).*




Figure 1: Overview of our closed-loop extraction and knowledge base system. The extractor produces triples from raw text, which populate the KB and are then fed back to improve future extraction.

A Dynamic Self-Evolving Extraction System

Moin Amin-Naseri
Megagon Labs
moin@megagon.ai

Hannah Kim
Megagon Labs
hannah@megagon.ai

Estevam Hruschka
Megagon Labs
estevam@megagon.ai

Abstract

The extraction of structured information from raw text is a fundamental component of many NLP applications, including document retrieval, ranking, and relevance estimation. High-quality extractions often require domain-specific accuracy, up-to-date understanding of specialized taxonomies, and the ability to incorporate emerging jargon and rare outliers. In many domains–such as medical, legal, and HR–the extraction model must also adapt to shifting terminology and benefit from explicit reasoning over structured knowledge. We propose DySECT, a Dynamic Self-Evolving Extraction and Curation Toolkit, which continually improves as it is used. The system incrementally populates a versatile, self-expanding knowledge base (KB) with triples extracted by the LLM. The KB further enriches itself through the integration of probabilistic knowledge and graph-based reasoning, gradually accumulating domain concepts and relationships. The enriched KB then feeds back into the LLM extractor via prompt tuning, sampling of relevant few-shot examples, or fine-tuning using KB-derived synthetic data. As a result, the system forms a symbiotic closed-loop cycle in which extraction continuously improves knowledge, and knowledge continuously improves extraction[1].

named entities, relations, and events across diverse formats (Xu et al., 2024; Zhang et al., 2025). At the same time, domain-specific case studies, for example in scientific and clinical text, show that high-quality extraction still requires careful schema design, substantial domain adaptation, and rigorous evaluation (Dagdelen et al., 2024; Adam, 2025). Taken together, these lines of work suggest that both classic neural IE systems and newer LLM-based approaches remain heavily dependent on curated datasets and manually engineered adaptation strategies.

Despite progress in label-efficient and continual learning methods, updating IE systems in response to new data remains cumbersome. Self-training and bootstrapping approaches reduce annotation costs but typically rely on manually designed seed rules, confidence thresholds, and offline retraining cycles (Angeli et al., 2015; Sarkhel et al., 2023). Domain-adaptive continual learning for LLMs aims to incrementally absorb new domain data without catastrophic forgetting, yet it generally assumes explicit training phases, access to model weights, and non-trivial engineering to maintain stability (Rostami, 2024; Kharrat et al., 2024). Frameworks that combine ontologies or knowledge bases with language models can

DySECT: extraction and the knowledge base improve each other

Amin-Naseri, M., Kim, H., & Hruschka, E. (2026). A Dynamic Self-Evolving Extraction System. *ACL2026 (Demo).*

- Traditional LLM extractors handle each document in isolation and lose what earlier extractions found. That hurts in domains such as HR, legal and medical, where terminology shifts, taxonomies evolve and rare concepts matter.
- In Dysect, very extraction call inserts triples into a self-evolving knowledge base with probabilistic confidence. The KB enriches itself and feeds back into the extractor.
- The system improves through use with no retraining cycle, nor curated adaptation data or access to model weights.
- The loop can run on its own, but an interactive KB interface lets curators inspect, validate or correct what it has learned.

DySECT: extraction and the knowledge base improve each other

Amin-Naseri, M., Kim, H., & Hruschka, E. (2026). A Dynamic Self-Evolving Extraction System. *ACL2026 (Demo).*




Figure generated with help from Claude Code

DySECT: extraction and the knowledge base improve each other

Amin-Naseri, M., Kim, H., & Hruschka, E. (2026). A Dynamic Self-Evolving Extraction System. *ACL2026 (Demo).*

- Each fact is a (subject, relation, object) triple with typed arguments; inverse relations are added automatically. The KB is built on Theo (Mitchell et al., 1989).
- Local confidences c_i from extractors and acquisition LLMs, a frequency f_i of repeated observations, and the source label of each batch.
- Repeated support combines as $C_agg = 1 - \Pi(1 - \lambda c_i)^{f_i}$, with $\lambda = 0.75$ by default. Each mutually exclusive rival divides it: $C = C_agg / (m + 1)$. Curator decisions are fully trusted ($C = 1.0$).
- Generalization and specialization links, LLM-labelled cluster nodes under broad concepts, and automatically detected mutually exclusive concept families, such as sports versus religious organizations.

DySECT: extraction and the knowledge base improve each other

- The outer loop ingests each batch of extractor output with a source label. An inner loop then runs a few rounds of knowledge integration, concept acquisition and relation acquisition; proposed items enter as candidates with an initial confidence.
- High-confidence subconcepts and representative relations go into the prompt as positive examples, so the extractor finds more facts like them.
- Saturated subconcepts are marked as already extracted, steering the extractor toward relations it has not yet covered.
- Few-shot examples sampled from the KB, or fine-tuning on text generated from high-confidence triples. Neither was used in the reported experiments.
- Through the interface they validate, invalidate or add triples, and track sources and confidence across iterations.




Figure generated with help from Claude Code

STEP 4 · TWO PROMPT MODES

Encouraging: "look here"

high-confidence subconcepts and representative relations as positive examples

```
Known subconcepts of Music genre:
Rock, Jazz, Blues
Example: (Band A, genre, Rock)
Extract more facts like these.
```

illustrative prompt snippet

Prohibitive: "stop repeating"

saturated subconcepts marked as already extracted, to reach unexplored relations

```
Already extracted (skip):
Rock, Jazz, Blues
Look for relations and concepts
not covered above.
```


illustrative prompt snippet

Also supported: few-shot examples sampled from the KB; fine-tuning on text generated from high-confidence triples (not used in the experiments)


DySECT: extraction and the knowledge base improve each other

Evaluation

- DocRED (96 relation types): 500 fixed documents, a KB initialized from 100 other documents, four extractors, measuring recall and the number of extracted triples. Prompt feedback only: no fine-tuning or synthetic data.
- One round of KB feedback raised recall for every model: +5.6 to +7.8 points in encouraging mode, +4.5 to +5.9 in prohibitive mode. After two rounds GPT-4.1 went from 22.8 to 37.0 (chart). Encouraging mode was more stable; prohibitive mode explored more but added noisier extractions.




DySECT: extraction and the knowledge base improve each other




Concept	File	Is Rel?	Uniq.All	Uniq.H	Uniq.R	Uniq.T	Cnt.All	Cnt.H	Cnt.R	Cnt.T	First Iter	Last Iter
0	0/0.json	☐	8	4	0	4	16	8	0	8	1	5
1	1/1.json	☐	10	5	0	5	16	8	0	8	1	5
10	1/0/10.json	☐	6	3	0	3	8	4	0	4	2	4
100	1/0/0/100.json	☐	8	4	0	4	16	8	0	8	1	5
1000	1/0/0/0/1000.json	☐	6	3	0	3	12	6	0	6	1	5
105	1/0/5/105.json	☐	4	2	0	2	4	2	0	2	5	5
10_december_1815	1/0/_/d/e/10_december_1815.json	☐	4	2	0	2	8	4	0	4	1	2
10_january_1971	1/0/_/j/a/10_january_1971.json	☐	4	2	0	2	16	8	0	8	1	5
10_january_2016	1/0/_/j/a/10_january_2016.json	☐	4	2	0	2	20	10	0	10	1	5
10_september_1865	1/0/_/s/e/10_september_1865.json	☐	4	2	0	2	4	2	0	2	0	0


DySECT: extraction and the knowledge base improve each other




DySECT: extraction and the knowledge base improve each other



DySECT: extraction and the knowledge base improve each other



DySECT: extraction and the knowledge base improve each other



Meta-Harness: optimize the harness, keep the model fixed

Meta-Harness: End-to-End Optimization of Model Harnesses

Yoonho Lee
Stanford

Roshen Nair
Stanford

Qizheng Zhang
Stanford

Kangwook Lee
KRAFTON

Omar Khattab
MIT

Chelsea Finn
Stanford

Pr
Optimized h

Harnes

-artifact

mance

Abstract

The performance of large language model (LLM) systems depends not only on model weights, but also on their *harness*: the code that determines what information to store, retrieve, and present to the model. Yet harnesses are still designed largely by hand, and existing text optimizers are poorly matched to this setting because they compress feedback too aggressively: they are memoryless, condition only on scalar scores, or restrict feedback to short templates or summaries. We introduce **Meta-Harness**, an outer-loop system that searches over harness code for LLM applications. It uses an agentic proposer that accesses the source code, scores, and execution traces of all prior candidates through a filesystem. On online text classification, Meta-Harness improves over a state-of-the-art context management system by 7.7 points while using 4× fewer context tokens. On retrieval-augmented math reasoning, a single discovered harness improves accuracy on 200 IMO-level problems by 4.7 points on average across five held-out models. On agentic coding, discovered harnesses surpass the best hand-engineered baselines on TerminalBench-2. Together, these results show that richer access to prior experience can enable automated harness engineering.

Lee, Y., Nair, R., Zhang, Q., Lee, K., Khattab, O., & Finn, C. (2026). Meta-harness: End-to-end optimization of model harnesses. *arXiv preprint arXiv:2603.28052*.

Meta-Harness: optimize the harness, keep the model fixed

Meta-Harness: End-to-End Optimization of Model Harnesses

Yoonho Lee
Stanford

Roshen Nair
Stanford

Qizheng Zhang
Stanford

Kangwook Lee
KRAFTON

Omar Khattab
MIT

Chelsea Finn
Stanford

Lee, Y., Nair, R., Zhang, Q., Lee, K., Khattab, O., & Finn, C. (2026). Meta-harness: End-to-end optimization of model harnesses. *arXiv preprint arXiv:2603.28052*.




Figure 1: **(Left)** On text classification, Meta-Harness outperforms the best prior hand-designed harnesses (ACE) and existing text optimizers (TTT-Discover, OpenEvolve), matching the next-best method's final accuracy after just 4 evaluations. **(Right)** On TerminalBench-2, Meta-Harness outperforms all reported `Claude Haiku 4.5` harnesses.

Meta-Harness: optimize the harness, keep the model fixed

Meta-Harness: End-to-End Optimization of Model Harnesses

Yoonho Lee
Stanford

Roshen Nair
Stanford

Qizheng Zhang
Stanford

Kangwook Lee
KRAFTON

Omar Khattab
MIT

Chelsea Finn
Stanford





Figure 2: **Meta-Harness search loop. (1)** An agent reads a filesystem containing all prior candidates' source code, execution traces, and scores, and proposes a new harness. **(2)** We evaluate the proposed harness on evaluation tasks. **(3)** All logs (proposed code, reasoning traces, evaluation scores) are stored in the filesystem in a new directory, and the loop repeats.

Lee, Y., Nair, R., Zhang, Q., Lee, K., Khattab, O., & Finn, C. (2026). Meta-harness: End-to-end optimization of model harnesses. *arXiv preprint arXiv:2603.28052*.

Meta-Harness: optimize the harness, keep the model fixed

- In this context, Harness is the stateful program around an LLM that decides what context the model sees at each step: what to store, retrieve and show, and how tools are called. Engineers usually tune it by hand.
- Traditional prompt and text optimizers learn from compressed feedback such as scores, summaries or short windows. Harness failures often trace back to decisions made many steps earlier, and summaries hide them.
- In Meta-Harness, an outer loop in which a coding agent (Claude Code with Opus 4.6) reads the code, scores and execution traces of every earlier harness from a filesystem, then writes a better one. The model weights never change.
- The learned artifact is code, so every change is readable, diffable and reversible, and the proposer never sees held-out test results.

Meta-Harness: optimize the harness, keep the model fixed



What is learned: harness code, not model weights.

Feedback per evaluation: up to 10M tokens of raw diagnostics.

Kept outside the proposer: the model and held-out test results.

Figure generated with help from Claude Code

Meta-Harness: optimize the harness, keep the model fixed

Figure generated with help from Claude Code

THE PROPOSER'S FILESYSTEM

illustrative layout: one directory per evaluated harness

```
search_run/
├─ SKILL.md                    rules: where to write, what may be modified
├─ cand_001/
│  ├─ harness.py               full source code
│  ├─ scores.json              accuracy, context tokens
│  └─ traces/                  prompts, tool calls, model outputs, state updates
│     ├─ task_0007.log
│     └─ …
├─ cand_002/  …
├─ …
└─ cand_040/  …
```

Read selectively, not all at once

the proposer navigates with grep and cat

82 files median read per iteration


20+ earlier candidates referenced

in the most demanding setting

Figure generated with help from Claude Code

FEEDBACK PER STEP

million tokens per iteration, log scale (paper's Table 1)




About three orders of magnitude more diagnostic context than prior text optimizers, because nothing is summarized away up front.

Meta-Harness: optimize the harness, keep the model fixed

- Each evaluated harness keeps its source code, its scores, and its execution traces: prompts, tool calls, model outputs and state updates.
- The proposer browses with grep and cat rather than loading everything. In the most demanding setting it read a median of 82 files per iteration, drawing on more than 20 earlier candidates.
- A short skill file says where to write harnesses, how to inspect earlier ones and which files may change. There is no fixed search template or separate memory module: the files are the memory.
- One evaluation can produce up to 10 million tokens of diagnostics, about three orders of magnitude more than prior text optimizers use (right).

Meta-Harness: optimize the harness, keep the model fixed

ONE ITERATION



A TYPICAL RUN

~20 iterations, a few candidates each (2 per iteration for text classification); a few hours of wall-clock time


No parent-selection rule: the proposer decides which past candidates to inspect and build on

Example diagnosis: two regressions shared a prompt edit; the proposer isolated the structural change, then tried a safer additive edit, which became the run's best

After the last iteration: test the frontier once on held-out tasks

PARETO FRONTIER

illustrative points; after the paper's Figure 3



- frontier: no other candidate is both more accurate and cheaper
- dominated candidates stay on disk as evidence for later steps

Figure generated with help from Claude Code

Meta-Harness: optimize the harness, keep the model fixed

- Each iteration the proposer writes new candidates (two per iteration for text classification, over about 20 iterations). They run on search-set tasks with the fixed model, and their code, traces and scores go back into the filesystem.
- Candidates are compared on several objectives, for example accuracy against context tokens. There is no hand-written rule for choosing which candidate to build on.
- The proposer never sees test results. After the last iteration, the frontier is evaluated once on held-out tasks.
- In one run the proposer noticed that two regressions shared a prompt edit, isolated the structural change, and switched to a safer additive edit, which became the run’s best harness.

Meta-Harness: optimize the harness, keep the model fixed

- Text classification (three datasets, GPT-OSS-120B): 48.6% average accuracy versus 40.9% for ACE, with 11.4K instead of 50.8K context tokens. Best on 6 of 9 unseen datasets (73.1% vs 70.2%).
- Math with retrieval (200 IMO-level problems, five models): +4.7 points over no retrieval, but only +1.3 over plain BM25.
- TerminalBench-2 (89 tasks): 76.4% with Opus 4.6, second among Opus agents; 37.6% with Haiku 4.5, first.
- With full traces the median reached 50.0%, versus 34.9% with summaries and 34.6% with scores only.
- Only one proposer was tested. TerminalBench-2 search and evaluation used the same tasks; the authors audited for leakage. The model used to select the math harness was also among the five evaluated. Repeated selection on a search set can overfit it, though overfitting in code is easier to inspect than in weights.

LLM/Skills wiki, DySECT and Meta-Harness

The LLM and skills wiki, DySECT and Meta-Harness all improve a deployed system without changing model weights. The question is how far each goes toward Post-Deployment Self-Improving agents.

- Does the system keep learning from its own use, couple several learners and grow its task set?
- Does it separate candidate from promoted beliefs, keep explicit state with provenance, and control errors?
- Does it improve the answer path and the acquisition path, with evidence over time?
- Does light human supervision correct drift?

.

LLM and skills wiki: compounding memory, light governance

ACCOMPLISHES

Persistent, compounding memory. Knowledge is compiled once into readable pages and refined with every source and query, instead of being re-derived per question.

Explicit, versioned state. Pages cite sources and live in Git with an index and a log, so every change can be inspected and reverted.

Knowledge that improves learning. In WikiSkill, giving the skill proposer the wiki raised average accuracy from 48.7 to 63.7: the clearest sign among the three cases that accumulated knowledge makes the learner better.

LLM and skills wiki: compounding memory, light governance

FALLS SHORT

Weak belief control. Pages are written without a candidate stage, confidence or constraints between claims, so ingest errors get baked in; WikiSkill never rolls back or prunes its wiki.

Short horizon. One 13-question study and offline benchmark runs; no new learning problems are created.

DySECT

ACCOMPLISHES

- Coupled learners over one KB: Extraction, concept acquisition and relation acquisition share a knowledge base constrained by hierarchies and mutual exclusion, as in NELL.
- Confidence-weighted beliefs with provenance: Each triple keeps confidences, frequency and source labels; conflicts lower confidence; curator decisions are trusted.
- A growing ontology and measured gains: New subconcepts and exclusive families emerge, and one round of KB feedback raised DocRED recall for all four extractors (+5.6 to +7.8 points).

DySECT

FALLS SHORT

Early evidence: Two rounds on one dataset, recall only (precision not reported); faster learning of new relations is untested.

Meta-Harness: rigorous promotion, short horizon

ACCOMPLISHES

- Candidate versus promoted: Every candidate is scored on a search set, a Pareto frontier is kept, and held-out tasks are used once, at the end.
- Self-diagnosis from raw experience: Reading code, traces and scores lets the proposer explain regressions; with raw traces the median result was 50.0%, against about 35% with summaries.
- Learning stored as code: The learned artifact is versioned, inspectable code, with large gains in text classification and transfer to unseen datasets.

Meta-Harness: rigorous promotion, short horizon

FALLS SHORT

- One task, offline: Each run optimizes one harness for one domain over a few hours: no coupled tasks, no growing task set, no learning during deployment.

- Selection pressure: Repeated selection on one search set can overfit it; only one proposer was tested; faster learning over time is not measured.

Broader View

	LLM and skills wiki	DySECT	Meta-Harness
What is learned	Wiki pages; skills in WikiSkill	Typed triples with confidence; a growing ontology	Harness code
Experience used	Sources and queries; agent traces in WikiSkill	Its own extractions, LLM acquisitions, curator edits	Code, traces and scores of every candidate
Coupling	Wiki feeds skills; claims unconstrained	Several learners; hierarchy and mutual-exclusion constraints	None: one harness per domain
Gate	Lint for pages; validation score for skills	Confidence; optional trusted curator	Search-set Pareto frontier; held-out test once
Best evidence	Preregistered 13-question test; WikiSkill ablation	DocRED recall, four extractors, two rounds	Three domains; raw-trace ablation
PDSI strength	Compounding, readable memory	Coupled, confidence-weighted beliefs	Rigorous promotion and self-diagnosis
Main PDSI gap	never-pruned knowledge	No precision or long-run evidence	Offline, single-task search

What a PDSI agent would take from each

- Complementary strengths: Readable, compounding memory from the LLM Wiki; an evidence layer feeding gated, reversible skills from WikiSkill; coupled learners and confidence-weighted beliefs from DySECT; trace-based diagnosis and held-out promotion from Meta-Harness.
- Shared gaps (shaded): None runs for long during deployment, whereas PDSI should work every day for years.
- Next step: Combine DySECT-style beliefs, wiki-style memory and Meta-Harness-style, and evaluate the result longitudinally with the Part V protocol. Part VII turns these gaps into open problems.

KEY MESSAGE · PART IV

- The learned state lives in different places: KB triples in DySECT, pages and skills in the LLM Wiki and WikiSkill, harness code in Meta-Harness, and weights in real-time RL.
- The three case studies have complementary strengths.
- What's still open: few systems measure whether learning gets faster, control errors over long runs, or report evidence beyond a few rounds.

Continuous learning is useful when it is selective, verifiable and reversible.

Next · Part V — Design Patterns

PART V · 25 MINUTES

Design patterns for never-ending NLP systems

How do we turn update targets into a loop that improves the system without destabilizing it?

Patterns for self-improving language agents

1 Knowledge-grounded retrieval and memory updates
2 Substrate choice: modular vs. end-to-end
3 Consolidation and selective forgetting
4 Coupled views and tasks without circularity
5 Provenance and auditability
6 The governed update lifecycle and validation gates
7 Staging, shadow mode and quarantine
8 Version bundles, rollback and repair
9 Bounded autonomy and human curation
10 Reflective improvement grounded in evidence

1-Retrieve structure and evidence, not only passages

For every output:

- Which evidence supports the answer?
- Which claims are uncertain or stale?
- What new candidate knowledge emerged?

StackFeed: a structured textual actor, critic that edits a knowledge base using feedback.

Kirtania et al., 2025

MemGov: detects must-link and cannot-link constraints among retrieved memories. Christou et al., AACL2026

see also LLM Wiki in Part VI

1-Every memory write should be a controlled update

Write path:

Mem0 (Chhikara et al., 2025); A-MEM links and evolves notes (Xu et al., 2025)

Read path: Retrieve by relevance **and learned usefulness**: the most similar memory is not always the one that prevents the failure.

MemRL (Zhang et al., 2026)

2-Modular versus end-to-end: where should learning live?

Parametric

continual fine-tuning · adapters / LoRA · RL

+ broad generalization, cheaper inference

– effects are distributed; hard to inspect, scope or remove a single influence

Non-parametric

KB · memory · prompts and context · skill library · evaluators

+ local, inspectable, versionable, reversible

– interference, context crowding, unexpected interactions

2-Prompts, contexts and harnesses as learned artifacts

GEPA: Reflects on trajectories to propose and test prompt changes. Agrawal et al., 2025

ACE: Context as an evolving playbook: generate, reflect, curate. Zhang et al., 2026

Test-time learning: Adapting an LLM during deployment on the inputs it sees. Hu et al., 2025

RPT: Reflective Prompt Tuning through Language Model Function-Calling, Bayat et al., 2026

An optimizer that repeatedly selects prompts against one dev set **adapts to that set's peculiarities**.

3-Consolidation moves learning across substrates and can lose it

COMPRESSION HAZARD

“Do not inherit training datasets without explicit support in derived-model documentation”

Can be summarized as:

“Do not inherit facts.” — shorter, broader, harmful

Test every summary on positive and negative cases. Keep links to evidence. Version the datasets.

3-Operations that are often confused

Operation	What happens
Revision	A belief or rule changes in response to evidence
Forgetting	Previously available information or capability is lost
Expiration	An item is withdrawn under a validity or retention policy
Deletion	A representation is removed

4-Multiple views can be complementary without being independent

View — a representation or channel: local sentence, document structure, typed KB context.
Source — the origin of an observation. One source can feed several views.

Each view contributes **within its evidential scope**
Validate a view's labels with sources or procedures that **do not repeat its predictions**.

Co-training assumes conditions on the views (Blum and Mitchell, 1998).

5-Every learned change should be able to explain itself

For each learned claim or rule

Who or what produced it?

At what time?

By which method?

From which source?

With what confidence?

Approved by whom?

And: what depends on it now?

6-stages between an observation and active state

Observation: record the event and context

Proposal: a candidate change and its intended benefit

Assessment: technical evidence about the candidate

Authorization: does policy permit activation?

Commitment: a versioned active state

Monitoring: consequences not visible before; may open a new cycle

Any stage may end in rejection, revision or staging, not only in commitment.

7-Limit exposure before you trust a change

Shadow mode: Run the candidate on representative inputs and compare outputs — without writing accepted state.

Quarantine ≠ deletion: A questionable record stays visible to auditors but is excluded from supervision and ordinary retrieval.

Staged promotion: Start with one domain or relation family. Expanding needs evidence about the newly exposed conditions.

8-Version compatible bundles, not individual files

- **Why bundles**: Prompt p4 assumes schema s2 and index r7. Reverting p4 alone can produce an invalid configuration if a later schema removed a relation name.
- **What to record:** before/after states · change sets · provenance · affected records and inferences · outputs already delivered
- **Rollback:** Replace the harmful state with an earlier compatible bundle. Simple when little has happened since.
- **Repair:** Trace descendants; keep those with independent support; quarantine the rest; preserve unrelated progress.

9-Autonomy is decided stage by stage, not all at once

Stage	Who decides	Why
Detect an error pattern	Agent	Cheap, reversible
Propose a new task	Agent	A proposal changes nothing
Collect examples, train a candidate	Agent, in a sandbox	No effect on active state
Recommend promotion	Agent + evaluator	Evidence, not permission
Activate in production	Policy or human	Affects users
Change the acceptance rule	Never the agent alone	Avoid circular validation

Bounded autonomy is not guaranteed safety.

9-Spend scarce human attention where it changes outcomes

Prioritize for review

- high-impact updates, even when confident
- conflicting evidence
- schema and policy changes
- proposed new learning tasks
- a random sample, to find blind spots

Reviewer decisions are themselves trusted signals and review effort belongs in the cost of learning.

10-Reflection proposes; evidence decides

Reflection can happen:

- **Within an episode:** Iterative self-feedback and revision of outputs. Self-Refine · Madaan et al., 2023
- **Across trials:** Verbal lessons stored and reused on later attempts. Reflexion · Shinn et al., 2023

Must be Grounded in supervision: Instance-level critiques plus reusable semantic guidance from labeled examples. Hassell et al., 2026

KEY MESSAGE · PART V

Design the update path as carefully as the inference path: typed state, explicit lineage, gated promotion and reversible change.

Good governance makes decisions explicit and repair possible. It does not certify correctness by construction.

Next · Part VI — evaluation, governance and reliability under change.

PART VI · 20 MINUTES

Evaluation, governance and reliability under change

What evidence justifies calling a system self-improving and who decides when it may learn?

Self-improvement is as much an evaluation problem as a learning problem.

A plausible architecture is not evidence of improvement. State changes and mechanisms make the claim **testable**; they do not **settle** it.

What improved?	Relative to what?	With which resources?	For how long?	With what uncertainty?

Evaluation shifts from a snapshot to a lifecycle

Snapshot Evaluation: one model, one test set, one score

Lifecycle Evaluation: initial quality, forgetting and regressions, hallucinated updates, human review efficiency, temporal robustness, constraint satisfaction, provenance quality, time to recover from errors

Key questions:

Is the system better after a week, a month, a year?

Is the process that changes it reliable?

Declare the evaluation before you see the result

TASK: evidence-supported extraction from new documents

POPULATION: domains, sources, languages, time range

RESOURCES: inference budget, labels, review effort

STATE BOUNDARY: which components may change

METRIC: with its matching policy and judge version

COMPARISON: frozen, maintained, or a simpler remedy

Report two reference frames

$$P_{ref}(S_\square) = E_{x \sim D_{ref}} [\, score(S_\square, x) \,]$$

fixed reference distribution D_{ref} · operational distribution $D_\square$ at time t

Up on D□, down on D_ref
Adapting while forgetting. A single moving score hides it.

Flat on D_ref, failing on D□
Preserving while not adapting. A single fixed score hides it.

The expectation is a target quantity; real evaluations use finite samples and depend on budget, evaluator and environment — all of which must be specified.

Does the system stay correct as the world changes?

Does the system stay correct as the world changes?

FreshLLMs

Vu, Tu, et al. "Freshllms: Refreshing large language models with search engine augmentation." *Findings of the Association for Computational Linguistics: ACL 2024*. 2024.

FRESHLLMS: Refreshing Large Language Models with Search Engine Augmentation

Tu Vu[1] **Mohit Iyyer**[2] **Xuezhi Wang**[1] **Noah Constant**[1] **Jerry Wei**[1]
Jason Wei[3*] **Chris Tar**[1] **Yun-Hsuan Sung**[1] **Denny Zhou**[1] **Quoc Le**[1] **Thang Luong**[1]

Google[1] University of Massachusetts Amherst[2] OpenAI[3]
freshllms@google.com

Abstract

Since most large language models (LLMs) are trained once and never updated, they struggle to dynamically adapt to our ever-changing world. In this work, we present FRESHQA, a *dynamic* QA benchmark that tests a model's ability to answer questions that may require reasoning over up-to-date world knowledge. We develop a two-mode human evaluation procedure to measure both correctness and hallucination, which we use to benchmark both closed and open-source LLMs by collecting >50K human judgments. We observe that all LLMs struggle to answer questions that require encoded in their parameters. While additional training using human feedback (Ouyang et al., 2022) or knowledge-enhanced tasks can mitigate this issue, it is not easily scalable for real-time knowledge updates (e.g., stock prices). In-context learning (Brown et al., 2020) is an appealing alternative by which real-time knowledge can be injected into an LLM's prompt. While recent work has begun to explore augmenting LLM prompts with web search results (Lazaridou et al., 2022; Press et al., 2022), it is unclear how to take full advantage of search engine outputs to increase LLM factuality.

In this work, we collect FRESHQA, a novel bench-

Does the system stay correct as the world changes?

FreshLLMs

Vu, Tu, et al. "Freshllms: l
language models with sea
augmentation." *Findings o
Association for Computat
ACL 2024*. 2024.

Type	Question	Answer (as of this writing)
never-changing	*Has Virginia Woolf's novel about the Ramsay family entered the public domain in the United States?*	***Yes**, Virginia Woolf's 1927 novel To the Lighthouse entered the public domain in 2023.*
never-changing	*What breed of dog was Queen Elizabeth II of England famous for keeping?*	***Pembroke Welsh Corgi** dogs.*
slow-changing	*How many vehicle models does Tesla offer?*	*Tesla offers **six** vehicle models: Model S, Model X, Model 3, Model Y, Tesla Semi, and Cybertruck.*
slow-changing	*Which team holds the record for largest deficit overcome to win an NFL game?*	*The record for the largest NFL comeback is held by the **Minnesota Vikings**.*
fast-changing	*Which game won the Spiel des Jahres award most recently?*	***Dorfromantik** won the 2023 Spiel des Jahres.*
fast-changing	*What is Brad Pitt's most recent movie as an actor*	*Brad Pitt is credited as Keith in **IF**.*
false-premise	*What was the text of Donald Trump's first tweet in 2022, made after his unbanning from Twitter by Elon Musk?*	*He **did not tweet** in 2022.*
false-premise	*In which round did Novak Djokovic lose at the 2022 Australian Open?*	*He **was not allowed to play** at the tournament due to his vaccination status.*

Figure 1: FRESHQA exemplars. Our questions are broadly divided into *four* main categories: *never-changing*, in which the answer almost never changes; *slow-changing*, in which the answer typically changes over the course of several years; *fast-changing*, in which the answer typically changes within a year or less; and *false-premise*, which includes questions whose premises are factually incorrect and thus have to be rebutted.

Does the system stay correct as the world changes?

EvoWiki

Tang, Wei, et al. "Evowiki: Evaluating llms on evolving knowledge." *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*. 2025.

EvoWiki: Evaluating LLMs on Evolving Knowledge

Wei Tang [1,2], Yixin Cao [3*], Yang Deng [4], Jiahao Ying [4], Bo Wang [5], Yizhe Yang [5], Yuyue Zhao [1,2], Qi Zhang [3], Xuanjing Huang [3], Yugang Jiang [3], Yong Liao [1,2]

[1] University of Science and Technology of China
[2] CCCD Key Lab of Ministry of Culture and Tourism
[3] Institute of Trustworthy Embodied AI, Fudan University
[4] Singapore Management University, [5] Beijing Institute of Technology
weitangcs@gmail.com yxcao@fudan.edu.cn

Abstract

Knowledge utilization is a critical aspect of LLMs, and understanding how they adapt to evolving knowledge is essential for their effective deployment. However, existing benchmarks are predominantly static, failing to capture the evolving nature of LLMs and knowledge, leading to inaccuracies and vulnerabili-




Figure 1: EvoWiki categorizes knowledge into three states according to the cut-off date of the LLMs.

Longitudinal Evaluation

Mitchell, Tom, et al. "Never-ending learning." *Communications of the ACM* 61.5 (2018): 103-115.

DOI:10.1145/3191513

Never-Ending Learning

By T. Mitchell, W. Cohen, E. Hruschka, P. Talukdar, B. Yang, J. Betteridge, A. Carlson, B. Dalvi, M. Gardner, B. Kisiel, J. Krishnamurthy, N. Lao, K. Mazaitis, T. Mohamed, N. Nakashole, E. Platanios, A. Ritter, M. Samadi, B. Settles, R. Wang, D. Wijaya, A. Gupta, X. Chen, A. Saparov, M. Greaves, and J. Welling

Abstract

Whereas people learn many different types of knowledge from diverse experiences over many years, and become better learners over time, most current machine learning systems are much more narrow, learning just a single function or data model based on statistical analysis of a single data set. We suggest that people learn better than computers precisely because of this difference, and we suggest a key direction for machine learning research is to develop software architectures that enable intelligent agents to also learn many types of knowledge, continuously over many years, and to become better learners over time. In this paper we define more precisely this *never-ending learning* paradigm for machine learning, and we present one case study: the Never-Ending Language Learner (NELL), which achieves a number of the desired properties of a never-ending learner. NELL has been learning to read the Web 24hrs/day since January 2010, and so far has acquired a knowledge base with 120mn diverse, confidence-weighted beliefs (e.g., *servedWith(tea,biscuits)*), while learning thousands of interrelated functions that continually improve its reading competence over time. NELL has also learned to reason over its knowledge base to infer new beliefs it has not yet read from those it has, and NELL is inventing new relational predicates to extend the ontology it uses to represent beliefs. We describe the design of NELL, experimental results illustrating its behavior, and discuss both its successes and shortcomings as a case study in never-ending learning. NELL can be tracked online at http://rtw.ml.cmu.edu, and followed on Twitter at @CMUNELL.

(e.g., the spam filter) given a training set of input/output pairs $\{\langle x_i, y_i \rangle\}$ of that function. Other machine learning paradigms exist as well (e.g., unsupervised clustering, topic modeling, reinforcement learning) but these paradigms also typically acquire only a single function or data model from a single dataset.

In contrast to these paradigms for learning single functions from well organized data sets over short time-frames, humans learn many different functions (i.e., different types of knowledge) over years of accumulated diverse experience, using extensive background knowledge learned from earlier experiences to guide subsequent learning. For example, humans first learn to crawl, then to walk, run, and perhaps ride a bike. They also learn to recognize objects, to predict their motions in different circumstances, and to control those motions. Importantly, they learn *cumulatively*: as they learn one thing this new knowledge helps them to more effectively learn the next, and if they revise their beliefs about the first then this change refines the second.


The thesis of our research is that *we will never truly understand machine or human learning until we can build computer programs that, like people,*

- learn many different types of knowledge or functions,
- from years of diverse, mostly self-supervised experience,
- in a staged curricular fashion, where previously learned knowledge enables learning further types of knowledge,
- where self-reflection and the ability to formulate new representations and new learning tasks enable the learner to avoid stagnation and performance plateaus.

Longitudinal Evaluation

Mitchell, Tom, et al. "Never-ending learning." *Communications of the ACM* 61.5 (2018): 103-115.


Figure 5. NELL KB size over time. Total number of beliefs (left) and number of high confidence beliefs (right) versus iterations. Left plot vertical axis is tens of millions, right plot vertical axis is in millions. The horizontal axis covers NELL iterations from January 2010 until July 2017.



Longitudinal Evaluation

Mitchell, Tom, et al. "Never-ending learning." *Communications of the ACM* 61.5 (2018): 103-115.


Figure 6. Evolution of NELL reading accuracy over time. The vertical axis shows the estimated Mean Average Precision over the 1000 most confident predictions for a representative sample of 18 categories and 13 relations in NELL's ontology. The horizontal axis represents NELL iterations from January 2010 through November 2016.



Longitudinal Evaluation

Mitchell, Tom, et al. "Never-ending learning." *Communications of the ACM* 61.5 (2018): 103-115.

Figure 7. Human feedback to NELL over time. Each bar in this histogram shows the number of NELL beliefs for which humans provided negative feedback, during a 78 iteration interval. This averages out to 2.4 items of feedback per month, per predicate in NELL's ontology. Human input to NELL has been dropping over time, even as its reading accuracy has been increasing.




Did the update damage what used to work?

Measure

- accuracy on old tasks and on new tasks
- backward transfer — effect of new learning on old tasks
- forward transfer — effect of old learning on new tasks
- negative transfer on protected slices
- schema-level and calibration regressions

Same final score, very different learning trajectories



Steady improvement

Early gain, severe regression, recovery

Late improvement

Report the path: time to benefit, worst regression, recovery time, variance across runs.

checkpoints over deployment time →

schematic, not results

Gama et al., 2014 (concept drift and sequential evaluation)

Benchmarks test different properties

Benchmark	What it probes	Reference
LoCoMo	Very long-term conversational memory	Maharana et al., 2024
LongMemEval	Long-term interactive memory, knowledge updates, temporal reasoning	Wu et al., 2025
MTU-Bench	Multi-granularity tool use	Wang et al., 2025
AssistantBench	Realistic, time-consuming web tasks	Yoran et al., 2024
EvoWiki	Evolving knowledge	Tang et al., 2025
AgentCL	Continual learning across task streams	Shu et al., 2026
FuncBenchGen	multi-step tool-use tasks	Maekawa et al., 2026
MAWILE	workbench for auditing LLM-as-a-judge sensitivity	Hassel et al., 2026b

What a self-improvement report should show

things to report

Performance. Target performance and protected slices.

Costs. Labels, model calls, latency and review effort.

Acceptance rate. How many proposed updates were accepted.

Harm. Harmful-update rate and the worst regression.

Recovery. Time to recover after errors.

Uncertainty. Intervals and the confounds still unresolved.

Report failures too. A failed auxiliary task is evidence about the mechanism. Preservation under drift is compared with the frozen system; it is not required to rise.

Governance: when is learning allowed?

Before an update acts, four questions need answers: where it came from (provenance), who may learn what and when (policy), whether it harmed safety, fairness, calibration or old tasks (monitoring), and how to undo it and its consequences (rollback).

AgentSpec gives customizable, declarative constraints on what an LLM agent may do at run time.

Which agent components actually help, under controlled protocols.

Version thresholds and permissions: relaxing a promotion threshold alters the learning trajectory.

Learning opens a new input channel to future behaviour

- Whatever enters memory, the KB or skills shapes later answers, so each stage of the channel carries its own risk.

- Poisoning and injection can happen. Seeded false relations, instructions hidden in retrieved text, manipulated feedback. Document content is never permission to modify configuration.

- Reward hacking is a risk. Optimizing a proxy, such as an auxiliary metric or a lenient judge, instead of the target.

- Privacy leakage can also be a risk. Memories and traces hold personal data. Keep only what learning and audit require, with access and retention controls.

KEY MESSAGE · PART VI

A self-improving system is only as trustworthy as its evaluation loop.

Show what improved, relative to what, with which resources, for how long — and with what remaining uncertainty.

Next · Part VII — Open Problems and Discussions

PART VII · 10 MINUTES

Open problems and discussion

What remains open — and what the *ACL community is especially well placed to solve.

open research problems

Diagnosis-driven task invention

Learning coupling structure

Separate information gain from population shift

Evaluator co-evolution

Long-horizon reproducibility

Learning to learn, measured

Questions for the *ACL community

Benchmarking self-improvement. Streams with fixed targets and evolving tasks, where adding easy tasks cannot inflate progress (sketch, right).

Multilingual and domain adaptation. Methods built on English and high-resource benchmarks may not transfer, and feedback loops can widen gaps between languages.

Online versus offline. Which updates belong in deployment, and which in a curated offline cycle? All three case studies learn offline or between rounds.

Reward hacking and proxies. How to keep an agent from optimizing its judge instead of its task. Cursor’s real-time RL already met this in production.

Discussion: which of these would you put in a shared task?

A design and evaluation checklist for self-improving agents

Design commitment	Evidence or specification required
Target tasks	Inputs, outputs, populations, metrics, protected constraints
Learner boundary	Persistent state, transient context, external dependencies
Experience	Sources, selection process, supervision, exposure history
Retained pathway	What changes and how it can affect future decisions
Views	Complementarity, provenance, dependence assumptions
Coupled tasks	Meaning and permissions of each learning edge
New tasks	Diagnosis, specification, alternatives, target transfer test
Substrates	Scope, generalization, cost, auditability, reversibility
Governance	Proposal, assessment, authorization, commitment, monitoring
Repair	Version bundles, descendants, rollback, compensation
Evaluation	Frozen and updating comparisons, prospective tests, uncertainty
Reporting	Gains, failures, resources, limitations, reproducible history

The conclusion: conditional and testable

- A deployed language agent can improve through retained changes across many substrates: knowledge bases, wikis, skills, harness code and weights.

- That improvement is established only when future performance, learning efficiency or preservation under change improves under a defensible comparison.

- What makes it credible is evidence, governance, revision and longitudinal evaluation.

Where to read next

- Start with the foundations: Mitchell et al. (Mitchell et al., Never-Ending Learning. *Communications of the ACM*, 2018) define never-ending learning; Silver and Sutton argue for agents that learn from their own stream of experience.

- Add the two literatures this tutorial connects. Continual learning of LLMs, which Hou et al. describe as moving from weights to memory, skills and protocols; and self-evolving agents with persistent memory.

- Check also related tutorials. Two 2025 tutorials treat continual learning of LLMs mainly at training time, one at IJCNLP-AACL 2025. This tutorial adds the post-deployment, governed, multi-substrate view.

Thank you. Questions?

Estevam Hruschka · Megagon Labs · estevam@megagon.ai