KEY MESSAGE · PART I

Static systems drift out of alignment with a changing ecosystem. Learning after deployment must be designed, validated and governed.

Next · Part II — what it means, precisely, for a deployed system to learn.

KEY MESSAGE · PART I

Every channel through which an agent improves after deployment (its weights, reward signal, memory, skills, or code) is also a channel through which it can be corrupted, so self-improvement is only as safe as the provenance of what it learns from and the independence of what evaluates it.

Next · Part II — what it means, precisely, for a deployed system to learn.

Main takeaway

Today’s deployed AI systems usually adapt around the model, not through durable learning in the model.

True post-deployment learning is hard because every interaction can become a safety, reliability, privacy, and governance decision.

The future is not models that update themselves freely.

The future is systems that learn continuously, selectively, verifiably, and reversibly.

“A Post-Deployment Self Improving Agent is only useful when it is controlled.”

PART II · 30 MINUTES

Foundations: never-ending, lifelong and continual learning

What must be true before a change in a deployed system supports the claim that it learned — and what do the classic traditions already tell us?

General Classic Terminology

	Research question	reference
Lifelong learning	Can knowledge from earlier tasks make later learning easier?	Thrun, 1998
Never-ending learning	Can an agent keep acquiring and revising diverse knowledge and capabilities, and autonomously become a better learner over time?	Mitchell et al., 2018
Continual learning	Can a model learn new tasks without catastrophically forgetting old ones?	De Lange et al., 2022

Lifelong Learning

Lifelong learning research question:

Can knowledge learned from previous tasks improve future learning?

Key Ideas

- **Sequence of tasks**
- **Transfer across task**
- **Accumulated knowledge**
- **Better sample efficiency**
- **Learning-to-learn over time**

Foundations

Thrun, Sebastian, and Tom M. Mitchell. "Lifelong robot learning." *Robotics and autonomous systems* 15.1-2 (1995): 25-46.

Lifelong Robot Learning[1]

Sebastian Thrun[2] and Tom M. Mitchell[3]

[2] University of Bonn, Institut für Informatik III, Römerstr. 164, 53117 Bonn, Germany
[3] School of Computer Science, Carnegie Mellon University, Pittsburgh, PA 15213, USA

Abstract. Learning provides a useful tool for the automatic design of autonomous robots. Recent research on learning robot control has predominantly focussed on learning single tasks that were studied in isolation. If robots encounter a multitude of control learning tasks over their entire lifetime, however, there is an opportunity to transfer knowledge between them. In order to do so, robots may learn the invariants of the individual tasks and environments. This task-independent knowledge can be employed to bias generalization when learning control, which reduces the need for real-world experimentation. We argue that knowledge transfer is essential if robots are to learn control with moderate learning times in complex scenarios. Two approaches to lifelong robot learning which both capture invariant knowledge about the robot and its environments are presented. Both approaches have been evaluated using a HERO-2000 mobile robot. Learning tasks included navigation in unknown indoor environments and a simple find-and-fetch task.

Core Question

How do we build systems that take advantage of learning many tasks to learn them better (needing less training experience)?

Lifelong Learning

Thrun, Sebastian. *Lifelong Learning: A Case Study*. No. CMUCS95208. 1995.

Lifelong Learning: A Case Study

Sebastian Thrun

November 1995

Abstract

Machine learning has not yet succeeded in the design of robust learning algorithms that generalize well from very small datasets. In contrast, humans often generalize correctly from only a single training example, even if the number of potentially relevant features is large. To do so, they successfully exploit knowledge acquired in previous learning tasks, to bias subsequent learning.

This paper investigates learning in a lifelong context. Lifelong learning addresses situations where a learner faces a stream of learning tasks. Such scenarios provide the opportunity for synergetic effects that arise if knowledge is transferred across multiple learning tasks. To study the utility of transfer, several approaches to lifelong learning are proposed and evaluated in an object recognition domain. It is shown that all these algorithms generalize consistently more accurately from scarce training data than comparable "single-task" approaches.

Lifelong Learning

Sodhani, Shagun, Sarath Chandar, and Yoshua Bengio. "Toward training recurrent neural networks for lifelong learning." *Neural computation* 32.1 (2020): 1-35.

Towards Training Recurrent Neural Networks for Lifelong Learning

Shagun Sodhani[1*], **Sarath Chandar**[1*], **Yoshua Bengio**[1, 2]
[1]Mila, Université de Montréal, Canada
[2]CIFAR Senior Fellow
*Equal Contribution
Contact: sshagunsodhani@gmail.com, apsarathchandar@gmail.com


Keywords: lifelong learning, catastrophic forgetting, capacity expansion, sequential supervised learning, continual learning, neural networks

Abstract

Catastrophic forgetting and capacity saturation are the central challenges of any parametric lifelong learning system. In this work, we study these challenges in the context of sequential supervised learning with an emphasis on recurrent neural networks. To evaluate the models in the lifelong learning setting, we propose a curriculum-based, simple, and intuitive benchmark where the models are trained on tasks with increasing levels of difficulty. To measure the impact of catastrophic forgetting, the model is tested on all the previous tasks as it completes any task. As a step towards developing *true* lifelong learning systems, we unify *Gradient Episodic Memory* (a catastrophic forgetting alleviation approach) and *Net2Net* (a capacity expansion approach). Both these models are proposed in the context of feedforward networks and we evaluate the feasibility of using them for recurrent networks. Evaluation on the proposed benchmark shows that the unified model is more suitable than the constituent models for lifelong learning setting.

Lifelong Learning

Gururangan, Suchin, et al. "Don’t stop pretraining: Adapt language models to domains and tasks." Proceedings of the 58th annual meeting of the association for computational linguistics. 2020.



Don’t Stop Pretraining: Adapt Language Models to Domains and Tasks

Suchin Gururangan[†] Ana Marasović[†◇] Swabha Swayamdipta[†]
Kyle Lo[†] Iz Beltagy[†] Doug Downey[†] Noah A. Smith[†◇]

[†]Allen Institute for Artificial Intelligence, Seattle, WA, USA
[◇]Paul G. Allen School of Computer Science & Engineering, University of Washington, Seattle, WA, USA
{suching,anam, ah}@allenai.org

Abstract

Language models pretrained on text from a wide variety of sources form the foundation of today’s NLP. In light of the success of these broad-coverage models, we investigate whether it is still helpful to tailor a pretrained model to the domain of a target task. We present a study across four domains (biomedical and computer science publications, news, and reviews) and eight classification tasks, showing that a second phase of pretraining in-domain (*domain-adaptive pretraining*) leads to performance gains, under both high- and low-resource settings. Moreover, adapting to the task’s unlabeled data (*task-adaptive pretraining*) improves performance even after domain-adaptive pretraining. Finally, we show that adapting to a task corpus augmented using simple data selection strategies is an effective alternative, especially when resources for domain-adaptive pretraining might be unavailable. Overall, we consistently find that multi-phase adaptive pretraining offers large gains in task performance.

Lifelong Learning

Gururangan, Suchin, et al. "Don't stop pretraining: Adapt language models to domains and tasks." Proceedings of the 58th annual meeting of the association for computational linguistics. 2020.




Figure 1: An illustration of data distributions. Task data is comprised of an observable task distribution, usually non-randomly sampled from a wider distribution (light grey ellipsis) within an even larger target domain, which is not necessarily one of the domains included in the original LM pretraining domain – though overlap is possible. We explore the benefits of continued pretraining on data from the task distribution and the domain distribution.

Lifelong Learning

Gururangan, Suchin, et al. "Don't stop pretraining: Adapt language models to domains and tasks." Proceedings of the 58th annual meeting of the association for computational linguistics. 2020.

IMDB review	**REALNEWS article**
"The Shop Around the Corner" is one of the great films from director Ernst Lubitsch. In addition to the talents of James Stewart and Margaret Sullavan, it's filled with a terrific cast of top character actors such as Frank Morgan and Felix Bressart. [...] The makers of "You've Got Mail" claim their film to be a remake, but that's just nothing but a lot of inflated self praise. Anyway, if you have an affection for romantic comedies of the 1940's, you'll find "The Shop Around the Corner" to be nothing short of wonderful. Just as good with repeat viewings.	[...] Three great festive films... The Shop Around the Corner (1940) Delightful Comedy by Ernst Lubitsch stars James Stewart and Margaret Sullavan falling in love at Christmas. Remade as You've Got Mail. [...]
HELPFULNESS review	**REALNEWS article**
Simply the Best! I've owned countless Droids and iPhones, but this one destroys them all. Samsung really nailed it with this one, extremely fast, very pocketable, gorgeous display, exceptional battery life, good audio quality, perfect GPS & WiFi performance, transparent status bar, battery percentage, ability to turn off soft key lights, superb camera for a smartphone and more! [...]	We're living in a world with a new Samsung. [...] more on battery life later [...] Exposure is usually spot on and focusing is very fast. [...] The design, display, camera and performance are all best in class, and the phone feels smaller than it looks. [...]

Table 4: Examples that illustrate how some domains might have overlaps with others, leading to unexpected positive transfer. We highlight expressions in the reviews that are also found in the REALNEWS articles.

Lifelong Learning

Pezeshkpour, Pouya, and Estevam Hruschka. "Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?." arXiv preprint arXiv:2501.17840 (2025).

Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?

Pouya Pezeshkpour
Megagon Labs
pouya@megagon.ai

Estevam Hruschka
Megagon Labs
estevam@megagon.ai

Abstract

Large Language Models (LLMs) have demonstrated remarkable performance on various tasks, yet their ability to extract and internalize deeper insights from domain-specific datasets remains underexplored. In this study, we investigate how continual pre-training can enhance LLMs' capacity for insight learning across three distinct forms: declarative, statistical, and probabilistic insights. Focusing on two critical domains: medicine and finance, we employ LoRA to train LLMs on two existing datasets. To evaluate each insight type, we create benchmarks to measure how well continual pre-training helps models go beyond surface-level knowledge. We also assess the impact of document modification on capturing insights. The results show that, while continual pre-training on original documents has a marginal effect, modifying documents to retain only essential information significantly enhances the insight-learning capabilities of LLMs. We released our dataset and code[1].

Lifelong Learning

Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?

Pouya Pezeshkpour
Megagon Labs
pouya@megagon.ai

Estevam Hruschka
Megagon Labs
estevam@megagon.ai




Figure 1: We use domain-specific data, like the Hallmarks of Cancer dataset, to adapt an LLM through continued pre-training with LoRA. Our goal is to assess whether LLMs are capable of effectively capture three types of insights: declarative, statistical, and probabilistic.


Pezeshkpour, Pouya, and Estevam Hruschka. "Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?." arXiv preprint arXiv:2501.17840 (2025).

Lifelong Learning

Pezeshkpour, Pouya, and Estevam Hruschka. "Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?." arXiv preprint arXiv:2501.17840 (2025).

Learning Beyond the Surface: How Far Can Continual Pre-Training with LoRA Enhance LLMs' Domain-Specific Insight Learning?

Pouya Pezeshkpour **Estevam Hruschka**



(a) Declarative (b) Statistical (c) Probabilistic

Figure 2: LLMs performance on insight extraction during continual pre-training. Declarative and statistical insights show slight improvement, while probabilistic insights remain largely unchanged. Increasing model size and using simplified documents significantly enhance performance.

Lifelong Learning

Szep, Marton, et al.
"Fine-tuning large language models with limited data: a survey and practical guide."
Transactions of the Association for Computational Linguistics 14 (2026): 341-377.

Fine-tuning Large Language Models with Limited Data: A Survey and Practical Guide

Marton Szep[1,2] **Daniel Rueckert**[1,3,4] **Rüdiger von Eisenhart-Rothe**[2]
Florian Hinterwimmer[1,2]

[1]AI in Healthcare and Medicine, Technical University of Munich (TUM) and TUM University Hospital, Munich, Germany
[2]Department of Orthopaedics and Sports Orthopaedics, TUM University Hospital, Germany
[3]Munich Center for Machine Learning (MCML), Munich, Germany
[4]Department of Computing, Imperial College London, UK

Abstract

Fine-tuning large language models (LLMs) with limited data poses a practical challenge in low-resource languages, specialized domains, and constrained deployment settings. While pre-trained LLMs provide strong foundations, effective adaptation under data scarcity requires focused and efficient fine-tuning techniques. This paper presents a structured and practical survey of recent methods for fine-tuning LLMs in data-scarce scenarios. We systematically review parameter-efficient fine-tuning techniques that lower training and deployment costs, domain and cross-lingual adaptation methods for both encoder and decoder models, and model specialization strategies. We further examine preference alignment approaches that guide model behavior using limited human or synthetic feedback, emphasizing sample and compute efficiency. Throughout, we highlight empirical trade-offs, selection criteria, and best practices for choosing suitable techniques based on task constraints, including model scaling, data scaling, and the mitigation of catastrophic forgetting. The aim is to equip researchers and practitioners with actionable insights for effectively fine-tuning LLMs when data and resources are limited.

Lifelong Learning

Kalajdzievski, Damjan. "Scaling laws for forgetting when fine-tuning large language models." arXiv preprint arXiv:2401.05605 (2024).

Scaling Laws for Forgetting When Fine-Tuning Large Language Models

Damjan Kalajdzievski [1]
Tenyx

Abstract

We study and quantify the problem of forgetting when fine-tuning pre-trained large language models (LLMs) on a downstream task. We find that parameter-efficient fine-tuning (PEFT) strategies, such as Low-Rank Adapters (LoRA), still suffer from catastrophic forgetting. In particular, we identify a strong inverse linear relationship between the fine-tuning performance and the amount of forgetting when fine-tuning LLMs with LoRA. We further obtain precise scaling laws that show forgetting increases as a shifted power law in the number of parameters fine-tuned and the number of update steps. We also examine the impact of forgetting on knowledge, reasoning, and the safety guardrails trained into Llama 2 7B chat. Our study suggests that forgetting cannot be avoided through early stopping or by varying the number of parameters fine-tuned. We believe this opens up an important safety-critical direction for future research to evaluate and develop fine-tuning schemes which mitigate forgetting.

Lifelong Learning

Kalajdzievski, Damjan. "Scaling laws for forgetting when fine-tuning large language models." arXiv preprint arXiv:2401.05605 (2024).




Figure 1. **Generation examples** of the pre-trained model, and a model fine-tuned with LoRA on a dataset of recent news articles (see Section 3.2 for a description of the dataset). These generations exemplify the updated knowledge, forgotten knowledge (ARC dataset (Clark et al., 2018)), and forgotten safety/alignment behavior (AdvBench dataset (Zou et al., 2023)) resulting from fine-tuning.

Lifelong Learning

Kalajdzievski, Damjan. "Scaling laws for forgetting when fine-tuning large language models." arXiv preprint arXiv:2401.05605 (2024).




Figure 1. **Generation examples** of the pre-trained model, and a model fine-tuned with LoRA on a dataset of recent news articles (see Section 3.2 for a description of the dataset). These generations exemplify the updated knowledge, forgotten knowledge (ARC dataset (Clark et al., 2018)), and forgotten safety/alignment behavior (AdvBench dataset (Zou et al., 2023)) resulting from fine-tuning.

Lifelong Learning

Kalajdzievski, Damjan. "Scaling laws for forgetting when fine-tuning large language models." arXiv preprint arXiv:2401.05605 (2024).




Figure 1. **Generation examples** of the pre-trained model, and a model fine-tuned with LoRA on a dataset of recent news articles (see Section 3.2 for a description of the dataset). These generations exemplify the updated knowledge, forgotten knowledge (ARC dataset (Clark et al., 2018)), and forgotten safety/alignment behavior (AdvBench dataset (Zou et al., 2023)) resulting from fine-tuning.

Never-Ending Learning

Never-ending learning research question:

Can an agent run indefinitely, acquire many kinds of knowledge, and become a better learner over time?

Key Ideas

- **Coupled Training of many interrelated learning tasks**
- **Discover New Coupling Constraints**
- **Automatically Learn to Extend the Set of Learning Tasks**
- **Growing Competence with Time**

Achieving pro-active, autonomous, cumulative, and persistent Post-Deployment Self-Improving AI agents

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell, T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning

Andrew Carlson[1], **Justin Betteridge**[1], **Bryan Kisiel**[1], **Burr Settles**[1], **Estevam R. Hruschka Jr.**[2], and **Tom M. Mitchell**[1]

[1]School of , USA

Abstract

We consider here the problem of building a never-ending language learner; that is, an intelligent computer agent that runs forever and that each day must (1) extract, or read, information from the web to populate a growing structured knowledge base, and (2) learn to perform this task better than on the previous day. In particular, we propose an approach and a set of design principles for such an agent, describe a partial implementation of such a system that has already learned to extract a knowledge base containing over 242,000 beliefs with an estimated precision of 74% after running for 67 days, and discuss lessons learned from this preliminary attempt to build a never-ending learning agent.

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning





Figure 1: Our Never-Ending Language Learner (NELL) architecture. See "Approach" for an overview of the approach implemented in NELL, and "Implementation" for subsystem details.

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning




Key Idea 1: Coupled training of many functions

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell, T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning




Key Idea 2: Discover New Coupling Constraints – Perform Inference

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell, T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning




Key Idea 3: Automatically Learn to Extend the Set of Learning Tasks

Never-Ending Learning

Carlson, A., Betteridge, J., Kisiel, B., Settles, B., Hruschka, E., & Mitchell T. (2010, July). Toward an architecture for never-ending language learning. In *Proceedings of the AAAI conference on artificial intelligence* (Vol. 24, No. 1, pp. 1306-1313).

Toward an Architecture for Never-Ending Language Learning



Key Idea 4: Cumulative, Staged Learning
Learning X improves ability to learn Y

Never-Ending Learning

From one learning problem to a coupled, evolving set

$$\text{Never-ending Learning} = (L, C)$$

$L = \{ (T_i, P_i, E_i) \}$ C = coupling constraints among solutions

Representation is Key

“What is the right representation that allows Post-Deployment Self-Evolving Agentic AI Systems without imposing constraints on confidence and controllability, and also not imposing constraints on what to learn next to improve the overall performance?”

The shared intuition

> Learning should not be a one-time event

Instead, intelligent systems should:

- **Learn from experience**
- **Reuse prior knowledge**
- **Adapt to new tasks**
- **Avoid forgetting**
- **Improve learning process**

Continual Learning

Continual learning research question:

Can a model learn new tasks without catastrophically forgetting old ones?

Key Ideas

- **Stability vs. Plasticity**
- **Incremental Learning**
- **Catastrophic Forgetting**
- **Modularity & Replay**
- **Transfer Learning**

Continual Learning Literature tends to consider ideas from both Lifelong and Never-Ending Learning

Continual Learning

Wang, Liyuan, et al. "A comprehensive survey of continual learning: Theory, method and application." IEEE transactions on pattern analysis and machine intelligence 46.8 (2024).




Fig. 3. A state-of-the-art and elaborated taxonomy of representative continual learning methods. We have summarized five main categories (
blocks), each of which is further divided into several sub-directions (red blocks).

Continual Learning

Continual learning asks:

Shi, Haizhou, et al. "Continual learning of large language models: A comprehensive survey." *ACM Computing Surveys*58.5 (2025): 1-42.




Fig. 1. A high-level overview of the modern pipeline for continually pre-training and fine-tuning LLMs, where two dimensions of continuity are described. **Vertical Continuity (or Vertical CL):** LLM training can be vertically divided into three stages: (i) CPT, (ii) DAP, and (iii) CFT. The main focus is the retention of the LLM's general knowledge (prevention of vertical forgetting). **Horizontal Continuity (or Horizontal CL):** After the LLMs are deployed, the models are continually updated when a new set of data becomes available. The primary goal is to prevent horizontal forgetting in a long sequence of tasks.

LLM agents are not automatically Post-Deployment Self-Improving

Many agents are adaptive, but not necessarily Post-Deployment Self-Improving

Post-Deployment Self-Improving requires:

persistent update targets + validation + governance + measurable self-improvement over time

AutoHarness: improving LLM agents by automatically synthesizing a code harness

Xinghua Lou, Miguel Lázaro-Gredilla, Antoine Dedieu,
Carter Wendelken, Wolfgang Lehrach, Kevin P. Murphy
Google DeepMind
{xinghua,lazarogredilla,adedieu,cwendelken,wpl,kpmurphy}@deepmind.com

March 5, 2026

Abstract

Despite significant strides in language models in the last few years, when used as agents, such models often try to perform actions that are not just suboptimal for a given state, but are strictly prohibited by the external environment. For example, in the recent Kaggle GameArena chess competition, 78% of Gemini-2.5-Flash losses were attributed to illegal moves. Often people manually write "harnesses" around LLMs to prevent such failures. In this paper, we demonstrate that Gemini-2.5-Flash can automatically synthesize such a code harness, using a small number of rounds of iterative code refinement given feedback from the (game) environment. The resulting harness prevents all illegal moves in 145 different TextArena games (both 1-player and 2-player), enabling the smaller Gemini-2.5-Flash model to outperform larger models, such as Gemini-2.5-Pro. Pushing our technique to the limit, we can get Gemini-2.5-Flash to generate the entire policy in code, thus eliminating the need to use the LLM at decision making time. The resulting code-policy receives a higher average reward than Gemini-2.5-Pro and GPT-5.2-High on 16 TextArena 1-player games. Our results show that using a smaller model to synthesize a custom code harness (or entire policy) can outperform a much larger model, while also being more cost effective.

Lou, X., Lázaro-Gredilla, M., Dedieu, A., Wendelken, C., Lehrach, W., & Murphy, K. P. (2026). AutoHarness: improving LLM agents by automatically synthesizing a code harness. *arXiv preprint arXiv:2603.03329*.

LLM agents a

Lou, X., Lázaro-Gredilla, M., Dedieu, A., Wendelken, C., Lehrach, W., & Murphy, K. P. (2026). AutoHarness: improving LLM agents by automatically synthesizing a code harness. *arXiv preprint arXiv:2603.03329*.

AutoHarness: improving LLM agents by automatically synthesizing a code harness

Xinghua Lou, Miguel Lázaro-Gredilla, Antoine Dedieu,
Carter Wendelken, Wolfgang Lehrach, Kevin P. Murphy
Google DeepMind
{xinghua,lazarogredilla,adedieu,cwendelken,wpl,kpmurphy}@deepmind.com

March 5, 2026

An agent is often defined as the combination of a specific LLM and a harness that acts as the "glue" or "plumbing" between the model and the task that needs to be solved. In this work, we propose "code as harness", a framework where the LLM itself completes the agent by coding its own harness. In its simplest incarnation, the harness can be seen as a control loop that calls the LLM and rejects unacceptable answers. The definition of what is acceptable is itself learned. This essentially results in a rejection sampler for LLMs in which the conditioning is learned based on the task.

LLM agents a

AutoHarness: improving LLM agents by automatically synthesizing a code harness

Xinghua Lou, Miguel Lázaro-Gredilla, Antoine Dedieu,
Carter Wendelken, Wolfgang Lehrach, Kevin P. Murphy
Google DeepMind
{xinghua,lazarogredilla,adedieu,cwendelken,wpl,kpmurphy}@deepmind.com

March 5, 2026

Lou, X., Lázaro-Gredilla, M., Dedieu, A., Wendelken, C., Lehrach, W., & Murphy, K. P. (2026). AutoHarness: improving LLM agents by automatically synthesizing a code harness. *arXiv preprint arXiv:2603.03329*.

5 Conclusion and Future Work

We developed a novel approach for improving the performance of an LLM agent, based on automatically synthesizing a code harness. Currently we generate a separate harness for each environment (game). In the future, we would like to distill the resulting domain specific experts (agents) back into the base LLM, so that the whole system becomes recursively self-improving. We also hope to explore building up a library of reusable harnesses, and to apply our method to more challenging multimodal games, such as Craftax [4] and Terra Nova [5].

Learning through weights and recursive self-improvement (RSI)

Parameter adaptation and RSI are important complementary techniques, but neither is synonymous with PDSI. Suggested further readings:

- Zweiger et al. (2025), Self-Adapting Language Models (SEAL) — Self-generated update directives and lasting weight adaptation; NeurIPS 2025.
- Zhao et al. (2025), Absolute Zero: Reinforced Self-play Reasoning with Zero Data — Self-proposed/verifiable training curricula; NeurIPS 2025, primarily a training paradigm, not automatically PDSI.
- Yin et al. (2025), Gödel Agent — Agent-side self-modification, self-referential design; ACL 2025.
- Zhang et al. (2025), Darwin Gödel Machine: Open-Ended Evolution of Self-Improving Agents — Empirically validated changes to an agent's own code, with archives of variants; relevant to RSI regardless of deployment timing.
- Shi et al. (2026), PluginRSI: Recursive Improvement of Agent Harnesses with Reusable Plugins — Evolves modular reusable agent-harness components (preprint).
- Ren et al. (2026), Self-Improvements in Modern Agentic Systems: A Survey — Contemporary model- vs scaffold-modification taxonomy; excellent secondary resource.

Takeaways

NELL: Long-horizon learning vision.

Lifelong Learning: Transfer across experience.

Continual Learning: Stability under updates.

LLM Agents: Harness, Interaction, tools, and memory.